

Douglas County Surveyor's Record of
Government Corners Renewed

25 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Francis L. Ingram, Deputy County Surveyor
John M. Powell
January, 1972
C. S. File 56/10 M 44 - 48

This corner set from resurvey of township line for T25-5 & T26-5 102
 $\frac{1}{4}$ Cor. for Sec. 34 T25-5 & Sec. 3 T26-5.
 Set - Brass cap at corner mkd: County Surveyors T 25 S
 (Steel fence post alongside) Office $\frac{1}{4}$ $\frac{S34}{S 3}$ R
 1972 T 26 S
 Bearing Objects: T Iron 1" x 36", N.39°E., 20.0 ft.
 T Iron 1" x 36", South, 20.0 ft.
 No BT's available. 1/19/72

This corner set from resurvey of township line for T25-5 & T26-5 103
 Section corner for Secs. 33 & 34 T25-5 and Secs. 4 & 3 T26-5.
 Set - Brass cap at corner mkd: County Surveyors T 25 S R 5 W
 (Steel fence post alongside) Office $\frac{S33}{S 4}$ $\frac{S34}{S 3}$
 1972 T 26 S R 5 W
 New BT's: 13" B.Oak, N.56°W., 42.2 ft. scribed T25S R5W S33 CS BT.
 14" D. Fir, N.67°E., 60.5 ft. scribed T25S R5W S34 CS BT.
 11" W. Oak, S82°E., 49.5 ft. scribed T26S R5W S3 CS BT.
 15" Maple, S.8°W., 46.0 ft. scribed T26S R5W S4 CS BT.
 East-west fence bears south 45.0 ft. 1/19/72

This corner set from resurvey of township line for T25-5 & T26-5. 104
 $\frac{1}{4}$ Corner for Sec. 33 T25-5 and Sec. 4 T26-5.
 Set - Brass Cap at $\frac{1}{4}$ Cor. mkd: County Surveyors T 25 S R 5 W
 Office $\frac{1}{4}$ $\frac{S 33}{S 4}$
 1972 T 26 S
 New BT's: 15" D. Fir, S.70°E., 18.3 ft. scribed $\frac{1}{4}$ S4 CS BT.
 15" Maple, N.11°W., 19.6 ft. scribed $\frac{1}{4}$ S33 CS BT. 1/21/72

This corner set from resurvey of township line for T25-5 & T26-5. 105
 Section corner for Secs. 32 & 33 T25-5 and Secs. 5 & 4 T26-5.
 Set - Brass cap at Sec. cor. mkd: County Surveyors T 25 S R 5 W
 Office $\frac{S32}{S 5}$ $\frac{S33}{S 4}$
 1972
 New BT's: 10" W. Oak, N.31 $\frac{1}{2}$ °W., 37.0 ft. scribed T25S R5W S32 CS BT.
 12" W. Oak, N.3°E., 37.3 ft. scribed T25S R5W S33 CS BT.
 12" W. Oak, S25°E., 15.2 ft. scribed T26S R5W S4 CS BT.
 10" W. Oak, S28°W., 40.6 ft. scribed T26S R5W S5 CS BT.
 Fence cor. bears S.40°E., 21.6 ft. 1/21/72

This corner set from resurvey of township line for T25-5 & T26-5. 106
 $\frac{1}{4}$ Corner for Sec. 32 T25-5 and Sec. 5 T26-5.
 Set - Brass cap at $\frac{1}{4}$ Cor. mkd: County Surveyors T 25 S R 5 W
 (steel fence post alongside) Office $\frac{S 32}{S 5}$
 1972 T 26 S
 New BT's: 12" W. Oak, N.54°E., 179.6 ft. scribed $\frac{1}{4}$ S32 CS BT.
 22" Triple Ash, S.10°W., 229.8 ft. scribed $\frac{1}{4}$ S5 CS BT.
 East-west fence bears South 18.0 ft. 1/21/72

This corner set from resurvey of township line for T25-5 & T26-5. 107
 Section corner for Secs. 31 & 32 T25-5 and Secs. 6 & 5 T26-5.
 Set - Brass cap at Sec. cor. mkd: County Surveyors T 25 S R 5 W
 (Steel fence post alongside) Office $\frac{S 31}{S 6}$ $\frac{S 32}{S 5}$
 1972 T 26 S
 FDOCK PER PIESKE
 MAY 1987 M104-20
 New BT's: 30" W. Oak, N.36°E., 78.6 ft. scribed T25S R5W S32 CS BT.
 13" W. Oak, N.33 $\frac{1}{2}$ °W., 97.0 ft. scribed T25S R5W S31 CS BT.
 13" W. Oak, S.30°E., 117.7 ft. scribed T26S R5W S5 CS BT.
 12" Ash, S.83°W., 133.7 ft. scribed T26S R5W S6 CS BT.
 This corner lies between 2 creeks, east 300.0 ft. west 130.0 ft. 1/21/72