

Douglas County Surveyor's Record of
Government Corners Renewed

25 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

~~Section Corner for Secs. 5 and 6, and Secs. 31, 32, T24-4
Set - 3/4" Iron pipe by single proportion.
Found - ~~stone~~ with X 10.0 ft. East of 1947 record. Ren. #2 of T24-4~~

7/76

Section Corner for Secs. 2, 1, 11 and 12.

132

Found - 1" I. Pipe with brass cap 10" above ground and firmly set, stamped "County Surveyor's Office" T25S R5W S2 S1 S11 S12 1960. Ren. #67
1" Orig. Oak 24" now 30" now uprooted and partially decayed. The root hole of the tree bears S.17 1/2°W., 60.7 ft. We open tree and find good reverse scribing "BT", actual face rotted out. All other orig. BT's are down and badly decayed.
An Oak 10" now 17" bears N.16°W., 27.4 ft. Tree has well healed double blaze. Ren. #21
A Madrone 10" now 12" bears N.38 1/4°E., 33.8 ft. Blaze and scribing have been destroyed.
A F. Fir 10" now 12" bears N.50°E., 20.4 ft. Tree has well healed double blaze. Ren. #67
A R. Fir 12" now 16" bears S.34°W., 12.0 ft. Tree has well healed double blaze. We partially open and find scribing "S11" (Record, S2).
A R. Fir 8" now 10" bears S.62°E., 20.1 ft. to center of base. (Rec. 21.2 ft. checks center trunk breast hight). Tree has well healed double blaze.
Fence corner bears N.72°W., 18.4 ft. (Rec. 19') Fence runs north and west.

Larry E. Monrean
Douglas County Surveyors Office
Pete Earle
March 31, 1977
C.S. 59/31

3/31/77

Section Corner for Secs. 10, 11, 14, 15.

133

Found - A 1" Iron pipe with 1960 Doug. Co. Brass cap facing south, set 1" below ground properly marked Removed brass cap and bent I.P.
A Sandstone (squared) rock on south side of BC 13"x10"x5", 8" below ground with 1" X chiseled on top.
An arched auto spring 31 1/2" x 1 1/2" x 3/8" 8" below ground.
Burned remains of Ash stump bears S.76 1/4°W., 99.0 ft. Southerly portion of a 2 forked Ash is rotted away, remains bear N.14°E., 97.0 ft. (Rec. N.13°E.) Ren. #57
An 11" Ash stump bears S.76°W., 98.5 ft.
A 5" now 11" Ash bears N.30 1/2°W., 56.6 ft. Open upper blaze and find fragmentary scribing.
Set - A new brass cap on a 36" I.P. 1" diam. 8" below ground stamped County Surveyors Office T25S R5W S10 S11 S15 S14 1977
Reset - Sandstone rock on south side of BC 1.0 ft. below ground.
Reset - Auto spring on north side of BC 8 ins. below ground.
New BT's - An Ash 10" bears N.14°E., 97.9 ft. marked "T25S R5W S11 CS BT"
A 2 forked Ash, 18" measured below fork, bears S.68°W., 146.8 ft. marked "T25S R5W S15 CS BT"
A 3 forked Ash, 25" measured below forks, bears S.80 3/4°E., 218.5 ft. marked "T25S R5W S14 CS BT".

R.B. Kimberling
P. L. Earle
Doug. Co. Surveyors Office
July 26, 1977
C.S. 59/38

7/26/77

1/4 Corner for Secs. 10 and 11.

134

Found - 1" I. P. with brass cap 1.2 ft. above ground marked "County Surveyor's Office" T25S R5W 1/4 S10 S11 1960. Corner is almost washed out in badly eroded East-West trail. Ren. #59
A 24" now 30" White Oak bears S.42 1/2°E., 100.3 ft. with rotted out blaze.
A 20" now 30" Fir stump bears S.85°W., 78.5 ft. with opened blaze and fragmentary scribing. (BT's set by Theil).
A 14" Fir stump bears N.61 1/2°W., 27.7 ft. with a well healed blaze.
A 15" Fir snag bears N.84°E., 18.6 ft. with a well healed blaze.
Set - Reset Brass cap 2.0 ft. below orig. ground, rechanneled ditch around brass cap. Stamped B.C. to read "Reset 1977"
New BT - A 14" White Oak bears N.88°E., 49.7 ft. double blazed and scribed "1/4 S-1 CS BT". Tree is at fence corner West and North.
Note: Corner is 10 ft. South of E-W fence.

R. B. Kimberling
M. W. Cline
Doug. Co. Surveyors Office
Sept. 26, 1977
C.S. 59/40

9/26/77

(No Ren. #135)

Fd. B.C.
8/90
M110-46