

Douglas County Surveyor's Record of  
Government Corners Renewed

25 T.S. 6 R. W. W. M.

B.B. Irving  
County Surveyor  
1-15-45. *C.S. File 38/5*

NORTHEAST CORNER WILLOUGHBY CHURCHILL D.L.C. NO. 38

Set  $1\frac{1}{2}$ " x 42" I. Pipe  
Marked a B. Oak S. 38° W. 28.7 ft. **SEE CORNER NO. 61**

S.W. COR. OF D.L.C. # 56 DAVID HUNT

Renew from old Gov. B.T's. Set in a  $\frac{3}{4}$ " x 30" Iron Bar,  
from which:  
A 40 in. W. Oak bears N. 57° E., 81.5 ft.  
A 30 in. W. Oak bears N. 16° W., 175 lks. **SEE CORNER NO. 74**

N.W. OF THE C. BARRETT CL. 54

Renew form old B.T's. - SEARCHED FOR, NOT FOUND - APRIL 1964 - C.S. 49/123  
Set in a 1" x 48" G.I.P. from which  
A 24" W. Oak bears S. 20° E., 68 ft.

COR. OF 14-15-22-23.

Renew from old Gov. B.T's. Set in  $1\frac{1}{2}$ " x 30" Galv. Iron  
Pipe from which:  
All old Gov. corners bear as given. I remarked all  
old trees. **SEE CORNER NO. 87**

S.W. CORNER OF C. BARRETT D.L.C. 54

Renew from old Govt. B.T's. Set in a  $\frac{3}{4}$ " x 2" x 30" Iron  
Bar from which  
A 12" W. Oak bears N. 47° E., 14 lks.  
A 14" W. Oak bears S. 37° E., 36 lks. **SEE CORNER NO. 156**

COR. BET. SECS. 10 and 11.

Renew from old B.T's both standing marks plain. I set a  
 $10$ " x  $10$ " x  $10$ " sand stone and drove an 8" x 30" Charred  
Stake from which:  
A 20" Fir marked C.S.  $\frac{1}{2}$  S.B.T. bears N.  $11\frac{1}{2}$ ° E., 8 lks. **SEE CORNER NO. 90**

N.W. COR. OF G. VAN RIPER D.L.C. # 52

Renewed from old B.T's both standing and in good condition  
I remarked same and set a  $1\frac{1}{2}$ " x 40" Iron rod for corner. **SEE CORNER NO. 94**

SEC. COR. COMMON TO 2-3-10-11.

Reset from one O.B.T. and 1 stamp of O.B.T. Set Sandstone  
with x cut in it. Marked a  
6" Pine S. 15° W., 135.0 ft.  
12" W. Oak S. 64° E., 63.0 ft. (O.B.T.)  
16" W. Oak N 38° E., 116.0 ft.  
No other trees suitable. **SEE CORNER NO. 95**

COR. BET. 2/3

Reset from one B.T. standing and dead; and one O.B.T. fallen  
Set sq. Oak Post for corner Marked  
16" Fir N. 63° E., 32.0 ft.  
18" Fir S. 59° W., 15.6 ft. **SEE CORNER NO. 102**

SEC. COR. COMMON TO 3-4-9-10.

Reset form one O.B.T. others gone. Set Rock for corner.  
Marked  
A 48" Fir S. 58° W., 25.0 ft.  
A 8" Fir N. 68° E., 14 ft.  
A 24" Fir N. 19° W., 24.6 ft.  
A 15" Fir S. 2° E., 35.0 ft. (O.B.T.)  
**SEE CORNER NO. 108**

COR. BET. 3 and 4.

Reset Cor. form Laurel, O.B.T. badly rotted, other B.T.  
gone. Set rock for corner. Marked  
6" Fir N. 51° W., 4.0 ft.  
10" Fir S. 10° E., 12.0 ft. **SEE CORNER NO. 106**

COR. BET. 3 and 10. - SEARCHED FOR - NOT FOUND - JAN. 1963 - C.S. 49/123

Re-established midway between 2-3-10-11 and 3-4-9-10.  
Set 4" sq. Oak Post. Marked  
24" Fir S. 33° E., 24.8 ft.  
18" Fir N. 42° W., 11 ft.

Frear D.C. Frear F.C. Frear T.C. Frear  
H.J. Cole Wit. D.C.S. Dep. Co. Sur.  
J.A. Cole F.A. Bemis Wit. Oscar Gar. Wit.  
Wit. C Bemis J.E. Winniford Scott Henry  
C.E. Keyser J.B. Large C.E. Miller Henry  
Oct. 28, 1919 Jan. 30, 1919 Apr. 10, 1919  
3/22/22 Vol. 3, Page 113 C.S. File 2/14  
3/24/22  
G.G. Stewart Deputy  
Wit. Fay and J.H. Leatherwood  
Geo. McGugly  
E.E. Goodman  
N.J. Baird  
J.G. Stewart D.C.S.  
J.H. Leatherwood  
N.J. Baird  
Geo. McGugly

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12