

Douglas County Surveyor's Record of  
Government Corners Renewed

25 T.S. 6 R.W.W.M.

Ben B. Irving Dep. Co. Sur.  
Co. Rdmstr May 9, 1931  
J. Wolford Wit. N.E. Richardson  
P.D. Wolford Cecil Fessler  
B. Lane  
Nov. 22, 1932  
C.S. FILE 37/45

F.C. Frear Ben B. Irving Dep. Co. Sur.  
Co. Rdmstr May 9, 1931  
J. Wolford Wit. N.E. Richardson  
P.D. Wolford Cecil Fessler  
B. Lane  
Nov. 22, 1932  
C.S. FILE 37/45

H.L. Eppstein C.E. Roberts  
Wit. G.G. Stewart  
Nov. 4 1908  
SEE F.B. 7, P. 76

Apr. 18, 1936 H.L. Eppstein C.E. Roberts  
A. Boyer DCS. Wit. G.G. Stewart  
Wit. W. Cook  
Joe Winniford  
Nov. 4 1908  
SEE F.B. 7, P. 76

Ben B. Irving Dep. Co. Sur.  
Surveyor  
Witnesses  
N.E. Richardson  
Jas McHugill  
M11-10  
C.S. FILE M11-10

- N.E. COR. NICHOLAS DAY D.L.C. # 40. 22  
Location identified from stump of orig. B.T. Letters B.T.  
in good condition. Set Oak Post 4" x 4" x 36"  
10" W. Oak S.55°E., 94 lks. blazed and scribed 157  
S.E. Cl. 40 C.S.B.T.  
10" B. Oak N.84°W., 9 lks. blazed and scribed  
S.E. Cl. 40 C.S.B.T.
- S.E. COR. THOMAS WATSON D.L.C. # 41 - FD 1 1/8" DIAM. STEEL SHAFT AT COR. APR. 1964  
BETH. B.T.'S. GOOD CONDITION, M.C. 23  
Location identified from snag of one O.B.T. letters legible  
but badly rotted and stump which checked location of other  
O.B.T. Set Oak Post 4"x4"x36"  
30" W. Oak S.32°W., 62 lks. Scribed S.E. Cl. 41 C.S.B.T.  
10" W. Oak N.41°E., 18 lks. Scribed S.W. Cl. 41 C.S.B.T.
- 1/4 COR. 11 and 14. - SEE SEARCHED FOR NOTES IN C.S. 49/123. - WRONG -  
CORNER - 24  
Reset from 1 old B.T. Marks plain set 1 1/2" x 30" Iron Bolt  
with nut from which  
A 30" W. Oak bears S.57 1/4°E., 685 ft. 30" W. Oak, S.75 1/2°W.  
548° other trees destroyed, set plow share along field fence  
WRONG TWP. & RANGE
- N.W. COR. N. DAY D.L.C. # 40 - SEARCHED FOR - East 150ft. - NOT FOUND 4/21/64  
Reset N.E. Cor. N. day claim from stump of tree. Reset S.E.  
Cor. Watson Cl. 4.17 chs. W. of Day cor. Ran W. 75.71 from  
S.E. Cor. Cl. 41 to river set post marked C.S. Cl. 40 Cl. 53  
from which:  
REFER TO F.B. 7, P. 76  
A B. Oak 17" dia. bears S.6°E., 97 lks.  
A W. Oak 8" dia. bears N.49°W., 65 lks. 25
- COR. SECS. 31-32-5-6. T 25 S R L W & T 26 S R L W 26  
Reset S.E. Cor. 31 Sandstone 8x6x16 in. marked C.S. Witness  
trees cut down markings still legible. SEE CORNER NO. 66
- 1/4 COR. BET. SECS. 30 and 31. - SEARCHED FOR. NOT FOUND - 7-1963. 11/23 NORTH  
Reset 1/4 cor. Bet. 30 and 31. Sandstone 6x6x14. Ran south from  
same 13.50 set stake. Witness Ash 15" dia. N.43 1/2°W., 30 lks  
18.71 ft. 27
- 1/4 COR. BET. 17 and 20. 28  
Stake set by G. G. Stewart on Jan. 25, 1923. Marked #99  
A 14" Fir N.66°W., 29.0 ft.  
A 6" W. Oak S.9°W., 17.2 ft.
- SEC. COR. 28, 29, 32 and 33. 29  
Reset from stump of orig. B.T. in Sec. 32. Other B.T.'s  
destroyed. Marked New B.T.'s as follows:  
W. Oak 12" dia. N.75°E., 32 ft.  
W. Oak 8" dia. S.16°E., 11.4 ft.  
B. Oak 12" dia. S.44°W., 9.4 ft.  
Fir 13" dia. N.30°W., 34.4 ft.
- N.W. CORNER OF THE E. WILLIAMSON D.L.C. #48 30  
Location identified from an Oak stake bearing correct scribe  
marks. This evidently the corner as renewed by surveyor  
Briggs in 1892, although the bearing trees are down and butt  
sections burned off. Checks for bearing and distance. Drove  
a 4" Iron Pipe alongside. Blazed and scribed 155  
An Oak 42" diam., S.60°W., 44.0 ft.
- S.E. COR. OF THE E. WILLIAMSON D.L.C. #48 - SEARCHED FOR - NOT FOUND 31  
All evidence of the original corner destroyed or obliterated  
A 4" x 36" Iron Pipe set for corner by proportional measure-  
ments between the S.W. Cor. of D.L.C. # 48 and the N.E.  
Cor. of D.L.C. # 59. No trees or objects available for  
reference.
- N.E. CORNER OF THE E. WILLIAMSON D.L.C. # 48 32  
All evidences of the original corner and of the corner set  
by Surveyor Briggs in 1892 have been destroyed or obliterated  
A 4" x 36" Iron Pipe driven for the corner using proportion  
distance as obtained and computed through the tie given in  
the deed of the properts (S.W. Cor.) now owned by C. A. Goff  
and distances as called for in the original description of  
D.L.C.'s # 46, 47 and 48.  
An Ash 16" diam. bears N.87°W., 92.7 ft.  
SEE ALSO #53  
- OVER -