

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 25 S. T. S. R. 6 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

89

$\frac{1}{4}$  Corner to Sections 20 and 21.  
Found - W. Oak, now 32", N.9°E. 258.7 ft. Cut open & fd. good scribing, "B".  
W. Oak, now 34", N.3 $\frac{1}{2}$ °W. 249.5 ft. No scar visible. Did not open.  
Both Old Bearing Trees in good condition.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962  
T25S R6W  $\frac{1}{4}$  S20/S21  
New BT's: 17" W.Oak N.30°W. 39.8 ft. Mkd:  $\frac{1}{4}$  S20 CS BT.  
36" D.Fir N.25°E. 69.8 ft. Mkd:  $\frac{1}{4}$  S21 CS BT.  
Fence Corner bears West 4 feet, (Fences North & East).

90

$\frac{1}{4}$  Corner to Sections 10 and 11.  
Found - Black Oak, now 30", almost dead, S.54°W. 18.5 ft. Cut open &  
find good reverse scribing (old) " $\frac{1}{4}$ S". More recent scribing "BT".  
Stump Hole & Fragments of Rotten Oak Wood N.88°E. (not N.83°E.)  
40.9 ft. Found reverse scribing on fragment of wood "4".  
Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1962  
T25S R6W  $\frac{1}{4}$  S10/S11  
New BT's: 10" D. Fir S.12°E. 26.4 ft. Mkd:  $\frac{1}{4}$  S11 CS BT.  
19" W.Oak S.60°W. 28.1 ft. Mkd:  $\frac{1}{4}$  S10 CS BT.  
A fence corner - fences E.-W.-S.- bears N.77°W. 5.0 ft.  
A 30" Doug. Fir Stands 5 feet directly North of Corner. - REN. No. 6

91

Section Corner to Sections 5 - 6 - 7 - 8.  
Found - No Orig. BT's. Germond's & Springer's, now 26" R.Fir N.49°40'E.  
20.5 ft., shows scars. I do not open. Springer's 48", now 54"  
Fir S.16°E. 34.0 ft. Open & find good scribing. - Cor. #17-5042  
Also find Springer's 6", now 14" W.Oak N.71°W. 253.6 ft.,  
shows faint scar. I do not open.  
Set - Brass Cap Mkd: County Surveyor's Office, 1958  

S 6	S 5
S 7	S 8

 T25S R6W  
New BT's: 7" B.Oak bears N.83°W. 20.0 ft. scribed T25S R6W S6 CS BT.  
6" R.Fir bears S.34°E. 58.5 ft. scribed S8 CS BT.  
14" R.Fir bears S.64°W. 79.6 ft. scribed S7 T25S R6W.

October 11, 1962 - Found Brass Cap for corner above  
Found - 7" B. Oak N.83°W. 20.0 ft. Tree alive. 

S 6	S 5
S 7	S 8

  
All other trees found or scribed in 1958; dead & down.  
New BT's: 4" D.Fir N.33°E. 44.2 ft. Mkd: "S5 CS BT".  
10" D.Fir S.83°E. 65.5 ft. Mkd: T25S R6W S8 CS BT.  
8" B.Oak S.37 $\frac{1}{2}$ °W. 57.2 ft. Mkd: T25S R6W S7 CS BT.

92

N. E. Corner D. L. C. No. 52.  
Found - 24" W. Oak N.50°W. 14.5 ft., top scar previously opened &  
face rotted. Cut open lower scar & fd. perfect scribing "BT".  
No trace of N. E. tree.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962  
T25S R6W NE DLC 52  
New BT's: 10" W.Oak S.45°W. 17.7 ft. Mkd: NE DLC 52 CS BT.  
14" D.Fir S.88°E. 28.3 ft. Mkd: NE DLC 52 CS BT.  
Found - Sandstone, 4" x 5" top, nearly flush with ground. N.20°E. 1.5 ft.  
from corner I set, appears to have been set for corner at  
some previous time.

93

$\frac{1}{4}$  Corner to Sections 5 and 8.  
Found - Sandstone Rock, 14" x 14" x 5", in fence corner. This rock  
mentioned by Germond in 1909. 15043  
32" W.Oak bears S.21°W. 21.8 ft. This tree was cut open years ago.,  
center completely gone now, no scribing found.  
Stump Hole bears N.3°W. 21.1 ft.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962  
T25S R6W  $\frac{1}{4}$ 

S 5
S 8

  
New BT's: 15" W.Oak N.28°E. 46.8 ft. Mkd:  $\frac{1}{4}$  S5 CS BT.  
6" W.Oak S.67 $\frac{1}{2}$ °W. 114.7 ft. Mkd:  $\frac{1}{4}$  S8 CS BT.  
Corner lies in fence corner, fences North, East & S.66°W. from corner.

Milo E. Godfrey, Deputy County Surveyor  
Vernon Tracy  
Mike Stone  
August 1962  
C. S. File No. 49/123

October 10, 1962