

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 6 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

N. W. Corner D. L. C. No. 58.

159

Found - $\frac{3}{4}$ " Pipe in line with fence running east, Ren. #36.
Ash Stump N.50°E. 35.0 ft., good scribing found, "BT".

New BT's: 12" Ash N.68°E. 45.1 ft. Mkd: N. W. DLC 58 CS BT.

10" Ash N.61 $\frac{1}{2}$ °E. 52.0 ft. Mkd: N.W. DLC 58 CS BT.

Found - $\frac{3}{4}$ " Bolt with square head 2.4 ft. south of $\frac{3}{4}$ " Pipe.

A telephone pole marked 32-55-16R 2 bears S.88°E. 23.8 ft.

Apr. 24, 1964

S.W. Cor. D.L.C. No. 41 & S. E. Cor. D.L.C. No. 62.

160

Found - 57" Black Oak N.30°E. 166.3 ft., opened & found reverse scribing "62".

Set - Brass cap at Cor. Mkd: County Surveyor's Office, 1964

T25S R6W SE DLC 62/SW DLC 41

New BT's: 16" White Oak S.69°E. 77.9 ft. Mkd: SW DLC 41 CS BT.

12" White Oak N.87°E. 59.0 ft. Mkd: SE DLC 62 CS BT.

Note - A fence corner (fences East & North) bears East approx. 75 ft.

Apr. 29, 1964

Int. "L" Cor. DLC #48 & Most Stherly S.E. Cor. DLC #47.

161

Found - $\frac{3}{4}$ " Iron Pipe, 4" below present ground surface. See Ren. #33.

9" White Oak S.24°E. 161.6 ft., very plain scar.

Corner at old fence corner, traces of old fences West & North.

New BT: 18" Doug. Fir S.71°E. 36.4 ft. Mkd: Int. "L" DLC 48 CS BT.

N.E. Corner D.L. C. # 49.

162

Found - Rock 12" x 12" x 5" above ground, with $\frac{3}{4}$ " pipe driven along side. (Ren. #35)

New BT: 21" White Oak N. 25° E 69.0 ft. Mkd: "NE DLC 49 CS BT"

Corner is in fence corner-fences south & east from corner.

Milo E. Godfrey, Deputy County Surveyor
Wm. Stoffel - M. Stone - M. Darby
April - May 1964
C. S. File No. 49/123

163

Sec. Cor. to Secs. 35 & 36, T25-6W. & Secs. 1 & 2, T26-6W.

Found - 16" Oak, standing but dead, S. 81° W. 229.0 ft. Cut open and found good reverse scribing "R6W T26S". Orig. face rotted, overgrowth dead.

Portion of Oak Stump S. 74° E. 54.8 ft., found overgrowth of old face, badly rotted, no scribing visible.

No trace of N. W. nor N. E. BT's.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963

T25S	R6W	S 35	S 36
T26S	R6W	S 2	S 1

New BT's: 13" D.Fir N. 45° W. 26.2 ft. Mkd: T25S R6W S35 CS BT.

8" D.Fir S. 52° W. 43.8 ft. Mkd: T26S R6W S 2 CS BT.

10" D.Fir S. 73° E. 52.4 ft. Mkd: T26S R6W S 1 CS BT.

16" D.Fir N. 13° E. 68.3 ft. Mkd: T25S R6W S36 CS BT.

Note - $\frac{1}{2}$ " Pipe & Cedar Stake in E. - W. Fence Line bears S. 29° E. 49.8 ft.

July 1963

164

Center of Section 7.

Set - $\frac{3}{4}$ " Iron Rod for Corner.

Bearing Tree: 12" Fir bears N. 85° 30' W, 47.6 ft. scribed C $\frac{1}{4}$ S 7 BT.

April 7, 1966

Don E. Garrett
For. J. Barnes
Map File
M 31 - 44

MICROFILM TO HERE 10/67

SEPT. 68