

Douglas County Surveyor's Record of  
Government Corners Renewed

T 25 - T. S. R 6 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21681

177

Glenn Baughman  
for Bill Escalle  
October 1974  
M 49 - 76

Section Corner for Sec. 31; and Sec. 1 of T26-7; and Sec. 36 of #181  
T.25-7; and Sec. 6 of T26-6.  
Set - Brass cap on a 1" L.P. on the inside edge of a dike of a farm pond  
approx. 15' from lower edge of a steep bank between field and  
lower field terrace.  
BT - Only one tree close to corner which I scribed:  
42" Oak, bears N.61°W., 46.0 ft. scribed S36 BT.

JAN '75

Section corner for Secs. 7, 8, 18, and 17.

178

Don E. Garret  
For: Don Kerbo  
April, 1975  
M 55 - 75

Set - 1 1/2" I. Pipe  
BT's - 10" Madrone, bears N.19°W., 17.4 ft. scribed S. 7 BT  
4" Madrone, bears N.33°E., 23.3 ft. scribed S 8 BT  
4" Madrone, bears S.70°E., 18.9 ft. scribed S 17 BT  
15" Madrone, bears S.35°W., 15.6 ft. scribed S 18 BT.

4/75

179

1/4 Corner for Secs. 18 and 17.

Set - 1 1/2" Iron pipe  
BT - 11" Oak, bears S.33 1/2°W., 27.2 ft. scribed 1/4 S 18 BT.

4/75

1/75

Robert W. Wade  
For: City of Sutherlin  
and Mrs. Harry  
Baimbridge  
M 61 - 47 Sept. 1976

Southwest Corner, Williamson D.L.C. #48  
Set - 1/2" Iron pipe.  
(Point is N.89°54'W, 433.47' measured distance from the NW Corner  
of DLC #58)

180

9/17/76

Sec. Cor. for S. 31; Sec. 36 of T25-7; Sec. 1 T26-7; Sec. 6 T26-6  
Found - Brass cap 6" above ground on a 1" I.P. and stamped OLS 536

181

R T25S R  
6 S 36 S 31 5  
W S 1 S 6 W  
T26S  
1974

Brass cap is on inside edge of a dike for a pond.  
Ren. #177

We stamped correction on BC to read "OLS 536"

	T25S		
R	S 36	S 31	R
76	S 1	S 6	36
W	T26S		W
	1974		
	CS 1977		

Found - A 42" Oak, now down bears N.61°W., 46.0 ft. double blazed and  
scribed "S36 BT".  
Set - A metal fence post with survey marker sign 1.0 ft. north of B.C.  
A 5/8" I. Rod 30" long 3" above ground with an alum. cap stamped  
"B.O. 1", bears N.24°E., 74.0 ft.  
Set a metal fence post with survey marker sign 1.0 ft. west of I.R.,  
point is on top of dike at west side of pond.  
Set a 5/8" I.R. 30" long 4" above ground with an alum. cap stamped  
"B.O. 2", bears S.4°W., 105.8 ft. Set a metal fence post with  
survey marker sign 1.0 ft. west of I.R., point is on edge of  
upper field.  
A 7" Pear tree bears N.67°W., 107.3 ft. double blazed and marked  
T25S R 7 W S36 CS BT"

6/28/77

182

Romanso E. Ware  
For: Gail Winniford  
Oct. 1977  
M 67 - 51

Section Corner for SEcs. 20, 21, 29 and 28.  
Set by double proportional measurements.  
Set - 3/4" Iron pipe.  
B.O's - Peak on South end of Henry hay barn bears N.42°18'20"E., 700 ft. +  
Power pole #A4563 bears S.9°46'E., 303.9 ft.  
Corner lies 15 ft. west of small season creek.

10/77

183

Glenn Baughman  
For: John Tilley  
May 1978  
M 70 - 18

Center 1/4 Corner for Sec. 19  
Set - 5/8" Iron Rod  
From Which:  
28" Madrone bears S.41°E., 30.0 ft. scribed C 1/4 S19 BT.  
46" Oak bears S.47°W., 74.2 ft. scribed C 1/4 S19 BT.

5/78

R. B. Kimberling  
P. L. Earle  
Douglas Co. Surveyors Office  
June 28, 1977  
C.S. 59/34