

Douglas County Surveyor's Record of
Government Corners Renewed

T 25 T. S. R 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

184

1/4 Corner for Secs. 18 and 19.
Found - Orig. 26" Oak, now 56", bears N.88°30'E., 87.0 ft. scribes visible.
Orig. 30" Oak, down, bears S.76°30'W., 59.4 ft. to root hole.
Set - Brass cap
New BT's- 9" D. Fir bears N.12°W., 27.7 ft. scribed 1/4 S18 BT.
10" D. Fir bears S.83°E., 12.6 ft. scribed 1/4 S19 BT.

Glenn Baughman
For: John Tilley
May 1978
M 70 - 18

5/78

185

Section Corner for Secs. 31 and 32; and Secs. 5 & 6 of T.26-6
Found - A 9"x9"x17" Rock marked "CS" on North face. Ren. #26
A 5/8" I. Rod set next ot rock. (unrecorded)
A root hole bears S.20°W., 32 ft. (orig.)
A 4" Oak bears S.72°E., 11.1 ft. tree down and rotted. Ren. #66
A 10" B. Oak, now 14" bears N.7°E., 61.3 ft. with well healed double blaze.
A 10" Madrone now 14" was removed by cat work has tag and shows good scar.
A 6" Madrone, now 10" trunk on triple trunk tree bears N.38°W., (rec. N.36°W.) 38.8 ft. to face, 39.8 ft. to center of base, with well healed double blaze. Ren. #66
Set - A 1" x 36" Pipe with brass cap marked "Douglas County Surveyor" T25S S31 S32 S6 S5 T26S R6W 1979. Cap 5" above ground, Rod 9" above ground, in position of stone. Placed stone next to cap and rod east side of cap.

Karen Reed
S. J. Flause
Doug. Co. Survey-
ors Office
March 15, 1979
C.S. 60/24

New Accessories:

A 12" Madrone bears S.31°E., 50.4 ft. scribed "S5 T26S R6W CS BT" in double blaze.
A 11" Oak bears S.33°W., 158.5 ft. scribed "S6 T26S R6W CS BT" in double blaze.

3/15/79

186

1/4 Corner for Sec. 2 and Sec. 35 of T.24-6
Set - 5/8" Iron rod
BT's - An 8" Fir, N.27°W., 31.1 ft. scribed "1/4 S35 BT"
A 20" Fir, S.27°E., 11.0 ft. scribed "1/4 S2 BT".

Romanso E. Ware
For: Gary Barnett &
Roseburg Lumber
April 1979
M 70 - 59

187

Section corner for Secs. 14, 15, 22 and 23.
Found - A 1962 County brass cap on a 1" I.P. protruding 0.8 ft. above ground properly marked. Ren. #87
An orig. 18" Y. Oak, now a 30" x 4.5 ft. stump bears N.68°W., 25.1 ft.
An orig. 18" Y. Oak, now a 30" B. Oak, bears S.23 1/2°W., 67.3 ft. Faint scar visible.
An orig. 40" W. Oak, still 40" bears S.33°E., 36.6 ft. (Rec. 35.0 ft.) This is a face meas.) Tree has been previously chopped out faint scribe marks visible.
An 18" B. Oak, now 21" with healed over double blaze bears S.52°E. 13.0 ft. Ren. #87
A 9" Madrone, now an 11" with well healed double blaze bears S.70°W., 41.8 ft. (Rec. 41.0 ft.) Ren. #87
A 9" W. Oak still 9" with well healed double blaze bears N.10°W., 14.8 ft. Ren. #87
A 6" W. Oak, now 7" with well healed double blaze bears N.46°E., 18.2 ft. Ren. #87

Karen Reed
Deputy, Doug
Co. Surveyor
Office
Terrie Plouf
Teresa Buley
Oct. 14, 1980
C.S. 61/11

Left cap in place. Tagged all BT's.
Corner lies 1.7 ft. N. of an E-W. fence approx. 40 ft. west of ridge top.
1" I.P. set by Frear no found. Ren. #4

10/14/80

188

1/4 Corner for Sections 16 and 17.
Found - A stone & a 2 1/2" DCSO brass cap on a 1" I.P. protrude 7" and 8" respectively, from the soil; both monuments are firmly set, the brass cap is leaning slightly west and is on the east side of the stone. The cap is marked properly. The stone (unrecorded when set) is exposed and found to measure 6x6x21 inches long & marked 1/4 S on the east face. (stone is covered again & soil firmed)

BT's- This area has re-ently been cleared for pasture, most trees and stumps have been removed & land has been graded. A thorough