

Douglas County Surveyor's Record of
Government Corners Renewed

T 25

T. S.

R 6

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

196

Section Corner for SEcs. 31 and 32; and Secs. 5 and 6 of T.26-6
Found - A 2½" dia. 1979 DCSO brass cap on a 1¼" O.D. I.P. protrudes
6" out of ground, now bent approx. 12" north of plumb. Ren.#185
5/8" dia. Iron rod, protrudes 9" out of ground, now bent approx.
15" north of plumb. (source unknown)
9" x 9" x 17" stone, no marks visible found approx. 2.0 ft. North
of DCSO BC/IP's plumb position (possibly from Ren. #66)
Above 5/8" iron rod found along North side of BC/IP.
(Bearings and distances taken to plumb position of DCSO brass cap):
10" now 14" B. Oak with a fully healed double blaze bears
N.8½°E., 59.9ft. (Rec. N.7°E., 61.3 ft. slope dist.) From
Ren. #66
6" now 14" madrone with fully healed blazes bears N.36°W.,
38.8 ft. (agrees w/rec. Ren. #66)
12" now 14" madrone with partially healed double blaze scribing
visible 'T26S R6W" bears S.31°E., 50.4 ft. Ren. #185
11" now 14" Oak with fully healed double blaze bears S.34½°W.,
158.5 ft. (Rec. S.33°W., 158.5 ft.) Ren. #185
Set - Position of bent DCSO BC/IP is referenced. BC/IP is straightened
and returned to referenced position. BC/IP now protrudes
3" above ground. 5/8" I.R. is straightened and set along
North side of DCSO BC/IP. 5/8" I.R. now protrudes 1" above
ground. Stone is placed along East side of DCSO BC/IP.
BC/IP measures 36". 5/8" iron rod measures 50" long.
Corner lies on a NW-SE running ridge on a bench approx. 50 ft. North of
a dirt road.

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
Jan. 31, 1990
C.S. 64/5

1/31/90

197