

Douglas County Surveyor's Record of
Government Corners Renewed

25 T. S. 7 R. W. W. M.

1/4 COR. BETWEEN 15-16

28

Run S 10° W 90 lks. from trunk of fir tree which answers description of B. T. I drive a 1" x 60" pipe and marked the following trees;
24" Red Fir N 65° W 22.0 ft.
6" W. Fir S 10° E 6.0 ft.
18" W. Fir S 56° E 47.0 ft.
See File 40/227 for method of setting before using corner.

Percy C. Armstrong
March 24, 1949
CS 40/227

SOUTH WEST CORNER OF D.L.C. # 54 (HURST #56)
New bearing tree, scribed

T 25-6

H.E. Croeder
Surveyor, Wally M. Hector
May, 21, 1951

1/4 CORNER SECTIONS 26 and 27

29

From bearing tree S89W 683.0 ft. I set a 3/4 x 40" Bolt 36" in ground and checked this setting from a bearing tree S 11 W 395.0 ft. set bt Mr. Boyer. see Re.N. #4 & CS 32/35

RE-RENEWED, SEE CORNER NO. 86

H.E. Crowder
Witness Babcock
Merrill
Gorman
Surveyor - Wally Hector
Nov. 16, 1951
CS 44-47

N. W. Corner D. L. C. No. 37.

29-A

Set a Stone 6" x 8" x 15".
New BT's: Black Oak 7" N. 57°W. 20 lks.
Black Oak 7" S.66°E. 45 lks.

See Volume 2, Page 86

Oscar Thiel
March 8, 1900
CS Vol. 2,
page 86