

Douglas County Surveyor's Record of  
Government Corners Renewed

25

T. S.

7

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

Claude Kerr - November, 1953 Filed in surveyors file no. 41/228

Claude Kerr, 1954.  
See C. S. File 41/316.

North section cor. for secs. 16 and 17.

30

Found the two original BTs.

A 14" Laurel, bearing S79°E., for 29.0 ft.

A 26" Fir bearing S46°W., for 19.0 ft.

Set 3"x3"x4' stake for the corner.

The corner for sections 8 and 9 is 145.0' to the east.

RENEWED, SEE CORNER NO. 55

$\frac{1}{4}$  corner for secs. 9 and 16. Found one orig. BT, now a 30" stump. Chopped into old face and found the markings.

31

I set the corner from this original BT. Set a stake with a  $\frac{1}{2}$ "x $\frac{1}{2}$ "x18" steel rod alongside, from which two new BTs-

A 13" W. Fir bears N20°E for 4.3', scribed S39 BT.

A 13" W. Fir bears S33°W for 2.6', scribed S16 BT.

RENEWED, SEE CORNER NO. 55A

The section cor. for secs. 9, 10, 15, and 16. Found two orig. BTs, from which a 3"x3"x4' Myrtle stake was set for cor., from which-  
The orig. BT 30" Fir (now a 53" fir) bears S70°W for 27.7 ft., old marking visible. Rescribed this tree S16 BT.  
Original BT 24" Fir bears N5°W (now a 48" Fir) for 39.6 feet old marking visible, was rescribed by us S9 BT.

32

A 37" Fir not mentioned in field notes, with scribing visible was found, bears N68°E for 31.5 feet.

Marked a new BT, a 10" W. Fir bearing S.80°E. for 32.5 ft., marked S15 BT.

The  $\frac{1}{4}$  corner to secs. 16 and 17.

33

Found both orig. BTs-

A 46" Fir bearing S46°E for 42.2 ft.

A 24" Fir bearing S38°W for 30.4 ft.

I set a 3"x3"x4' Fir post for the  $\frac{1}{4}$  corner.

SEE ALSO COR. # 39

RENEWED, SEE CORNER NO. 97

The corner 16, 17, 20, and 21.

34

Found a 26" Fir with scribing instead of the 12" Laurel as called for in field notes. Faces properly for the orig. BT.

Set a 6"x8"x12" stone for corner from the BT. Stone marked with 2 notches on South side and 4 notches on north side, from which,

Original 26" Fir, bears S80°W for 18.5 feet.

New BT, a 5" Fir bears N18°W for 11.4', marked S17 BT

New BT, a 16" maple, bears South for 10.5', marked S21 BT

New BT, a 6" Fir, bears N11°E for 22.5', marked S16 BT.

MARCH 1967 - FOUND O.K. - V.R.T.

$\frac{1}{4}$  corner to secs. 7 (T25S, R7W) and 12 (T25S, R8W).

35

Found the original Oak B. T., now 37" in diameter, bearing N.6°30'W.,

for 81.0 lks. Chopped in and found BT scribe marks. Refaced the tree and marked it with  $\frac{1}{2}$ " S 12 BT. I set a Cedar stake for the  $\frac{1}{4}$  corner with a  $\frac{1}{2}$ " pipe alongside.

Marked a new BT - On the North side of the county road.

A 24" Oak, bearing S. 89° E. for 239.5 feet, marked  $\frac{1}{2}$  S 7 BT.

Witness Corner a line between Sections 7 ( T25S, R7W) and 12(T25S, R8W) at 58.95 chains south.

36

Found the original Fir BT, now 50 inches in diameter, bearing S.80°E. for 10 lks. (Marking still visible).

Reset the Witness Corner from this BT setting a 4"x4" stake, which I scribe W. C. on the east and west faces, and 58.75 Chs. S. on the North face.

Marked a new witness tree:

A 14" Red Cedar, bearing N.55°W. for 19 feet and marked W. C. S. 12 BT.

The  $\frac{1}{4}$  corner for 7 and 12 can be seen from the W. C. at 58.95 chains South. The correct variation between these corners is 20°20' East.

RENEWED, SEE CORNER NO. 69