

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

84

Vernon "Ray"
Tracy &
June 14, 1966
C.S. File
No. 54/10

$\frac{1}{4}$ Corner to Sec. 33, T25-7W. & Sec. 4, T26-7W.
Found - Orig. 24", now 33" Laurel S. 60° W. 18.5 ft., prev. opened,
upper face rotted away. Open lower & find "B" scribe reverse.
Ring count impossible, being too closetogether.
Orig. 12", now 30" Fir N. 80° W. 19.8 ft., shows very old scar
& renovation scar.
Set - Brass Cap 2.0 ft. N.W. of fence corner, course E. & S. Mkd:
County Surveyor's T25S R7W S 33
Office, 1966 T26S S 4
New BT's: 14" D. Fir S. 9 $\frac{1}{2}$ ° W. 27.0 ft. Mkd: $\frac{1}{4}$ S 4 CS BT.
6" W. Fir N. 47° W. 33.9 ft. Mkd: $\frac{1}{4}$ S33 CS BT.
Note - Corner lies approx. 100 ft. W. of small draw, course S. E.

85

C. S.
File
No.
54/10

$\frac{1}{4}$ Corner to Sections 17 and 18.
Orig. 24", now 69" Fir, N. 28° W. 40.9 ft., Alive, probably 64" when
scribed, " $\frac{1}{4}$ " bark scribe & BT. scar.
Laurel Stool bears N. 43° E. 19.8 ft. with 20" hole in middle where
other O.BT. probably stood. Old blazed line N. & S.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 25 S R 7 W
Office, 1967 $\frac{1}{4}$ S 18 | S 17
New BT's: 14" D. Fir N. 14° W. 22.5 ft. mkd. $\frac{1}{4}$ S18 CS BT.
6" I. Cedar S. 7° E. 14.6 ft. mkd. $\frac{1}{4}$ S17 CS BT.

March 8, 1967

MICROFILM TO HERE 10/67

86

Vernon "Ray" Tracy
Jack Heritage, V/Perron &
Chet Sorenson, BLM
Jan. 30, 1968 C.S. File No. 54/10

$\frac{1}{4}$ Corner to Sections 27 and 26.
Found - 3/4"x40" Iron Bolt, See Ren. #29.
14", now 15" W. Oak S. 89° W. 683.0 ft., alive, shows good scars.
(This is Frear's 1921 BT., See Ren. #4.)
10", now 14" Apple, alive, S. 11° W. 395.5 ft. (slope) shows " $\frac{1}{4}$ " S B"
scribe on unhealed blaze. Tree mkd. by Boyer in 1944, C.S. 32/35.
Do not find any other Iron Bars or original BT's.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 25 S R 7 W
(Reset Bolt alongside) Office, 1968 $\frac{1}{4}$ S 27 | S 26
New BT's: 4" Apple S. 66° E. 85.3 ft. mkd. $\frac{1}{4}$ S26 CS BT.
9" Ash N. 74° W. 111.5 ft. mkd: $\frac{1}{4}$ S27 CS BT (most southerly in clump
of five)
Note - Cor. lies on old fence line, course E-W along old
unused road.

87

Section Corner to Sections 22 - 23 - 26 - 27.
Found - No trace of Orig. BT. called for in Ren. #5.
24", now 36" B. Oak, alive, N. 39° 15' E. 221.3 ft., open & find
"T25S S2" reverse scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 25 S R 7 W
(Set cor. point 12" below Office S 22 | S 23
surface as corner falls 1968 S 27 | S 26
in orchard)
New BT's: 21" Maple N. 21° E. 185.3 ft. mkd. T25S R7W S23 CS BT.
23" Myrtle N. 33° W. 161.7 ft. mkd. T25S R7W S22 CS BT.
Note - This corner lies approx. 200 ft. south of river.

1/30/68

88

Section Corner to Sections 21 - 22 - 27 - 28.
Found - Orig. 12", now 16" Fir, alive, N. 20° E. 16.5 ft. (Rec. 23.1), shows scar.
Orig. 20", now 36" Fir, alive, N. 52° W. 19.8 ft., shows bark scribe.
Orig. 15", now 24" Fir, down, S. 22° E. 21.8 ft., scribe vis. in break.
Orig. 12", now 16" Fir, alive, S. 46° W. 15.4 ft., opened & shows "BT".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 25 S R 7 W
Office S 21 | S 22
1968 S 28 | S 27
New BT: 11" D. Fir S. 21° E. 24.8 ft. mkd. T25S R7W S21 CS BT.
Remarked Orig. BT's: 16" D. Fir N. 20° E. 16.5 ft. mkd. T25S R7W S22 CS BT.
16" D. Fir S. 46° W. 15.4 ft. mkd. T25S R7W S28 CS BT.
Note - This corner lies on moderate S. slope at N.E. corner of old
cut-off unit.

4/30/68

RE-OPENED CORNER NO. # 144

SEPT. 68