

Douglas County Surveyor's Record of
Government Corners Renewed

T 25 S T. S. R 7 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

89

Witness Corner N. W. Cor. DLC No. 38
Found - 1 3/4" Axle shaft 21.0 Ft. West of fence Cor. 5" Below surface, Ren. # 2A.
of Co. Rd. at a point 20 ft. East of true Cor. set 1" I.P.
Set - Brass Cap for witness corner Mkd. "

County Surveyors T 25S
Office, 1969 R 7 W Wit. Cor.

NW DLC 38 20 Ft. W. to Cor. No trees available for Bt's - At a point
26.0 Ft. West of true Cor. & 46.0 ft. West of Wit. Cor. set a 5/8" X 30"
I.R. in r/w fence on West side of Road. Wit. Cor. lies 1.0 Ft. No. &
1.0 Ft. West of Fence Cor. fences N-S&E & on N. side of gateway on East
side of Road. 2-17-69

90

1/4 Corner of Sections 5 & 8
Found - 8"x8"x20" Sandstone Mkd. "1/4 S CS" out of ground, & Coles BT's
See Ren #13
12" now 28" B. Oaks S 87 1/4 W. 133.0 Ft. Shows faint scar.
10" now 20" W. Oak N. 14° W. 98.5 Ft. (slope. Record N. 18° W.
We open & find "1/4 S C" Scribe & Reverse
also - Decayed remains of Orig. BT to N. W. no scribe at intersection of
Dist from Coles BT's
Set - 1" I.P. & Brass Cap for Cor. Mkd:

County Surveyors T 25S
Office, 1969 1/4 S 5 R 7 W
S 8

Mkd. new Bt's
13" D. Fir S 81° W. 9.7 Ft. Mkd. 1/4 S 8 CS BT
8" D. Fir N. 45° W 8.5 Ft. Mkd. 1/4 S 5 CS BT
Reset Coles Cor. stone along side Brass Cap. Remains of old N.S fence
in evidence. 3-28-69

91

D.L.C. Corner 49, Most Northerly N. W.
Found - 1" I. P. inside 1 1/2" I.P. set along side orig. cor. stone
(no mark fd.) as recorded in Ren. #16 from this Cor. the remains of the
S. E. cor. post of cemetery bears N. 54 1/2 E. 197.2 ft. in place of cor.
stone,
Set - 1 I.P. & Brass cap Mkd.:

County Surveyors T 25S R 7 W
Office, 1969 N.N.W. DLC 49

and reset stone along side--No trees close
Set - 5/8"x30" I.R. in fence 10.0 Ft. East of Cor. & 5/8"x30" I.R. 10.0 Ft.
West of Cor. Cor. lies in E. W. fence on So. Boundary of the Cole's
Valley Cemetery approx. 250 Ft. West of Co. Rd. 2-17-69

92

1/4 Cor of Sections 5 & 4
Found - O. BT's 2 S Follows
Orig. 24" now 48" Fir N. 2° W. 23.8 Ft. Now only shattered stump "1/4 S"
Bark scribe visible.
Orig. 18" now 24" Fir S. 2° E. 10.6 Ft. turned out. Opened in 1948 by Udell
& "BT" Scribe exposed.
Udell's BT see Ren. # 26. 30" Fir S. 41° W 18.5 Ft. Down - Blaze decayed.
No positive scribe Mks. fd.
Set - 1" I.P. & Brass Cap Mkd:

County Surveyors T 25 S 1/4 S 5 S 4 R 7 W
Office, 1969

& Mk. new BT's
8" W. Fir N. 60 1/2° W. 42.0 Ft. Mkd. "1/4 S 5 CS BT"
12" W. Fir S. 19° E 21.0 Ft. Mkd. "1/4 S 4 CS BT"
This cor. lies on a steep S. W. Slope. 3-28-69

Vernon "Ray" Tracy
Jack Heritage, V. Perron
& Jim Rabe of B.L.M.
March 28, 1969 C. S. File No. 54/10