

Douglas County Surveyor's Record of
Government Corners Renewed

25 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

99
 1/4 Cor. to Sections 29 & 32.
 Found: Fir cor. tree shows good scar. See Ren. # 9
 24" D. Fir now 30", N. 86° E., 17.0 ft. (to face). Bark scribed
 1/4 S29.
 10" D. Fir now 19", S. 7° E., 35.2 ft. (to face). Shows good scar.
 Set: Brass Cap on south side of 14" cor. tree mkd:
 County Surveyor's T 25 S R 7 W
 Office, 1971 S 29
 S 32
 Reblazed & Rescribed: 30" D. Fir, N. 86° E., 18.5 ft. scribed 1/4 S29 CS BT.

John M. Powell
 J. Heritage
 July 2, 1971
 C. S. File 54/10

100
 Section Corner to Sections 13 - 14 - 23 - 24.
 Found these BT's. mkd. by USBLM, 1968. No other evidence of the 1968 survey.
 24" D. Fir BT., scribes vis. bears N.48°W. 225.6 ft.
 18" Madrone BT. scribes vis. bears N.70°E. 84.0 ft.
 32" D. Fir BT. scribes vis. bears S.76°E. 100.7 ft.
 16" W. Oak BT. scribes vis. bears S.61°W. 229.0 ft.
 Found - Orig. 28" W. Oak BT., face rotted out bears N.18°E. 152.6 ft.
 (Record dist. = slope dist. 188.1 ft.)
 Set - Brass Cap Mkd: T25S, R7W, WM S14, S13, S23, S24 1972

JAN 1972

U.S. Bureau of Land Mgt.
 By: Bruce A. Shaner
 Oct. 27, 1972
 Map File M 49 - 1

101
 1/4 Corner to Section 14 and Section 15.
 Set - Brass Cap mkd: T25S, R7W, WM 1/4 S15, S14 1972
 Found - 36" Orig. D. Fir BT Stump with scribes vis. bears N.70°E. 12.5 ft.
 I scribed: 14" D. Fir "1/4 S15 BT" bears S.62°W. 18.0 ft.
 36" D. Fir Stump "1/4 S14 BT" bears S.31 1/2°E. 29.9 ft.

10/27/72

JAN 1972

102
 1/4 Corner to Sections 3 and 2.
 Found - 1958 BLM Brass Cap.
 10" White fir, N.39°E., 63.7 ft. Scribes vis.
 20" Hemlock, S.66°W., 64.0 ft. Scribes vis. now down.
 New BT - 12" Yew, S.67°W., 48.0 ft. scribed "1/4 S3 BT".

U.S. Bureau of Land Mgt.
 By: Bruce A. Shaner
 Dec. 26, 1972
 Map File M 47 - 40

103
 Section Corner to Sections 3 - 2 - 10 - 11.
 Found - 1958 BLM Brass Cap. REN. # 59
 24" D. Fir, N.39 1/2°E., 20.5 ft. High stump with Scribes vis.
 (Record White fir)
 18" W. fir, S.10°E., 5.9 ft. Badly rotted stump with scribes vis.
 15" W. fir, S.56°W., 38.6 ft. Badly rotted stump with scribes vis.
 23" W. fir, N.56°W., 68.0 ft. Badly rotted stump with scribes vis.
 New BT's - 36" D. fir stump, N.70 1/2°W., 83.3 ft. to face. Scribed "T25S,
 R7W, S3 BT"
 6" D. fir, S.77°E., 40.0 ft. Scribed "T25S, R7W, S11 BT."
 10" W. fir, S.3°W., 24.7 ft. Scribed "T25S, R7W, S10 BT."

104
 1/4 Corner Section 32 and Sec. 5, T.26-7.
 Found - 30" D. Fir, now 35", S.33°E., 8.0 ft. Shows good scar.
 16" Laurel, now 18", N.18 1/2°W., 12.9 ft. Bark Scribe visible
 2807 - S32 T25S R7W BT. Ren. No. 53
 Set - Drove 5/8" I. Rod at 1/4 Corner.
 New BT's - 9" D. Fir, S.27°W., 6.5 ft. Scribed 1/4 S5 CS BT.

John M. Powell
 J. Heritage
 G. Commons
 C.S. File 56/25
 February, 1973

2/14/73

105
 Section Corner for Secs. 33 and 34 only T24-7.
 Found - 3/4" x 18" Iron rod.
 18" Orig. D. Fir, snag, face vis. bears N.20°W., 24.4 ft.
 (to face)
 32" D. Fir, scribe vis. bears N.21°E., 58.0 ft.
 28" Orig. D. Fir snag, face vis. bears N.61°E., 42.2 ft.
 Set - Brass cap mkd. T24S, R7W, WM S33, S34, CC 1972.
 Note - Tie to Sections 3 and 4, T25-7, S.89°0'E., 204.61 Ft. (3.10 chs.)
 (Record East, 207.24 ft. (3.14 chains))

U.S. B.L.M.
 by Shaner Engineering
 M 49 - 7
 Dec. 11, 1972

RECORDED SEE CORNER NO. #107