

Douglas County Surveyor's Record of
Government Corners Renewed

25 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

U.S. Bureau Land Mg.
by Shaner Engin.
M 49 - 7
Dec. 11, 1972

CC Corner for Secs. 4 and 3 only. 106
Found - Wooden stake at CC for 4 & 3. Ren. No. 25.
Orig. 20" D. Fir, snag, bears N.43°E., 14.5 ft.
14" Fir, down, burned and rotted, bears S.66°E., 12.5 ft.
Stumphole with the burned remains of a cedar stump, bears
S.65°W., 12.5 ft.
Set - Hub and tack.

John Powell
J. Heritage
C.S. 56/34
12/14/70

Section corner for Secs. 33 and 34 only, T24-7. 107
Found - 5/8" Iron rod set firmly at sec. cor.
Fir stump, N.61°E., 42.2 ft. shows good scar.
17" D. Fir, now 19" N.20°W., 24.4 ft. shows good scar.
I do not open trees as every thing fits as noted. #105
New BT - 32" D. Fir, N.21°E., 58.7 ft. scribed T24S R7W S34 CS CC BT.

Glenn Baughman
for Bill Escalle
October 1974
M 49 - 76

Section Corner for Sec. 36; and Sec. 1 of T26-7; and Sec. 31 of T25-6;
and Sec. 6 of T26-6. 108
Set - Brass cap on a 1" I.P. on the inside edge of a dike of a farm
pond approx. 15' from lower edge of a steep bank between field and
lower field terrace. #116
BT - Only one tree close to corner which I scribe:
42" Oak, bears N.61°W., 46.0 ft scribed S36 BT.

Steve Wetherell
BLM
@/S.C57/33
6/9/75

1/4=Sec. Cor. Bet. Secs. 2 & 35 (S. Bdy) (Sec.2 T26-7) 109
Found: B. Oak snag, 37" N89 3/4°W., 792 Lks. Scribe Mark T vis.
B Oak snag, 38" S89 3/4°W 806 Lks. Scribe Marks 4S BT
Set: 2 1/2" Iron pipe 18" in grd., in M.S.4ft base to top,
w/B.C. mkd. T25S R7W

~~RENEWED, SEE CORNER NO. #114~~
L/4 S35
S2
T26S
1975
Sand Stone boulder 4'x4' in place N35°W., 85 1/2 Lks. X BO

Sec. Corner to Secs. 35 & 34 T25-7 and 3 & 2 T26-7 110
Found: B.Oak, 59" N89°W., 1196 Lks, BT Vis.
- Root hole N40°E., 708 Lks.
Set: 2 1/2" Iron pipe 28" long w/top 6" below surface B.C. mkd
W/B.C. Mkd. T25S R7W
S34 S35
S 31 S2
T 26 S

New BT'S
A Fir- 12" S80°W., 1011 Lks. T26S R7W S3 BT
A Fir- 20" N65 1/2°E., 553 Lks. T25S R7W S35 BT.

(UNOFFICIAL - SURVEY PEND)

L.E. Monrean
P.L.E.
11/17/75
C.S. 57/39

Sec. Corner to Sec. 4, 3, 9, and 10 111
Found US BLM Brass cap (1958) properly marked.
BT's- A 25" now 27" fir (stump) bears N68 1/4°E., 111.7 ft (rec. 112.2 ft)
stump is scribed " T25S R7W S3 BT" Stump is rotted and scribed portion
loose. Tagged.
a 10" now 18" dia. fir bears S13 1/2°E., (rec. S 15 1/2°E) 56.1 ft. Has good
blaze, tagged.
A 13" now 15" diam Fir bears S40°W (rec. S47 1/2°W) 45.5° ft. Has blaze
(facing slightly away from corner) tagged.
A 15" now 20" diam. fir bears N40°W., 38.9 ft. Has good balze, tagged.
Renewal- A Fir 15" diam. bears N64 1/2°E., 173.5 ft. scribed "T25S R7W S3
CS BT" Tagged 11/17/75

Howard Johnstone
For: Roseburg Ldr.
April 19, 1976
M 56 - 39

Center 1/4 Section 10 112
Set - 5/8" x 48" Iron rod & Alum cap.
BT - 5" Fir, West 192.0 ft.
West corner of house bears N.24°W.
East corner of barn bears N.10°W.

4/19/76