

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 25      T. S.      R 7      R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

**113**

1/4 Corner for Sections 10 and 15.  
Set - 5/8" x 48" Iron rod & Alum. cap.  
BT's - 20" Fir, N.75°W., 18.0 ft.  
20" Fir, S.41°E., 81.0 ft.

Howard Johnstone  
For: Roseburg Lbr.  
April 19, 1976  
M 56 - 39

4/19/76

-3-77

**114**

1/4 Corner for Sec. 35(South boundary) and Sec. 2 of T26-7.  
Found - Orig. 18" B. Oak, now 40" measured below fork, half dead, bears  
S.89 3/4°W., 532.0 ft. Found opened blaze and scribing "BT".  
Orig. 12" B. Oak, now 37" dead trunk (tree is triple trunked  
at ground) bears N.89 3/4°W., 522.7 ft. Found opened blaze  
and scribing "B" in cut out section. Ren. #109  
A 4 ft. mound of stone at corner location.  
A 4 ft. x 4 ft. outcropping in sandstone ledge marked "X"  
B0" bears N.35°W., 56.2 ft.  
Set - A 1" I.P. 36" long set 33" in ground in mound of stone 4 ft. base  
to cap, marked: T25S R7W 1/4 S35 S2 T26S 1977  
Set - A metal fence post 2.0 ft. North of brass cap with sign attached.  
New B.O.- A 2' x 3' outcropping in sandstone ledge marked "B0" on horiz.  
surface with 3" "X" on surface facing corner bears S.13 1/2°E.,  
63.7 ft.  
Set a metal fence post 18" West of "X" with witness post sign  
attached.  
Note: Equipment used, Ranger lazer beam distance meter and Gurley  
transit for bearing.

R. B. Kimberling, Doug. Co. Surveyors  
Office  
P. Earle  
May 19, 1977  
C.S. 59/34

5/19/77

**115**

Section Corner for Secs. 23, 24, 25 and 26  
Set - Brass cap on 1" I. pipe marked Sec. Cor. 23, 24, 25, 26.  
BT's- A 60" Maple bears N.48°W., 241.5 ft.  
A 30" Cottonwood bears N.12°E., 196.2 ft.

Romanso E. Ware  
For: H. B. Germond  
June 1977  
M 65 - 26

6/77

**116**

Sec. Cor. for S. 36; and S. 31 T25-6; & S. 1 T26-7; & S. 6 T26-6  
Found - Brass cap 6" above ground on a 1" I.P. and stamped OLS 536  
T25S R S36 | S31 R Brass cap is on inside edge of a  
6 S 1 | S 6 5 dike for a pond.  
W T26S W  
1974 Ren. #108

We stamped correction on BC to read "OLS 536

T25S			
R	S 36	S 31	R
76	S 1	S 6	6
W	T26S	W	
1974		CS 1977	

R. B. Kimberling  
P. L. Earle  
Douglas County Surveyors Office  
June 28, 1977  
C.S. 59/34

Found - A 42" Oak, now down bears N.61°W., 46.0 ft. double blazed and  
scribed "S36 BT"  
Set - A metal fence post with survey marker sign 1.0 ft. north of BC.  
A 5/8" I. Rod 30" long 3" above ground with an alum. cap stamped  
"B.O. 1", bears N.24°E., 74.0 ft.  
Set a metal fence post with survey marker sign 1.0 ft. west of  
I.R., point is on top of dike at west side of pond.  
Set a 5/8" I.R. 30" long 4" above ground with an alum. cap stamped  
"B.O. 2", bears S.4°W., 105.8 ft. Set a metal fence post with  
survey marker sign 1.0 ft. west of I.R., point is on edge of  
upper field.  
A 7" Pear tree bears N.67°W., 107.3 ft. double blazed and marked  
"T25S R67W S36 CS BT".

6/28/77

**117**

1/4 Corner For Sec. 7 and Sec. 12 of T.25-8  
Found - A 1" x 36" I.P. laying in crotch of tree, bent, with brass cap  
marked "County Surveyors Office" T 25 S R8W R7W 1/4 S12 S7  
BLM 1964 1961. Ren. #71  
A 3/4" x 30" I.P. bent and mangled (obviously dislocated) bears  
N.72°W., 7.6 ft. from corner reset from bearing trees. (Rec.  
set by Kerr 1954, a 1/2" I.P. bears S.79 1/2°W., 7.9 ft. according to  
BLM 1964, S.80°W., 7.8 ft. according to Ren. #64 /

R. B. Kimberling  
P. L. Earle  
Doug. Co. Surveyors  
Office  
Noy. 14, 1977  
C.S. 59/42