

Douglas County Surveyor's Record of
Government Corners Renewed

T 25 T. S. R 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

R. B. Kimberling
P.L. Earle
Doug. Co. Surveyors
Office
Nov. 14, 1977
C.S. 59/42

A. Boyer For:
the A.E. Thompson
Ranch-Nov. 1937
C.S. 30/-39

Gary L. Langlitz, Douglas Co. Surveyors Office
Larry E. Monrean - Stephen J. Flause
For: Ben J. Amerson
April 21, 1979
C.S. 60/24

REN. # 119 15
C.S. 60/29

CONT. 117
Found - A 24" now 37" White Oak bears N.7°W., (Rec. N.6 1/2°W) 534.6 ft. with visible scribing "S12 BT" in partly healed upper blaze and "BT" in chopped open lower blaze. A 9" high "K" is carved in south side of tree (O.B.T.)
A 20" now 24" White Oak bears N.87°E., 255.9 ft. with a well healed blaze.
Set - I straighten and reset brass cap, 0.4 ft. above ground, with distances controlling placement using Hewlit Packard electronic measurement to O.B.T. and transit/steel tape measurements on all other distances. I stamp "RESET 1977" above "BLM 1964".
New BT - A 12" Walnut tree bears S.33°W., 5.6 ft. but I do not mark tree.
Set a steel fence post 1.0 ft. south of BC with survey marker sign attached.
Corner is approx. 80 ft. south of county road in old walnut orchard.

11/14/77
N E Corner, DLC #49 118
Set - 1" Pipe.
11/37

1/4 Corner for Secs. 30 and 31 119
Found - No trace of original corner monument or accessories.
Set - At the corner point determined by single proportionate measurement, WE SET a 1" x 36" I. P., 32" in the ground on a steep northeast slope, with brass cap attached, marked "DOUGLAS COUNTY SURVEYOR"
*SEE M 109-54 A&B
DEC 1989*
T 25 S
S 30 1/4
S 31
R 7 W
1979

New Accessories:
A 16" D. Fir scribed "1/4 S30 CS BT" on a double blaze bears N.44°W., 2.6 ft.
A 15" Bigleaf maple, scribed "1/4 S31 CS BT" on a double blaze bears S.54°E., 14.4 ft.
A 14" D. Fir scribed "1/4 S31 CS BT" on a double blaze bears S.9°E., 12.9 ft.
A 2 ft. wide by 3 ft. high exposed vertical sandstone outcrop with chiseled markings "X 1/4 S31 Bears S.8°W., 6.6 ft.
From this 1979 corner location, a 3/4" I. Pipe set in a north-south fenceline by Boyer in 1953(REN. #38) bears N.72°52'17"W., 105.97 ft. The remains of Boyer's bearing trees were found as follows:
A 6" Chinquapin, now an 8" willow, with scribing "1/4 S31 1581 BT" visible on unhealed and rotten face bears S.36°W., 16.8 ft. (rec. S.34°W., 18 ft.)
A 8" now 10" chin quapin with no markings visible on partially healed and rotten blaze, bears S.79°E., 12.2 ft. (Rec. S.89°E., 12 ft.)

East 1/16 Corner for Secs. 30 and 31 120
No previous renewal.
Set - At the corner point determined by single proportionate measurement, We SET a 1" x 36" Iron pipe, 12" in the ground to bedrock and supported in a mound of stone three feet in diameter, 18 inches high on a steep SW slope, with brass cap attached marked:
"Douglas County Surveyor" T 25 S R 7 W
E 1/16 S 30
S 31
1979

New BT's - A 6" D. Fir scribed "E 1/16 S30 CS BT" on a double blaze, bears N.83°W., 29.8 ft.
A 8" D. Fir scribed "E 1/16 S30 CS BT" on a double blaze bears N.10°W., 23.2 ft.
Corner is located along North edge of clear-cut area.
5/21/79