

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 25 S. T. S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Thomas E. Shrumm  
P.L.S. #1706  
For: Champion International  
Dec. 13, 1982  
M 93 - 43

126

*FOR SEC. 20 ONLY 1/8 1/91*  
1/4 Corner common to Secs. 17, & 20. *SEE REN. #122*  
Set - 2 1/2" Alum. Cap (mkd: P.L.S. 1706) on a 1" x 36" I.P.  
New BTs - 14.5" D.Fir bears N.73°30'W., 13.5-ft.  
14" D.Fir bears S.5°15'W., 12.5-ft. 12/82

127

Center 1/4 Corner of Sec. 20.  
Set - 2 1/2" Alum. Cap (mkd: P.L.S. 1706) on a 1" x 36" I.P.  
5 1/2" D.Fir bears N.5°30'E., 11.2-ft.  
3 1/2" D.Fir bears S.70°E., 19.4-ft. 12/82

128

Witness Corner for Sec. Corner common to Secs. 5, & 6, and Secs. 31, & 32 of T.24-7. *Ren. #93.*  
Found - 2-1/2" B.C. on a 1-1/2" I.P. on the east bank Umpqua River,  
*FDOK PER JOHN - set in 1970 by P.L.S.896, & the following accessories:*  
*STONE MAY-87* 17" cedar stump bears N.3°E., 5.0-ft. (rec. 5.3-ft. (Scribed: X BT (in 1970).  
*M 104-16* 27" cedar stump bears N.47°W., 11.5-ft. (rec. 11.0-ft. (1970).  
18" oak bears S.63°W., 32.9-ft. (rec. S.60°W., 32.4-ft. (1970),  
Closed face, chopped X in face.  
New BTs - 18" oak bears N.87°W., 33.0-ft., scribed: X BT (1983).  
8" oak bears N.8°W., 18.8-ft., scribed: X BT (1983). *#143*  
11" willow bears S.39°E., 28.2-ft., scribed X BT (1983).  
2, & 3/83

**RE-RENEWED, SEE CORNER NO. #143**

129

Witness Corner for Sec. Corner common to Secs. 1, 6, 7, & 12. *(Res. 8-7)*  
Found - 3" B.L.M. B.C. on a 2-1/2" I.P. set in 1964, on the north bank  
of Umpqua River, & the following accessories:  
14" fir bears N.43-1/2°E., 62.0-ft...closed face (1964).  
Chiseled X BO on an 8' x 4' x 4' boulder bears S.27°E.,  
19.8-ft. (1964).  
Chiseled X BO on a 3' x 2' x 2' boulder bears N.47°W.,  
8.6-ft. (1964).  
Set - Chiseled X on a 4' x 3' x 2' boulder bears S.15-1/2°W.,  
18.7-ft. (1983). 2, & 3/83

130

1/4 Corner common to Secs. 6, & 7.  
Set *FDOK 3/92* - PK nail in north lane of paved road, and the following access.:  
*R. Dolan* 11" myrtle bears N.54°E., 68.56-ft., scribed: 1/4 S6 BT,  
*M 114-77* (1983)  
15" fir bears S.56°E., 164.88, scribed: 1/4 S7 BT (1983)  
Note - Nailed an aluminum washer (stamped PLS 1988) on the lower  
face of each BT. 2, & 3/83

131

Witness Corner for 1/4 Corner common to Secs. 5, & 6.  
Set - 2-1/2" aluminum cap set on a 7/8" x 36" iron pipe, w/follow.access.:  
Chiseled X BO on an 8' x 12' rock face, bears S.67°E.,  
84.0-ft. (1983).  
Chiseled X BO on a 5' x 2' rock face, bears N.56°E., 71.8-ft.  
(1983). 3/83

132

Meander Corner Sec. 6 and Sec. 31 of T.24-7.  
Set - 2-1/2" aluminum cap set on a 7/8" x 36" iron pipe, on west  
bank of Umpqua River near high water line, & the following  
accessories:  
4" fir bears N.60°W., 9.1-ft., scribed X BT (1983).  
24" fir bears N.6°E., 104.0-ft., scribed MC S31 BT (1983).  
Note - no BTs available south of line. 3/83

133

Center 1/4 Section Corner of Sec. 30. *SEE M 109-54 AD B DEC. 1988*  
Set - 7/8" x 36" I.P. w/a 2-1/2" aluminum cap stamped as per the  
1973 BLM Manual of Surveying, and PLS 1988, from which:  
New BTs - 8" fir bears S.18°W., 35.6-ft. (both BTs scribed: C1/4 S30 BT).  
16" fir bears S.75°E., 20.3-ft. 4-6/83

Ronald G. Geisler, LS#1988  
For: Champion International Corp.  
Feb. thru Mar., 1983  
M 93 - 79

Ronald G. Geisler,  
L.S. 1988  
For: Champ. Interna.  
Apr. thru June, 1983  
M 94 - 31