

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 25 _____ T. S. R 7 _____ R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97401

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
Terrie Franssen
Jan. 17, 1991
C.S. 64/13

146

Section Corner for Secs. 33 and 34; and Secs. 4 and 3 of T.26-7
 Found - 2½" dia. 1966 County brass cap on a 1½" O.D. I.P., protruding
 14" above ground. Ren. #81
 1 1/8" O.D. axle shaft protrudes 3" above ground. Ren. #45
 Axle shaft is south 0.4 ft. from brass cap.
 15" now 24" dia. 5 ft. high D. fir stump with a fully
 healed double blaze, bears S.25°W., 8.6 ft. (Rec. S.30½°W.,
 8.6 ft. in BLM resurvey) Ren. No. 45
 14" now 20" dia. D. fir with a fully healed single blaze,
 bears S.71½°E., 96.0 ft. (Rec. S.66°E., 96.0 ft.) 1975 BLM
 (BTs from Ren. No. 81 are gone).
 New BTs - A multi trunked elder berry double blazed and scribed "X BT"
 on 12" dia. near trunk, bears N.41½°E., 83.9 ft.
 5" dia. B. oak double blazed and scribed "X BT" bears
 S.78°W., 17.4 ft.
 7" dia. pistol butt maple double blazed and scribed "T25S R7W
 S33 CS BT" bears N.59°W., 104.5 ft. to center of trunk at
 upper blaze.

Greg Lang LS #2295
 For: John Korecki
 Aug. 1989 M109-3

1/17/91

Center 1/4 Corner for Saction 16
 Set Iron rod at intersection of N-S and E-W lines per found monuments.

RE-RENEWED, SEE CORNER NO. #148

147

Kristian DeGroot LS 1941
 For: Mrs. Mytly Stone
 January 1992
 M 112 - 43

148

Center 1/4 Corner for Section 16
 Found - 5/8" Iron rod as per M 109-3 Ren. No. 147
 New BTs - A 7" D. fir bears S.2°00'E., 23.5 ft. scribed "C 1/4 S16 BT".
 A 17" B.Oak bears N.75°30'E., 20.0 ft. scribed "C 1/4 S16 BT"

149