

Douglas County Surveyor's Record of
Government Corners Renewed

25

T. S.

8

R. W. W. M.

NOT RENEWED

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

Arthur R. Evans
1952.
C. S. File
41/57.

Sections 25 & 36 (T25S, R8W) and 30 & 31 (T25S, R7W).
60" Fir B. T. bears S56°W, 64 links marked as described in govt.
field notes. Renewed corner by setting a 2" iron pipe in proper location
from which:
8" Fir bears S75°E 10.5' Mk'd. at T25SR7W., S. 31, R.E. 2741 B. T.
6" Chinquapin bears N47°E., 26.7 feet, marked T25SR7W., S. 30 B. T.

RE-RENEWED, SEE CORNER NO. 1
K. Revo Co. Surveyors Office. C.S. 10/24

1

Claude Kerr, 1954.
See C. S. File 41/316.

1/4 corner to secs. 12 (T25S, R8W) and 7 (T25S, R7W).
Found the original Oak B. T., now 37" in diameter, bearing N.6°30'W.,
for 810 lks. Chopped in and found BT scribe marks. Replaced the tree and
marked it with 1/4" S 12 BT. I set a Cedar stake for the 1/4 corner with a
1/4" pipe alongside.
Marked a new BT: - On the North side of the county road.
m A 24" Oak, bearing S. 89° E. for 239.5 feet, marked 1/4" S 7 BT.

RE-RENEWED, SEE CORNER NO. 16

2

Witness Corner A line between Sections 12 (T25S, R8W) and 7 (T25S, R7W) at
58.95 chains south.
Found the original Fir BT, now 50 inches in diameter, bearing
S.80°E. for 10 lks. (Marking still visible).
Reset the Witness Corner from this BT setting a 4"x4" stake, which I
scribe W. C. on the east and west faces, and 58.75 Chs. S. on the North
face.
Marked a new witness tree:
A 14" Red Cedar, bearing N.55°W. for 19 feet and marked W. C. S. 12 BT.
The 1/4 corner for 7 and 12 can be seen from the W. C. at 58.95 chains
South. The correct variation between these corners is 20°20' East.

RE-RENEWED, SEE CORNER NO. 16

3

Claude Kerr
July, 1955.
C. S. File No.
42/11.

1/4 sec. corner to secs. 12 and 13.
Set a stake from Original B. T. - now a 35" D. Fir bearing North 3°
West for 16 lks.

RE-RENEWED, SEE CORNER NO. 17

4

Center 1/4 corner section 12.
At point for corner set a 3" x 3" x 5' fir post.

RE-RENEWED, SEE CORNER NO. #109

5

Arthur R. Evans
Work done for Martin Bros.
Box Co.
March 21, 1956.
C. S. File No. 42/206. (No map)

Section corner to secs. 2 & 3, T25S, R8W., and secs. 34 & 35, T24S, R8W.
Found 2 O. B. T.s: (1911)
18 inch Fir, S. 5°E., 50 lks.
30 inch Cedar, (Inc.) S.28°W., 25 lks.
Set 4 inch x 4 inch x 36 inch Fir stake.
Rescribe O. B. T.s.
Blaze and scribe 2 new B. T.s:
20 inch D. Fir, N.31°W., 25.2 feet (to centerline) mkd. T24, R8, S 34,
RE 2741 - BT.
14 inch D. Fir, N.36°E., 29.6 feet (to centerline) mkd. T24 - R8 - S 35,
RE 2741 - B. T.
Y. T. (G.L.O.) on N. W. B.T.
Plain yellow tag and G. L. O. warning sign on S. E. B.T.

RE-RENEWED, SEE CORNER NO. 7

6

James W. Byron, Deputy
M. Godfrey
S. Bilow
May 6, 1958
C.S. File No. 49/84

Section Corner to Secs. 2 & 3; T25S, R8W., & Secs. 34 & 35, T24S, R8W.
Found - Evans renewed Corner - BT's of record. Ren. #6
The Orig. S.E. & Evans' N.E. BT's. now dead.
Set Brass Cap at corner Mkd: S34/S35 T24S County Surveyor's
S3/S2 T25S Office, 1958.
New BT's: 5" R.Fir bears S.82°E. 26.3 ft. scribed S2 CS BT.
7" R.Fir bears N.69 1/2°E. 36.2 ft. scribed S35 T24S R8W CS BT.
I find Evans N.W. BT. should be N.34°W. 24.4 ft. - Record,
N.31°W. 25.2 ft.

7