

Douglas County Surveyor's Record of  
Government Corners Renewed

25 T. S. 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

8

Section Corner to Section 1 & 2, T25S R8W, & Secs. 35 & 36, T24S R8W.  
Found - Orig. 40", now 40" Fir Snag S.5°W. 13.2 ft., show faint  
but clear bark scribing "S2 R8W BT".

Rotted Base of large Fir that checks bearing & distances for  
N.W. BT.

The Orig. N.E. BT. down, checks for bearing & distance.

Set Brass Cap at Corner Mkd:  $\frac{S35}{S2} | \frac{S36}{S1}$  T24S T25S R8W County Surveyor's  
Office, 1958.

New BT's: 30" Cedar bears N.38°W. 24.9 ft. scribed S35 T24S R8W CS BT.  
7" W.Fir bears S.67°W. 12.8 ft. scribed S 2 T25S R8W CS BT.  
11" R.Fir bears N.65½°E. 53.3 ft. scribed S36 T24S R8W CS BT.  
24" R.Fir bears S.58½°E. 63.0 ft. scribed S 1 T25S R8W CS BT.

James W. Byron, Deputy  
M. Godfrey  
S. Blouw  
May 6, 1958  
C.S. File No. 49/84

9

Closing Corner to Sections 3 & 4, N. BDRY. T25-8W.

Found - Both BT's. Originals.

Orig. 42", now 60" Fir shows good scar., I do not open to  
face, S.40½°E. 50.2 ft.

Orig. 14", now 18" Snag., I open & Find good scribing  
"T25S R8W S3".

Set Brass Cap at Corner Mkd: County Surveyor's Office,  $\frac{S33}{S4} | \frac{T24S}{S3}$  R8W  
1958 Closing Corner T25S.

New BT's - 10" Hemlock bears S.33°E. 17.0 ft. scribed CC S3 T25S R8W  
CS BT.  
7" Hemlock bears S 4°W. 40.0 ft. scribed CC S4 T25S R8W  
CS BT.

Note: A.R. Evans Stake for 33/34 bears S.35°E. 46.2 ft. I destroy  
his BT's. Evans used S.E. BT. of Closing Corner for S.E.  
BT. 33/34.  $\frac{4}{3}$

James W. Byron, Deputy County Surveyor  
M. Godfrey  
S. Blouw  
May 14, 1958  
C. S. File 49/88

10

¼ Section Corner to Section 2, T25S R8W, & Sec. 35, T24S, R8W.

Found - Both Orig. BT's., both check for bearing & distance.

Orig. 24", now 36" R.Fir N. 8°W. 18.5 ft., has good bark  
scribing "S2". I do not find scribing on S.E. BT.  
Center Rotted.

Set Brass Cap at Corner Mkd:  $\frac{S35}{S2}$  T24S R8W County Surveyor's  
T25S R8W Office, 1958

New BT's: 20" Cedar bears S.70°W. 38.0 ft. scribed ¼ S 2 CS BT.  
36" R.Fir bears N. 8°W. 18.5 ft. bark scribed ¼ S35 CS BT.

22

11

¼ Section Corner to Sec. 31, T25S R7W, & Sec. 36, T25S R8W.

40.40 chains from the S. W. Corner of Sec. 31, I set in ¼ Cor. as  
follows:

A Stake Mkd: ¼ S, from which:

An Alder 18" diam. bears S.75½°W. 72 lks.

A Myrtle 5" diam bears N.73°E. 25½ lks.

Not Found V.R.T.

M.B. Germond, C.S.  
For J. S.  
Germond  
May 26, 1914  
Recorded in  
Vol. 3, Pg. 41.

12

Section Corner to Sections 9 - 10 - 15 - 16.

Found - Orig. 30", now 48" Fir Stump S.45°W. 35.0 ft. I open  
& find good scribing "BT".

Also find S.E. BT. as recorded 1911 Survey.

Set Brass Cap at Corner Mkd: County Surveyor's  $\frac{S9}{S16} | \frac{S10}{S15}$  T25S R8W  
Office, 1960

New BT's: 20" R.Fir bears S.18°E. 19.2 ft. scribed S15 T25S R8W CS BT.  
7" Maple bears N.70°E. 25.5 ft. scribed S10 CS BT. (scribed high)  
10" Hemlock bears N.43°W. 71.0 ft. scribed S9 T25S R8W CS BT.  
7" R.Fir bears S.25°W. 24.6 ft. scribed S16 T25S R8W CS BT.

James W. Byron, Deputy  
Milo Godfrey  
Clete Putnam  
Oct. 18, 1960

13

Section Corner to Sections 15 - 16 - 21 - 22.

Found - All four Orig. BT's: Orig. 50", now 60" Fir S.53°W. 67.3 ft.,  
shows scars. I do not open.

Orig. 40", now 40" Fir Snag S.27½°E. 50.8 ft., shows good  
scribe marks.

Orig. 50", now 50" Fir Snag N.33°15'E. 80.5 ft. rotted, no scribing.

Orig. 50", now 50" Fir Snag, N.38°W. 55.4 ft., shows good scribing.

Found very old scribed Stake at Corner (continued)

C.S. File  
No. 49/88