

Douglas County Surveyor's Record of
Government Corners Renewed

25 T. S. 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(Continued from previous page)

13 (CONT'D)

C. S. File
No. 49/88

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960

S16	S15
S21	S22

New BT's: 7" R.Fir bears N.45°W. 15.1 ft. scribed S16 T25S R8W CS BT.
10" R.Fir bears S.23°W. 20.8 ft. scribed S21 T25S R8W CS BT.
12" R.Fir bears N.11°E. 18.2 ft. scribed S15 T25S R8W CS BT.
8" R.Fir bears S.52°E. 35.2 ft. scribed S22 T25S R8W CS BT.

Milo E. Godfrey
Dec. 1961
C.S. File No.
49/76

1/4 Corner to Sec. 12, T25-8W., & Sec. 7, T25-7W. 14
Found-Old W.Oak, now 48", N.8 1/2°W., not 6 1/2°) 53 1/2 ft. Orig. tree, rescribed by Kerr, 1954, still in good condition. # 103
Old oak stump, now 24", S.38°E., (not 31°) 243.3 ft., cut open & find good reverse scribing "BT". REN. # 2
24" W.Oak Mkd. by Kerr, 1954 bears S.89°E. 232.5 ft. portions of SE BT DEST. BY ROAD CONST. 3/12/63
scribing still visible in nearly closed scars, Tree in good cond.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1961
T25S R8W 1/4 S12/S 7 R7W.
NEW BT: 20" W.OAK N.87°E. 255.9 ft. MKD. 1/4 ST CS BT. - 3/12/63 L.L.

By Howard W.
Johnstone
For Rsbrg. Lbr.
C.S. File No.
51/163

1/4 Corner to Section 9 and 16. 15
Found - 60" D. Fir N.70°E. 49.5 ft., scribing visible.
Set - 1" x 30" Iron Pipe
Scribed - 34" D. Fir S.51°W. 59.9 ft. Wit: J.Clark & R.Hendricksen
August 18, 1962

Milo E. Godfrey, Deputy
Vernon Tracy
Mike Stone
October 1962
C.S. File No. 49/76

Witness Corner to Sec. 12, T25-8 & Sec. 7, T25-7W. 16
Found - Stake, scribed, set by Kerr, 1954, fallen over & slid downhill from corner. REN # 3
18" Red Cedar N.55°W. 19.0 ft. Kerr's scribing still visible in partly healed over scars.
50" Fir S.80°E. 6.6 ft., old axe blazes vis. in bark. Faint traces of possible scribing visible in scars.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
T25S R8W W.C. S12/S 7 R7W
New BT: 6" Myrtle S.50°E. 16.0 ft. Mkd: T25S R7W W.C. S7 CS BT.
Corner lies on precipitous North slope, approx. 300 ft. South of River.

1/4 Corner to Sections 12 and 13. 17
Found - Square Cedar Stake set by Kerr, 1955. REN # 4
34" Fir N.3°W. 10.6 ft. (slope dist.) Faint trace of old axe face & old bark scribing, portions widely separated by growth of tree & subsequent splitting of old bark surface, marks illegible now, but unmistakable scribe marks.
30" Fir S.5°E. (not S.5°W.) 18.5 ft. (slope dist.) Entire old North face destroyed by old injury, no marks found.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
T25SR8W 1/4 S12/S13
Note - Kerr's Stake is 1 foot South of Corner.
New BT's: 21" D.Fir N.76°E. 11.3 ft. Mkd: 1/4 S12 CS BT.
9" D.Fir S.75°E. 32.2 ft. Mkd: 1/4 S13 CS BT.
Corner lies on steep south slope.

Godfrey and Crew
October 1962
C.S. File No. 49/88

East Corner to Sections 12 and 13 only. 18
Found - 30" Fir S.65°E. 17.8 ft., old bark scribing visible, has characteristics of Flint's scribing. This scribing was supposed to be destroyed by Heydon in 1896.
53" Fir S.85°W. 7.9 ft. No scribing found, but old axe faces on bark.
14" W.Fir N.5°W. 7.2 ft., shows 2 axe faces on bark & scribe mark "X"
No trace found of Original N.E. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
T25S R8W S12/S13
New BT's: 14" W.Fir S.55°W. 23.2 ft. Mkd: T25S R8W S13 CS BT.
18" W.Fir N.17°W. 62.0 ft. Mkd: T25S R8W S12 CS BT.
Corner lies on Bench at foot of fairly steep West Slope.