

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 25 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Weyerhaeuser Co.  
 By Donald L. Peel  
 May, 1967  
 C.S. File No. 55/30

**24**

Closing Corner common to Sections 6 & 7, T25-8W.  
 Found - GLO Survey Record - Post -- Gone.  
 30" hem N.20 3/4°E. 67 lks., now 36" hem., scribe visible.  
 20" cedar S.83°E. 55 lks., now 24" cedar, face not quite closed--  
 scribe visible.  
 Set - 4' x 3/4" Pipe 3' in ground & square post.  
 Both BT's. in good shape, so I just put Weyerhaeuser Co. plates with call  
 distances & bearings on the original BT's.

**25**

East 1/4 Corner common to Section 1, T25-9W.  
 Found - GLO Survey Record - Sandstone -- Gone.  
 48" fir N.87 1/2°E. 32 lks., now fir windfall--chopped open. Scribe  
 visible, supposedly markings destroyed in 1911, but not so.  
 50" fir S.85°W. 29 lks, now 50" fir, closed face.  
 Set - 4' x 3/4" pipe 2 1/2' in ground & square post.  
 Re-referenced with "W" nails & plates only: 50" fir S. 84° W. 17.0 ft.  
 60" fir N. 47° W. 5.3 ft.

**26**

Hiatus Corner common to Secs. 1 & 6, T25-8 & 9W.  
 Found - GLO Survey Record - Post -- Gone.  
 36" fir S. 30° E. 93 lks., now 37" fir, closed face--  
 not S30E but S.61°E.  
 40" fir S.61°W. 20 lks., now 42" fir, closed face--  
 not S61W, but S.30°W.  
 Note - from the call distances & the direction of the faces on the  
 BT's., I would say the bearings in the orig. field notes were reversed.  
 Set - 4' x 3/4" Pipe 3 1/2' in the ground & square post.  
 Re-referenced with "W" nails & plates only: 42" fir S.35°W. 11.7 ft.  
 18" cedar N. 47° W. 12.5 ft.

**27**

Closing corner common to Secs. 1 & 6, T25S, R8 & 9W.  
 Found - GLO Survey Record - Post -- Gone.  
 60" cedar S.86°W. 11 lks., now cedar snag--scribe visible.  
 12" cedar S.60°E. 78 lks., now 16" cedar already chopped open,  
 Scribe visible. **73**  
 Set = 4' x 3/4" pipe 3 1/2' in ground & square post.  
 Re-referenced with "W" nails & plates only: 30" hem S.49°E. 65.6 ft.  
 50" fir S.28°W. 44.9 ft.

**28**

Closing corner common to Secs. 6 & 5, T25S, R8W.  
 GLO Survey Record - Post -- Gone.  
 Found - 30" cedar S.46 1/2°E. 40 lks, now 36" cedar--had been chopped open  
 clear past scribing.  
 26" maple S.19 1/2°W. 22 lks., now 28" maple--chopped open,  
 Scribe visible.  
 Set - 4" x 3/4" Pipe 3 1/2' in ground & square post.  
 Re-referenced with "W" nails and plates only: 36" cedar S.52°E. 24.0 ft.  
 28" maple S.17°W. 13.5 ft.

**29**

1/4 Corner common to Secs. 6 & 5, T25-8W.  
 Found - GLO Survey Record - Post -- Gone.  
 6" fir N.50 1/4°E. 10 lks, now 13" fir, closed face.  
 6" fir N. 3°W. 28 lks. -- Gone.  
 Set - 4' x 3/4" Pipe 3 1/2' in ground & square post.  
 Re-referenced with "W" nails & plates only, 13" fir N.50°E. 6.2 ft.  
 14" fir N.21°W. 29.8 ft.

**30**

North 1/4 Corner common to Sec. 6, T25-8W.  
 (Set by single prop. measurement)  
 Set - 4' x 3/4" pipe 3 1/2' in ground & square post.  
 Referenced the Weyerhaeuser method ("W" nail, disc & plate):  
 16" fir S. 6° W. 15.1 ft.  
 36" cedar N.66°W.12.2 ft.  
 NOT FOUND  
 SEE C.S. 54/72 V.R.T  
 INFORMATION ON THIS CORNER