

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 25 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

31

Center $\frac{1}{4}$ Section 6, T25S, R8W.

The center of Sec. 6 was set at the intersection of the NS & EW centerlines.

Set - 4' x $\frac{3}{4}$ " pipe, $3\frac{1}{2}$ ' in ground & square post.

Referenced the Weyerhaeuser method ("W" nail, disc, plate)

20" hem N. 61° E. 20.6 ft.

62" fir S. 44° W. 33.2 ft.

April, 1967

Weyerhaeuser Co.

By. Donald L.

Peel

C.S. File

No. 55/30

32

Section Corner common to Secs. 5 - 6 - 7 & 8.

Found - GLO Survey Record - Post -- Gone.

72" fir N. 16° E. 103 lks., now 64" fir, closed face--

N. 26° E. not N. 16° E., by setting the corner from the other 3 BT's., I make the dist. to this BT. as 85.0 ft., which leads me to believe the dist. was 130 lks., not 103 lks.

6" fir S. 20 $\frac{3}{4}$ ° E. 20 lks., now 24" hem, not fir. Chopped open, scribe visible.

84" fir S. 41° W. 68 lks., now 70" fir stub--chopped open, scribe visible.

7" fir N. 6 $\frac{1}{4}$ ° W. 39 lks., now 24" fir--closed face.

Set - 4' x $\frac{3}{4}$ " Pipe $3\frac{1}{2}$ ' in ground & square post.

Re-referenced with "W" nails and plates only:

18" fir N. 82° E. 52.0'

24" hem S. 23° E. 11.8'

18" hem S. 64° W. 29.7'

24" fir N. 6° W 23.1'

Weyerhaeuser Co.

By Donald

L.

Peel

April,

1967

C.S. File

No.

55/30

33

Section Corner to Sections 3 - 4 - 9 - 10.

Found - Orig. 18", now 20" Fir, turned out, N. 75° E. 42.9 ft., we open & find "S 8 W BT" scribe on burned face.

Orig. 18", now 24" Fir, alive, S. 5° E. 33.7 ft., shows good scars.

Orig. 36", now 44" Fir, alive, S. 41° W. 15.2 ft., shows good scar. Rescribe: "T25S R8W S9 CS BT".

Orig. N.W. BT. is down & out of place.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office
1967

T 25 S R 8 W
S 4 | S 3

S 9 | S 10

New BT's: 10" D. Fir N. 81° E. 52.7 ft. mkd. T25S R8W S3 CS BT.

48" D. Fir N. 65° W. 44.2 ft. mkd. T25S R8W S4 CS BT.

Note - This corner lies on S.E. Slope approx. 460 ft. N. of Little Wolf Creek. This area has timber in the 30"-50" size.

Vernon "Ray" Tracy
Dick West
July 7, 1967
C.S. File No. 49/88

34

Section Corner to Sections 4 and 9.

Found - Orig. 30", now 47" Fir, alive, N. 66 $\frac{1}{2}$ ° E. 132.0 ft., shows good scar, do not open. BT. on N. side of creek, course E.

Orig. 45", now 62" Fir, alive, S. 79 $\frac{1}{2}$ ° E. 60.7 ft. Open & find scribe.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office
1967

T 25 S R 8 W
S 4

S 9

New BT's: 7" Hemlock N. 81° E. 52.8 ft. mkd. T25S R8W S4 CSBT.

7" Hemlock S. 48° E. 49.4 ft. mkd. T25S R8W S9 CS BT.

Note - This corner lies on steep N. E. slope approx. 90' S. of creek 4' wide, course E.

Unrecorded 56" Fir, alive, bears N. 41° W. 66.6 ft., shows good axe scar. Do not open.

Vernon "Ray" Tracy
Jack Heritage & E. West
Sept. 15, 1967
C. S. File No. 49/88

35

Section Corner to Sections 5 and 8.

Found - Orig. 40" Fir, now snag, N. 10° W. 27.7 ft., shows scribe on unhealed blaze.

Orig. S.W. BT., now down & slid downhill approx. 100 ft., shows scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office
1967

T 25 S R 8 W
S 5

S 8

New BT's: 8" Hemlock N. 9 $\frac{1}{2}$ ° W. 20.1 ft. mkd. T25S R8W S5 CS BT.

10" Hemlock S. 48° W. 40.8 ft. mkd. T25S R8W S8 CS BT.

Note - This cor. lies on steep N. slope 208' S. of cor. secs. 4 & 9, see above.