

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 8 W. R. W. W. M.

Section Corner to Sections 26 - 27 - 34 - 35. 41
 Found - Mound of Stone & Orig. BT's, as follows:
 Orig. 30", now 36" Fir Snag, S. 30° E. 7.9 ft. (Rec. S. 50° E), shows
 old bark scribe in poor condition.
 Orig. 24", now 36" Fir, S. 40° W. (Rec. S. 20° W.) 43.6 ft., down, bark
 scribe visible on underside.
 Orig. 24", now 32" Fir, alive, N. 30° W. (Rec. N. 50° W.) 11.9 ft., shows
 fair Bark scribe.
 Orig. 36", now 48" Fir, alive, N. 30° E. (Rec. N. 10° E) 19.8 ft.,
 old axe blaze & possible fragmentary bark scribe.
 Note - All bearings off 20° as though Flint did not use any variation.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 25 S R 8 W
 Office 1968 S 27 | S 26
 S 34 | S 35
 New BT's: 14" Hemlock S. 68° W. 30.2 ft. mkd. T25S R8W S34 CS BT.
 14" Hemlock N. 88° W. 42.5 ft. mkd. T25S R8W S27 CS BT.
 14" Hemlock S. 75° E. 10.3 ft. mkd. T25S R8W S35 CS BT.
 12" Hemlock N. 60° E. 33.7 ft. mkd. T25S R8W S26 CS BT.

Vernon "Ray" Tracy
J. Heritage & V. Perron
C. S. File No. 54/72

4/22/68 42

East $\frac{1}{4}$ Corner Section 5 only.
 Found - Remains of Rock Mound & Decayed Squared Post, from which:
 Orig. 14", now 18" Laurel, alive, S. 30° W. 22.4 ft., Open & find
 scribe and reverse.
 Orig. 30", now 40" Fir, alive, N. 50° W. 12.5 ft., shows very good scar,
 we do not open.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 25 S R 8 W
 Office, 1968 $\frac{1}{4}$ S 5
 New BT: 10" D. Fir S. 2° W. 39.0 ft. mkd: " $\frac{1}{4}$ S5 CS BT".
 Orig. 40" D. Fir N. 50° W. 12.5 ft., bark scribed " $\frac{1}{4}$ S5 CS BT" above.
 This corner lies on very steep, rocky SW slope about 80 ft. S. of top
 of rocky ridge, sloping SE.

Vernon "Ray" Tracy
Jack Heritage & V. Perron
July, 1968
C. S. File No. 54/72

43

East $\frac{1}{4}$ Corner to Section 17 only.
 Found - Orig. 10", now 14" Cedar, turned out, N. 45° W. 34.3 ft., scribe
 marks visible on open blaze.
 For Bearing & Dist., we use center of hole where cedar stood.
 Find only traces of Fir Log, no scribe in approx. location of BT. to West
 at corner point as determined from location of Cedar BT.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 25 S R 8 W
 Office, 1968 $\frac{1}{4}$ S 17
 New BT's: 6" Hemlock N. 71° W. 9.4 ft. mkd.: " $\frac{1}{4}$ S17 CS BT".
 13" Hemlock S. 24° W. 13.7 ft. mkd.: " $\frac{1}{4}$ S17 CS BT".
 This corner lies on steep N. slope.
 The W. $\frac{1}{4}$ Cor. Sec. 16, see below, bears N. 12° E. 187.7 ft., not agreeing
 with record bearing & distance of N. 0° 02' W. 208.6 ft.

44

West $\frac{1}{4}$ Corner to Section 16 only.
 Found - Orig. 12", now 18" Cedar, S. 22 $\frac{1}{2}$ ° E. 23.8 ft., alive, opened
 & shows scribe.
 No trace of NE BT probably due to huge fir windfall.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 25 S R 8 W
 Office, 1968 $\frac{1}{4}$ S 16
 New BT's: 12" Hemlock N. 20° E. 37.0 ft. mkd. $\frac{1}{4}$ S16 CS BT.
 14" Hemlock S. 47° E. 43.3 ft. mkd. " $\frac{1}{4}$ S16 CS BT."
 This corner lies 15 ft. S. of small creek, course N.E.

45

Section Corner to Sections 8 and 17 only.
 Found - Orig. 24", now 38" Fir, down & decaying S. 39 $\frac{1}{2}$ ° W. 30.4 ft. no scribe.
 Orig. 30", now 48" Fir, alive, N. 51° W. 38.3 ft. opened & shows
 scribe & reverse on pieces at base of BT.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 25 S R 8 W
 Office 1968 S 8 |
 17 |
 New BT's: 15" Hemlock S. 46° W. 21.3 ft. mkd. "T25S R8W S17 CS BT".
 14" Hemlock N. 69° W. 16.7 ft. mkd. "T25S R8W S 8 CS BT".
 This corner lies on moderate W. slope 75' E. of old jeep trail.
 The Sec. Cor. to Secs. 9 & 16, next page, bears N. approx. 208 ft.