

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 8 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21861

Vernon "Ray" Tracy
Jack Heritage & V. Perron
September, 1968
C. S. File No. 54/72

Section Corner to Sections 27 - 28 - 33 - 34. 56
Found - Orig. 36", now 65" Fir N. 54* W. 72.6 ft., alive, fragmentary bark scribe visible.
Orig. 36" W. Fir S.78*E.(Rec.S88E) 16.5 ft.(slope), only decayed remains of stump, no scribing.
Orig. 8", now 25" Hemlock, N.55*E.(Rec.N65E) 46.2 ft.(slope) Alive, scribe visible on open blaze.
No trace S.W. Orig. BT., Creek call to N. 26.4 ft. fits very good.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968

T 25 S	R 8 W
S 28	S 27
S 33	S 34

New BT's: 12" D. Fir N. 76* W. 23.8 ft. mkd: T25S R8W S28 CS BT.
10" Hemlock S. 64* W. 25,8 ft. mkd: T25S R8W S33 CS BT.
15" Cedar S. 3* E. 72.5 ft. mkd: T25S R8W S34 CS BT.
10" Hemlock N. 45* E. 11.6 ft. mkd: T25S R8W S27 CS BT.

This corner lies on very steep west slope on E. & S. of Creek, course S.W.
Note - From the corner described above, a 3" square post bears N.67*W. 10.8 ft. & Weyerhaeuser method BT's., as follows, from post:
65" Fir N.54*W. 60.4 ft. "W" Nail & Tag (O.B.T.)
52" Fir S.78*W. 55.7 ft., "W" Nail & Tag.
56" Fir S.20*E. 49.7 ft. "W" Nail & Tag.
25" Hemlock N.65*E. 45.3 ft. "W" Nail & Tag. (O.B.T.)

$\frac{1}{4}$ Corner to Sections 33 and 34. 57
Found - Orig. 36", now 60" Fir, alive, N.62*E. 28.4 ft., fragmentary bark scribe & axe notch. "W" Nail & Tag.
No trace other Orig. BT due to slide.
Weyerhaeuser Method BT's, as follows, (unrecorded):
16" Hemlock S. 47* E. 31.4 ft., "W" Nail & Tag.
16" Cedar S. 62* W. 41.0 ft. "W" Nail & Tag.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968

T 25 S	R 8 W
$\frac{1}{4}$ S 33	S 34

New BT's: 13" Hemlock N. 39* E. 6.4 ft. mkd: $\frac{1}{4}$ S34 CS BT.
15" Hemlock S. 8 * W 11.3 ft. mkd: $\frac{1}{4}$ S33 CS BT.

This corner lies in old slide sloping westerly. Orig. BT. found lies on N.E. edge of slide on top of bank & appears not to have moved. Sept. 12, 1968

Closing Corner to Sections 29 and 32. 58
Found - Remains of old scribed post at corner.
Orig. 30" Fir, now 36" Snag, S.80*W. 5.3 ft., open & shows scribe. In approx. locus of N.W. BT., only decayed remains of low stump.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968

T 25 S	R 8 W
S 29	S 32

 #115

New BT's: 13" Hemlock N. 38* W. 22.5 ft. mkd: T25S R8W S29 CC CS BT.
7" Hemlock S. 54* W. 20.8 ft. mkd: S32 CCCS BT.

This corner lies on very steep north slope, about 204 ft. south of section corner to sections 28 & 33, record distance 198 ft.

Section Corner to Sections 28 and 33. 59
Found - No trace of original 1881 Bearing Trees.
24", now 30" Fir Snag, N.70*E. 31.0 ft., open & shows "BT" scribe, open higher & find "W S28" scribe.
29", now 36" Fir N.88*E. 42.4 ft., (Rec.S80E). Open & find scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968

T 25 S	R 8 W
S 28	S 33

 #114

New BT's: 12" Cedar S. 69* E. 31.1 ft. mkd: T25S R8W S33 CS BT.
10" Hemlock N. 85 $\frac{1}{2}$ * E. 21.2 ft. mkd: T25S R8W S28 CS BT.

This corner lies on very steep northerly slope in shallow draw, and approx. 204 ft. north of C.C. Secs. 29 & 33, (record 198 ft.) Sept. 30, 1968

$\frac{1}{4}$ Corner to Sections 29 and 32. 60
Found - Orig. 36", now 48" Fir, N.83 $\frac{1}{2}$ *W. 13.2 ft.(Rec.N83 $\frac{1}{2}$ E), opened & find scribe & reverse under 56 rings of overgrowth.
Large hole bears S.85 $\frac{1}{2}$ *E. 58.7 ft., no trace of tree, extremely steep slope.
No evidence that there ever was a tree N. 83 $\frac{1}{2}$ * E. 13.2 ft.

(continued over)