

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 25 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

$\frac{1}{4}$ Corner to Sec. 32, T25-8W. and Sec. 5, T26-8W. 70
 Found - Orig. 18", now 25" Fir, alive, N. 10° W. 5.3 ft., bark scribe
 visible in fair condition.
 No trace of other Orig. BT., nor 1902 resurvey BT's.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T25S R8W $\frac{1}{4}$ S 32
 Office, 1968 T26S S 5
 New BT's: 25" Fir N. 10° W. 5.3 ft. (Orig. BT) mkd: " $\frac{1}{4}$ S32CS BT"
 (alongside old scribe)
 38" Fir S. 2° W. 27.1 ft. mkd: $\frac{1}{4}$ S 5 CS BT.
 This corner lies on very steep west slope. 9/24/68

$\frac{1}{4}$ Corner Section to Section 24 Only (T. 25-9) 71
 Found - O.B.T. as follows:
 Orig. 40" now 58" Fir N. 10 3/4° W. 7.3 ft. Now stump, Shows BT scribe
 No trace other O.B.T. or Cor. stone called for $\frac{1}{4}$ Cor. Falls on sand-
 stone out crop 8'x10'x6' High in area of many sandstone outcrops &
 boulders. At cor. point drill rock & set (SEE SKETCH IN FILE)
 Set - Brass Cap in concrete 7"x7"x3" high Brass Cap. Mkd:
 County Surveyors T 25 S
 Office, 1969 R9W S24/ R8W
 No trees available for B.T's--Set 5/8" I.R. S. 87° W.
 16.4 Ft. & Set 5/8" I.R. N. 29° W. 7.8 Ft. along side O.B.T. stump.
 Creek Bears East 25.0 Ft. also Weyerhaeuser reference
 40" Hemlock S. 85° E 44.2 Ft. "W" Nail & Tag this tree across
 creek on very steep slope 5-21-69

$\frac{1}{4}$ Corner Common to Sec. 34, T25-8W. and Sec. 3, T26-8W. 72
 (Cor. Set By Proportionate Measurement)
 Set- 5/8" Iron Rod and Aluminum Cap.
 Scribed- 24" R. Cedar S. 80° E. 29.1 ft.
 6" Hemlock N. 66° W. 12.5 ft.

Howard Johnstone
 Rebrg. Lbr.
 Feb., 1970
 Map M 39 - 13

Vernon "Ray" Tracy
 Jack Heritage & V. Perron
 1968-1969
 C. S. File No. 54/72

N. W. Corner Section 6, T 25 - 8 W. Closing Corner. 73
 Found - $\frac{1}{2}$ " Steel Pine, See Ren. #27. and Weyerhaeuser BT's.
 Orig. 60" Cedar, down, S. 86° W. 7.3 ft., scribe visible on
 decaying blaze.
 Orig. 12", now 16" Cedar, Alive, S. 60° E. 51.5 ft., open, scribe vis.
 Rescribed: "T25S R8W S 6 CC CS BT".
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 25 S
 (Reset Steel Tube alongside) Office, 1970 R9W S 6 R8W
 New BT: 13" Hemlock S. 15° W. 26.0 ft. mkd: " CC CS BT".
 This corner lies on N.E. slope in old growth timber.
 Also found 15X12X3" Sandstone mkd: "CR 6", no record at this time. 8/26/70

Vernon
 R. Tracy
 C.S. File
 54/72

Section Corner common to Secs. 21 - 22 - 27 and 28. 74
 Set - 1 1/2" x 3' Iron Pipe with Brass Cap Mkd: T25S R8W
 Ref. & Scribed: 12" Hemlock N. 53° E. 69.1 ft. 21 | 22
 Mkd: S22 T25S R8W BT. 28 | 27
 10" Hemlock N. 69° W. 47.4 ft. 1970
 Mkd: S21 T25S R8W BT.
 8" Hemlock S. 66° E. 22.5 ft. (Mkd: S27 T25S R8W BT)
 12" Fir S. 86° W. 17.4 ft. (Mkd: S28 T25S R8W BT)

Craig L. Templin
 For Weyerhaeuser Co.
 Oct. 15, 1970 C.S. 55/177

$\frac{1}{4}$ Corner common to Sections 21 and 22. 75
 Set - 1 1/2" x 3' Iron Pipe with Brass Cap mkd: $\frac{1}{4}$ S
 Referenced & Scribed: 21 | 22
 1970
 6" Hemlock N. 78 1/2° E. ? 1.5 feet (Mkd $\frac{1}{4}$ S BT) FD. OK 6/94
 5" Hemlock S. 32° W. 21.9 ft. (Mkd $\frac{1}{4}$ S BT) BY QUIMBY M 120-17