

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 25

T. S.

R 8

R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

104

C O N T.

G. Langlitz
F. Silagy
Doug. Co. Surveyors
Office
W. Rogers, BLM
April 9, 1979
C.S. 60/24

A 10" D. Fir, scribed "1/4 S10 BT" on a single blaze bears S.69°W., 9.6 ft.
A 15" D. Fir, scribed "1/4 S11 BT" on a single blaze bears N.83 1/4°E., 4.0 ft.
WE OBLITERATE the 1967 Douglas County Surveyor's Office monument and accessories as follows: We leave the monument in place and deface the markings "T25S R8W 1/4 S10 S11". We completely remove the scribing from both of the 1967 bearing trees.
From the BLM brass cap, the 1967 Douglas Co. Surveyor's Office monument bears S.44°E., 18.1 ft.

4/9/79

105

1/4 Corner for Sections 8 and 17.
Narrative: During March, 1977, Weyerhaeuser Co. surveyed the boundary common to Sections 8 and 17, T. 25 S., R. 8 W and set the common 1/4 corner at the porportionate distance as described in the original GLO survey and recorded same. See Ren. #100. Subsequently, cadastral surveyors from the Roseburg BLM office uncovered evidence of the original 1/4 corner at a point 181.1 ft. west and remonumented it.
On April 29, 1980, we destroyed all evidence of our set corner. Ren. #100.
Original GLO records called for two alder bearing trees as follows:

- 8" Alder, S.75°W., 35 links.
- 10" Alder, N.30°W., 20 links.

We found on 4/29/80:

- BLM brass cap dated 1979 from which:
- 12" Alder snag OBT with face and BLM tag, S.57 1/2°W., 35 links.
- 16" Alder OBT, scribing visible and BLM tag, N.50 1/2°W., 20 links.
- 8" Red cedar (scribed 1979), S.56 1/2°W., 06 1/2 links.
- 14" Red cedar, (scribed 1979), N.49 1/2°W., 36 links.

DCSO note: The Cadastral survey referred to is unofficial and not yet of record in our office. However, a copy of that particular corner from the 1979 survey was received and is attached to Reppeto's information in the C.S. file 58/141.

4/29/80

106

Ronald G. Geisler
L.S. #1988
For Champion Inter-
national Corp.
Feb.-Mar. 1983
M 93 - 79

Witness Corner, Secs. 1 and 12; and Secs. 6 & 7 of T.25-7
Found - 3" BLM brass cap on a 2 1/2" iron pipe set in 1964, on the north bank Unpqua River.
14" fir bears N. 43 1/2°E., 62.0 ft. Closed face. (1964)
Chiseled "X BO" on an 8' x 4' x 4' boulder bears S.27°E., 19.8 ft.
Chiseled "X BO" on a 3' x 2' x 2' boulder bears N.47°W., 8.6 ft.
Set - Chiseled "X" on a 4' x 3' x 2' boulder bears S. 15 1/2°W., 18.7 ft

2-3/83

107

1/4 Corner for sections 11 and 12
Found - 1964 Cadastral brass cap and iron pipe.
14" fir, N.7°E., (Rec. N. 4 1/2°E.) 37.0 ft. healed.
7" fir, N.75 1/2°W., 40.3 ft. down.
New BT - 9" fir, S.15°W., 27.7 ft. scribed.

108

Howard Johnstone,
L.S. #498
For: Roseburg
Lumber Company
August 10, 1983
M 94 - 63

Section corner for secs. 12 and 13 only, east side.
Found - 1962 county brass cap and iron pipe in root wad of blown down SW BT. Ren. #18
18" fir, S.55°W., 23.1 ft. part. healed.
22" fir, N.18°W., 62.0 ft. leaning
52" fir, S.85°W., 10.6 ft. down.
30" fir, S.65°E., 17.8 ft. down and rotted.
Set - Reset brass cap and iron pipe at record bearing and distance from standing BTs.
New BT - 13" cedar, S.67°E., 28.2 ft.

109

Center 1/4 corner for section 12
Set - 5/8" x 36" iron rod with alum. cap mkd, RLS 498.
BTs - 6" fir, N.24°E., 17.9 ft.
6" fir, S.1°E., 20.2 ft. (See also Ren. #5)

8/10/83