

Douglas County Surveyor's Record of
Government Corners Renewed

T 25 T. S. R 8 R.W.W.M.

FOKE-CHAPMAN CO., EUGENE, ORE. 91891

115

C O N T - - - - (CC Cor. Secs. 29 and 32)

Douglas County Surveyors
Office - Randall
Smith, Stephen Flause
Oct. 12, 1988
C.S. 62/59

A previously unrecorded corner reference, a 40" dia. 24" tall
D. fir stump cut as a logging cable anchor with no evidence of
blazes or scribing bears N.18½°W., 30.4 ft. (metal tag on stump
records bearing and dist. as N.16½°W., 28.4 ft.)
Set - The corner position as determined from the found bearing trees
is monumented with a PK nail driven into a small ledge of bedrock
chisled out for this purpose. Directly plumb over the above PK
nail is set the found brass cap monument with added marks "RESET
1988". A rough mound of stone is built up around the BC. Monu-
ment now protrudes 7" above mound of stone.

Corner lies on steep northerly slope near crest of easterly running spur
ridge. Corner is in old growth timber near edge of recent clear cut.

10/12/88

116

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
August 4, 1992
C.S. 64/31

1/4 Corner for Sections 30 and 31.
Found - 3½" dia. Brass cap (B.L.M. properly marked dated 1972) on a
2½" O.D. iron pipe protruding 8" above ground. See Renewal #91.

Accessories Found -

18" now 36" dia. 3' high Hemlock stump with a partially healed
blaze, illegible scribe mark visible, bears N.6°W., 23.1 ft.
(rec. N.8°W., 23.1 ft.)

10" now 23" dia. 6' high Hemlock stump with a fully healed blaze,
bears S.9½°E., 17.2 ft. (rec. S.6°E., 17.2 ft.) orig. BT.

New Accessories -

15" dia. Hemlock double blazed and scribed "¼ S30 CS BT"
bears N.20°E., 41.8 ft.

18" dia. 1 ft. high stump with boat spiike set through BT tag
near center of stump, B.S. bears S.31°W., 21.1 ft.

8/4/92

117

Ronald Geisler, LS 1988
For: International
Paper Corp.
April/June 1983
M 94-31

1/4 Cor. Secs. 25 & 30 T25-7

Found - 1964 BLM BCIP & the following accessories:
18" Fir, bears S.34°W., 8.5' (no record found)
13" Fir, bears N.70°E., 6.4' (rec. = N.76°E., 7.3', 1964)
Both BTs have closed faces.

118

Section corner to 21 & 28 only

BT's fd. - 60" Fir, N.85°E., 37', healed stump
16" Hemlock, S.61°E., 40.1', part healed stump

Set monument -

5/8" x 28" Iron rod & aluminum cap marked "LS 2354" 6" below
surface of dirt road at record bearing & dist. from fd. BT's.

New Accessories -

7" fir, N.88°E., 27.1', scribed "S21 BT"

6" fir, N.36°E., 23.3', scribed "S21 BT"

8" fir, S.76°E., 36.2', scribed "S28 BT"

8" alder, S.18°W., 37.5', scribed "S COR BT"

119

¼ cor to sec. 21 & 28

Monument Fd.- 3/4" Iron Pipe
Bt's Found - 18" fir, S.71°W., 20.3', stump scribe visible

New Accessories -

11" madrone, S.13°E., 79.8', scribed "¼ S BT"

12" chinquapin, S.11°W., 84.1', scribed "¼ S BT"

Monument set - 5/8" x 26" Iron rod & aluminum cap mkd. "LS 2354 R M",
N.45°W., 15'

5/8" x 26" iron rod & aluminum cap mkd. "LS 2354 R M",
N.44°E., 10"

Mark Smalley
For : Weyerhaeuser Co. &
Kenneth Ford
Oct. 1994 - M 119 - 41