

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

- 27**
- Section Corner to Sections 3 and 4, T27-1W.
Found - Corner Stone, firmly set, mkd. with 3 notches E - W.
18", now 18" D. Fir, S. 6° W. 11.9 ft., shows good scar.
18", now 22" D. Fir, S. 61° E. 21.8 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S RLW S 33
Office, 1969 T 27 S S 4 | S 3
- Bearing Trees O. K. & Tagged.
This corner lies 89.8 ft. West of Sec. Cor. 33 & 34, T26-1W.
- - - - - 11/13/69
- 28**
- 1/4 Corner to Sections 3 only, T27-1W.
Found - Corner Stone, firmly in ground, mkd. "1/4" on south side.
10", now 12" Hemlock S. 67° E. 9.2 ft., scribe visible.
10"(?), now 38" D. Fir, S. 57° W. 25.7 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S RLW 1/4 S 3
Office, 1969 T 27 S S 3
- Bearing Trees O. K. and Tagged.
This Corner lies 92.4 ft. west of 1/4 Corner Sec. 34, T26-1W.
- - - - - 11/13/69
- 29**
- 1/4 Corner to Section 34 only.
Found - No trace of Corner Stone.
36" D. Fir, now stump, N. 32° E. 23.1 ft., shows good scar.
12" Hemlock, now stob, N. 78° W. 15.8 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S RLW 1/4 S 34
Office, 1969 T 27 S S 3
- New BT's: 7" Hemlock N. 47° E. 32.9 ft., mkd: "1/4 S34 CS BT."
8" Hemlock N. 13° E. 30.0 ft. mkd: "1/4 S34 CS BT."
This corner lies 92.4 ft. E. of 1/4 Corner Sec. 3, T27-1W.
- - - - - 11/13/69
- 30**
- Section Corner to Sections 32 and 33 only.
Found - No trace of corner stone.
8", now 13" Fir, N. 72° E. (Rec. N82E) 9.2 ft. I find this tree
to be a cedar, scribe visible.
10", now 15" Fir, N. 65° W. 17.2 ft., opened for scribe "S3".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S RLW S 32 | S 33
Office, 1969 T 27 S RLW S 4
- Bearing Trees O. K. and Tagged.
- - - - - 11/5/69
- 31**
- Section Corner to Sections 4 and 5 only, T27 - 1W.
Found - No trace of Corner Stone nor S. W. BT.
12" Hemlock, now Spag, S. 44° E. 51.5 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S RLW S 32
Office, 1969 T 27 S RLW S 5 | S 4
- New BT's: 15" Hemlock S. 24° W. 40.1 ft. mkd: "T27S RLW S 5 CS BT".
13" Cedar S. 28° E. 53.2 ft. mkd: "T27S RLW S 4 CSB T".
- - - - - 11/5/69
- 32**
- Section Corner to Sections 34 and 35 only.
Found - 48" D. Fir Corner Tree, good scars.
5", now 6" Hemlock N. 31° E. 2.6 ft., scribe visible.
40", now 46" D. Fir, N. 26° W. 9.9 ft., shows good scar.
Set - Brass Cap on N. Side of Corner Tree Mkd: T 26 S RLW S 34 | S 35
County Surveyor's Office, 1969 T 27 S S 2
- New BT: 7" Hemlock N. 75° E. 25.6 ft. mkd: "T26S RLW S35 CS BT".
This corner lies 85.0 ft. W. of Cor. to Secs. 3 & 2, T27-1W.
- - - - - 11/6/69
- 33**
- Section Corner to Sections 3 and 2 only, T27-1W.
Found - Mound of Stone at Corner, Stone mkd. with notches, not found.
28" Hemlock, now snag, S. 67° E. 21.1 ft., scribe visible.
28", now 38" Hemlock, S. 70° W. 24.4 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T26S RLW S 34
Office, 1969 T27S RLW S 3 | S 2
- New BT: 40" Hemlock S. 62° E. 41.0 ft. mkd: T27S RLW S2 CS BT.
This corner lies 85.0 ft. E. of Corner Secs. 34 & 35, T26-1W.
- - - - - 11/6/69

John M. Powell
Frank Jones & W. Penley
November, 1969 C.S. 54/94