

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

South $\frac{1}{4}$ Corner to Section 33 only. 34
 Found - No trace of Corner Stone.
 10", now 13" D. Fir, N.60°E. 16.5 ft., opened for scribe.
 24", now 27" D. Fir, N.29°W. (Rec. N21W) 7.9 ft., shows good scar.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S R 1 W
 Office 1969 $\frac{1}{4}$ $\frac{S \ 33}{T \ 27 \ S}$
 Bearing Trees O. K. and Tagged. 12/1/69

Wit. Cor. $\frac{1}{4}$ Corner to Section 4 only, T27-1W. 35
 Found - Stone, firmly set, at Wit. Corner, mkd: "WC $\frac{1}{4}$ ".
 14", now 37" D. Fir, S.30°E. 15.4 ft. (Rec. 13.4), shows good scar.
 24", now 31" Hemlock, S.26°W. 4.6 ft., shows good scar.
 This corner is a Witness Corner, 13.2 ft. west of $\frac{1}{4}$ Corner. True
 corner falls on bluff.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T26S W.C. 13.2' East
 Office, 1969 T27S RLW to $\frac{1}{4}$ $\frac{S \ 4}{S \ 4}$
 Bearing Trees O. K. and Tagged. 12/1/69
 This corner lies 4.0 ft. south of 40 Foot bluff.

North $\frac{1}{4}$ Corner Section 5 only, T27-1W. 36
 Found - 12x8x8 Stone, firmly set, mkd: " $\frac{1}{4}$ ".
 12", now 15" Hemlock, S.38°E. 9.9 ft., scribe visible.
 6"^{FIR}, now 8" Hemlock, S.35°W. 16.5 ft., shows good scar
 Set - Brass Cap at Cor. Mkd: County Surveyor's T26S RLW $\frac{1}{4}$ $\frac{S \ 5}{S \ 5}$
 Office, 1969 T27S
 Bearing Trees O. K. and Tagged. 12/4/69

$\frac{1}{4}$ Corner Section 32 only, T26-1W. (South Bdry) 37
 Found - 48" D. Fir Corner Tree, now snag, rotted face, scribe visible, " $\frac{1}{4}$ S32".
 No trace of small Bearing Trees.
 This corner lies at top of 60 ft. bluff, BT's. probably went over.
 Set - Brass Cap on N. side of Cor. Tree, directly under face:
 Set - Brass Cap at Cor. Mkd: County Surveyor's T26S RLW $\frac{1}{4}$ $\frac{S \ 32}{S \ 32}$
 Office, 1969 T27S
 New BT's: 7" Cedar N.89°W. 20.0 ft. mkd: " $\frac{1}{4}$ S32 CSBT".
 8" Cedar N.50°W. 20.0 ft. mkd: " $\frac{1}{4}$ S32 CS BT". 12/4/69

Section Corner to Sections 5 and 6 only, T27-1W. 38
 Found - Corner Stone, right size, but no marks.
 36", now 40" Cedar, S.28°W. (Rec. S34W) 34.3 ft., scribe visible.
 36", now 40" D. Fir, S.35°W. 22.4 ft., shows good scar.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T26S RLW $\frac{S \ 31}{S \ 6 \ S \ 5}$
 Office, 1969 50 T27S
 Bearing Trees O. K. and Tagged. 12/4/69

Section Corner to Sections 31 and 32, only, T26-1W. 39
 Found - No trace of Stone.
 24", now 36" Cedar, N.34°E. 7.9 ft., rotten face. 51
 12", now 15" Hemlock, N.19°W. 21.8 ft., scribe visible, rotten face.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T26S RLW $\frac{S \ 31 \ S \ 32}{S \ 5}$
 Office, 1969 T27S
 Reblzd. & Resbd: 36" Cedar N.34°E. 7.9 ft. mkd: "T26S RLW S32 CS BT".
 15" Hemlock N.19°W. 21.8 ft. mkd: "T26S RLW S31 cSBT". 12/4/69

$\frac{1}{4}$ Corner to Section 31 only, T26-1W. 40
 Found - No trace of Corner Stone nor N.W. BT.
 12", now 25" Cedar, N.76°E. 48.2 ft., scribe visible.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T26S RLW $\frac{1}{4}$ $\frac{S \ 31}{S \ 31}$
 Office, 1969 T27S
 New BT: 10" Hemlock N.77°W. 29.2 ft., mkd: " $\frac{1}{4}$ S31 CS BT".
 Bear. & Dist. btwn. $\frac{1}{4}$ Sec. 6 and $\frac{1}{4}$ Sec. 31 is S.82°W. 117.6 ft.
 (Record West 125.4 ft.) 12/17/69

John M. Powell
 Frank Jones & W. Penley
 December, 1969 C. S. File No. 54/94