Douglas County Surveyor's Record of Government Corners Renewed

T. 26 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

41

¼ Corner to Section 6 only, T27-1W.
Found - 20x18x5 Corner Stone, in place & mkd: "¼" on south side.
40", now 50" Cedar, S.37°W. 22.4 ft., shows scribing.
No trace of S.E. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1969 T26S / T27S R1W ¼ S 6
New BT: 6" Hemlock S.36°E. 13.1 ft.mkd: "¼ S 6 CS BT".
The ¼ Sec. 6 only lies 117.6 ft. S.82°W. from ¼ Sec. 31 only on steep, N. slope.
12/17/69

E. S. File No. 54/94

– – – – – –

42

Section Corner to Sections 9 - 10 - 15 - 16.
Found - Orig. 60", now 60" Fir Snag, N.53°W. 26.4 ft., scribe marks visible on decaying blaze.
Orig. 40",now 40" Fir Snag, S.19°E. 42.0 ft., (Rec. 24.4').
No trace of Corner Stone or other Orig. BT's.
Ridge Call of 16.5 ft. West fits this point good.
Set - Brass Cap at Cor. Mkd: (Cap in Rock Mound) County Surveyor's Office 1970 T 26 S R 1 W: S 9 | S 10 / S 16 | S 15
New BT's: 8" D.Fir N.37°W. 6.6 ft. mkd: T26SR1W S9 CS BT.
7" D.Fir S.58°W. 17.5 ft.mkd: T26S R1W S16 CS BT.
5" D.Fir S.76°E. 15.0 ft. mkd: S15 CS BT.
6" D.Fir N.31°E. 17.8 ft.mkd: S10 CS BT.
3/3/70

– – – – – –

43

Section Corner to Sections 3 - 4 - 9 - 10.
Found - Corner Stone, tipped over. Also Mound of Stone as described West of Corner.
Orig.40",now 41" Fir Snag, N.22°E. 86.5 ft., scribe visible on unhealed blaze.
Orig.28",now 32" Fir, alive, S.49°E. 45.5 ft., shows good scar, we tag.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1970 T 26 S R 1 W: S 4 | S 3 / S 9 | S 10
New BT: 36" D.Fir N.25°E. 106.5 ft. mkd: "T26S R1W S 3 CS BT"
No trees available in sections 4 & 9 due to solid rock bluffs.
This corner lies at top of bluff 30 ft. high. Waterfall approx. 200 ft. high bears N.83°W. approx. 400 ft. distance.
3/4/70

– – – – – –

44

¼ Corner to Sections 8 and 9.
Found - Corner Stone, in place, mkd: "X" on top &"¼" on West face.
Orig.8",now 12" Fir Snag, S.69°E. 24.4 ft., scribe & blaze obliterated by previous excessive chopping.
Orig. 12",now 25" Fir, alive, N.41°W. 33.0 ft., scribe visible in previously opened blaze.
Set - Brass Cap at Cor. Mkd: (Reset Stone alongside) County Surveyor's Office, 1970 T 26 S R 1 W: ¼ S 8 | S 9
New BT's: 7" D.Fir N.65°W. 6.7 ft. mkd: "¼ S8 CS BT.
8" D.Fir S.19°E. 12.5 ft. mkd: "¼ S9 CS BT.
This corner lies on steep southerly slope about 400 ft. N. of P.P. & L. transmission line.
3/4/70

– – – – – –

45

¼ Corner to Sections 5 and 8.
Found - Corner Tree Gone.
Orig. 12",now 13" Fir, now 15' high snag, N.30°W. 13.9 ft., scribe visible on unhealed blaze.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1970 T 26 S R 1 W: ¼ S 5 / S 8
New BT's: 14" D.Fir N.30°E. 24.8 ft. mkd: "¼ S5 CS BT".
7" D.Fir S.63°W. 33.0 ft. mkd: "¼ S8 CS BT".
This cor. lies on steep, easterly slope about 300 ft. west of Fall Creek, good blazed line East of corner.
3/5/70

– – – – – –

Vernon "Ray" Tracy
Jack Heritage & V. Perron
March, 1970 C.S. File No. 52/77