

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 1 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 971881

Clell Goodwin
Vic Cangie
Lenora Ladig
CS 57/36
9/30/75

1/4 Corner to Sec. 26 & 35

Found: 6"x4"x5" stone scribed 1/4 on north face from which a 18" stump with visible scribe bears S35°E., 17.8 ft. and a rotted 10" stump bears N75°E., 9.2 ft.

New: We set at the corner a 1 1/2"x30" I.P. with brass cap stamped:

DOUGLAS CO. SURVEYOR
1975

T 26S RIW
S 26
S 35

We set the stone alongside from which:

A 15" Hemlock scribed "1/4 S 35 CS BT" in a double blaze bears S 4 1/2°E., 33.4ft.

A 18" Fir scribed "1/4 S26 CS BT" in a double blaze bears N23 1/2°W., 74.3ft
Compass declination 20° East

NOTE: Corner lies approx 50' south of road to rock pit and on west edge of clear cut.

1/4 Corner to Sec. 35 & 36

Found: 20" fir stump that bears N30°E., 23.1' dist. Scribing "1/4 36 BT" visible on unhealed blaze.

36" now 40" fir that bears S20°W., 8.6' dist. bearing healed blaze.

We open and find "BT", alive and well.

At corner determined from intersection of dist. and bearings of above BT's we find no trace of orig. basalt stone.

Set: A 1" X 30" I.P. with brass cap stamped: Douglas County Surveyor

T26S RIW
S35 | S36

1/4 1976

New BT: 9" Hemlock bears N21°E., 31.0' dist. marked "1/4 S36 CS BT" in a double blaze.

NOTE: Corner is approx. 300' East of Road #2616.

Compass dec. 20° East.

71

72

A. Victor Cangie
Peter L. Earle
County Surveyor's
Office
C.S. 59/15
5/27/76