

Douglas County Surveyor's Record of  
Government Corners Renewed

26 T. S. 1 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Clell Goodwin  
Vic Cangie  
Lenora Ladig  
CS 57/36  
9/30/75

1/4 Corner to Sec. 26 & 35 71  
Found: 6"x4"x5" stone scribed 1/4 on north face from which a 18" stump with visible scribe bears S35°E., 17.8 ft. and a rotted 10" stump bears N75°E., 9.2 ft.  
New: We set at the corner a 1 1/2"x30" I.P. with brass cap stamped:  

	T 26S RLW
DOUGLAS CO. SURVEYOR	S 26
1975	S 35

  
We set the stone alongside from which:  
A 15" Hemlock scribed "1/4 S 35 CS BT" in a double blaze bears S 4 1/2°E., 33.4ft.  
A 18" Fir scribed "1/4 S26 CS BT" in a double blaze bears N23 1/2°W., 74.3ft  
Compass declination 20° East  
NOTE: Corner lies approx 50' south of road to rock pit and on west edge of clear cut.

A. Victor Cangie  
Peter L. Earle  
County Surveyor's  
Office  
C.S. 59/15  
5/27/76

1/4 Corner to Sec. 35 & 36 72  
Found: 20" fir stump that bears N30°E., 23.1' dist. Scribing "1/4 36 BT" visible on unhealed blaze.  
36" now 40" fir that bears S20°W., 8.6' dist. bearing healed blaze.  
We open and find "BT", alive and well.  
At corner determined from intersection of dist. and bearings of above BT's we find no trace of orig. basalt stone.  
Set: A 1" X 30" I.P. with brass cap stamped: Douglas County Surveyor  

T26S RLW
S35   S36
1/4 1976

  
New BT: 9" Hemlock bears N21°E., 31.0' dist. marked "1/4 S36 CS BT" in a double blaze.  
NOTE: Corner is approx. 300' East of Road #2616.  
Compass dec. 20° East.

Karen Cheney  
James Cook  
A. Victor Cangie  
Douglas County  
Surveyor's Office  
C.S. 59/15  
5/25/76

1/4 Corner to Sec. 25 and 36. 73  
Found - A conglomerate stone 15" X 12" X 8" with "1/4" marked on North face. From Which - An original 7" Hemlock bears N19°E., 11.2 ft. dist. Visible scribing "4 S25 BT". Alive and well.  
A 48" downed fir, hole hits good for called bearing and dist. No visible blaze.  
Set - At corner point established from original N.E. BT a 1" X 30" I.P. with brass cap marked: Douglas County Surveyor  

T26S RLW
S25
S36
1976

  
NOTE - On North side of brass cap replaced original stone.  
New BT - A 16" Hemlock bears S21°E., 24.3 ft. marked "1/4 S36 CS BT" in double blaze.  
Compass dec. 20° East.

Maurice E. Farr  
For: Umpqua National  
Forest  
Jan. 1977  
M 63 - 20  
C.S. 58/138

1/4 Corner for Secs. 4 and 9. 74  
Set - 1" Iron Rod, 6 ft. in the ground, with a 1" x 36" I.P. over the rod. a 2 1/2" Brass cap on the pipe stamped T26S RLW 1/4 S4 S9 PE 5188 1977. From which bears:  
a 7" D. Fir, N.9°15'E., 99.0 ft. blazed and scribed "1/4 S4 BT".  
a 10" D. Fir, S.7°15'E., 125.2 ft. blazed & scribed "1/4 S9 BT".

Center 1/4 Corner For Sec. 9 75  
Set - 1" x 36" I.P. with a 2 1/2" Brass cap stamped T26S RLW C 1/4 S9 PE 5188 1977. From which bears:  
a 18" D. Fir, N.63°30'W., 9.0 ft. blazed & scribed "1/4 S9 BT"  
a 38" D. Fir, S.85°E., 7.0 ft. blazed & scribed "C1/4 S9 BT".  
1/77