

Douglas County Surveyor's Record of  
Government Corners Renewed

T 26 T. S. R 1 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE., 21881

81

1/4 Corner for Sec. 35 only of T25-1.

Found - 15" x 10" x 10" stone marked "X" on top and "1/4" on the north face. Stone is firmly set in the ground.  
Orig. 24" now 38" D. Fir bears N.35°E., 69.4 ft. (Rec. 96.4 ft.)  
Has a healed blaze.  
Orig. 15" now 41" D. Fir bears N.70°W., 13.5 ft. (Rec. 14.52 ft.)  
Has a healed scar. Placed County BT signs on both which are alive and well.  
Orig. 14" now 41" D. Fir (scribing supposedly destroyed by Mensch in 1910) bears S.5°E., 22.8 ft. (Rec. S.6 1/2°E., 17.82')  
Has a healed scar. Placed a County BT sign on it.  
Set - Removing the corner stone, I set in it's place a 2 1/2" Brass Cap on a 1" Iron pipe stamped: County Surveyor's Office T25S RLW 1977 S 35 1/4 only

I buried the original corner stone alongside.

No new accessories. Corner lies 100 ft. east of ridge top and old cat road.

9-15/77

82

Section Corner for Secs. 2, 3, 10 and 11.

Found - Stone, 16"x10"x8" and marked "X" on top, solidly set in the ground & covered with duff. 5 grooves on the "J" (broken S.E. face) and 2 grooves on the east face.  
A 51" D. Fir bears N.30°W., 43.7 ft. (Rec. N.31 1/2°W., 48.18 ft.)  
scribing visible on previously opened blaze "26S RLW S3 B"  
A 47" D. Fir bears N.7°E., 112.1 ft. (Rec. N.7°E., 111.54 ft.)  
BT's to the south are gone without a trace.  
Placed County BT signs on all 5 bearing trees.  
Set - Moving orig. corner stone aside, I SET in it's place a 2 1/2" Brass cap on a 1" Gal. I. Pipe marked County Surveyor's Office T26S RLW S3 S2 1978. S10 S11

I bury orig. corner stone alongside.

New BT's- A 11" D. Fir bears N.84°W., 9.1 ft. scribed "T26S RLW S3 CS BT" on a double blaze.  
A 14" D. Fir bears S. 17 1/2°W., 31.8 ft. scribed "T26S RLW S10 CS BT" on a double blaze.  
A 17" D. Fir bears S.31°E., 32.3 ft. scribed "T26S RLW S11 CS BT" on a double blaze.

Corner lies on a steep southeast slope approx. 200 ft. NW of the old North Umpqua Road.

1/19/78

83

1/4 Corner for Secs. 27 and 26.

Found - A 36" D. Fir stump with partly healed blaze bears N.47°E., 6.6 ft. scribing visible "4 S 26". Stump has been slightly disturbed during logging.  
BT to the NW is gone.  
Set - 2 1/2" Brass cap on a 1" I.P. stamped County Surveyor's Office T26S RLW 1/4 S27 S26 1978". Used only remaining BT stump as reference.

New BT - A 34" D. Fir bears S.69 1/2°E., 211.0 ft. scribed "1/4 S26 CS BT" on a double blaze.

Set - A 5/8" Re-bar in a 36" Fir stump, re-bar bears S.34°W., 28.9 ft.  
Placed Co. BT signs on all 3.  
Corner falls in skid trail.

1/19/78

84

1/4 Corner for Secs. 3 and 10.

Found - Stone, set solidly in place, mkd. "1/4" on the north face. stone measures 14" x 11" x 7".  
24" now 50" D. Fir bears N.78°E., 17.6 ft. There are 3 small axe marks on the bark facing the corner & a healed blaze on the south side of the tree.  
A 20" now 35" D. Fir snag bears S.12°W., 34.3 ft. Has a healed blaze which faces corner.  
Set - Moving the orig. corner stone aside, I set in its place a 2 1/2" B.C. on a 1" I.P. mkd. County Surveyors Office T26S RLW 1/4 S3 S10 1978.  
I bury the corner stone alongside.  
New BT - A 29" D. Fir bears S.16 30°W., 94.9 ft. scribed "1/4 S10 CS BT" on a double blaze. Corner lies 250 ft. north of power line.

Dennis Gaylord U.S.F.S.  
Doug. Co. Surveyors  
Office Deputy  
Witness: Travis  
Worthen  
Sept. 15, 1977  
59/40

Dennis Gaylord, U.S.F.S.  
Deputy, Doug. Co. Surveyors Office  
Roland Simshauser, witness  
Jan. 19, 1978  
C.S. 59/46

Dennis Gaylord USFS  
Deputy, Doug. Co.  
Surveyors Office  
Roland Simshauser  
Jan. 26, 1978  
C.S. 59/46