

Douglas County Surveyor's Record of  
Government Corners Renewed

T 26 T. S. R 1 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(NATC: #85 Not Used)

86

1/4 Corner for Secs. 16 and 21.

Found - Orig. corner stone is set solidly in place. Stone, 16" x 12" x 6", is mk. "X" on top and "1/4" on north face.

30" now 37" D. Fir bears N.81°30'W., (Rec. N.78°W.) 15.2 ft. (Rec. 14.52 ft.) Has a healed blaze. This tree is nearly dead.

A 29" D. Fir stump bears S.40°E., 29.7 ft. to the face. Reverse scribing visible "S21 BT".

Set - Moving orig. stone monument aside, I set in its place a 2 1/2" Brass cap on a 1" G.I. pipe. Cap stamped County Surveyors Office T26S R1W 1/4 S16 S21 1978. I bury the cor. stone alongside.

New BT's - A 11" D. Fir bears S.74°30'W., 13.5 ft. scribed "1/4 S21 CS BT" on a double blaze.

A 9" D. Fir bears N.57°E., 29.2 ft. scribed "1/4 S16 CS BT" on a double blaze.

Corner lies on south edge of clearcut unit.

1/26/78

87

1/4 Corner for Secs. 11 and 14.

Found - A 29" badly decomposed Fir snag. An unhealed blaze on the South side with scribing "14" visible. Axe marks on bark on the North side & no scribing remaining.

A 38" (Rec. 36") Fir snag bears N.43°E., 18.7 ft. Scribing visible "1/4 S11 B0", on partly decomposed face. (Rec. distance is 19.8 ft.).

The orig. BT to the SE is gone.

Set - Removing the remains of the orig. corner tree, I SET a 2 1/2" brass cap on a 1" galv. I.P.. stamped: County Surveyors Office

1/4 T26S R1W  
S11 1978  
S14

BT's - A 10" D. Fir bears N.11°E., 12.6 ft. scribed "1/4 S11 CS BT" on a double blaze.

A 20" D. Fir bears S.79°30'E., 27.7 ft. scribed "1/4 S14 CS BT" on a double blaze.

Placed County BT signs on both trees.

2/78

88

Section Corner for Secs. 10, 11, 15 and 14.

Found - Orig. corner stone firmly set in the ground, measures 18" x 9" x 7" & is marked "X" on top & has 4 notches on the South edge and 2 notches on the East edge.

Orig. BT to the SW is down & decayed. Stump hole bears S.87°W., 9.24 ft.

Orig. 38" now 37" D. Fir snag bears N.65°W., 54.8 ft. (Rec. N.63°W) Axe marks on bark where blaze was.

Orig. 24" now decayed Fir snag bears S.21°E., 14.48 ft. (Rec. S.24°E., 15.18 ft.) Has axe marks on bark where blaze was.

Orig. 24" now decayed D. Fir snag bears N.87°E., 16.5 ft. Axe marks on bark where blaze was.

Set - Moving the corner stone aside, I SET in it's place a 2 1/2" B.C. on a 1" I.P. stamped: County Surveyors Office T26S R1W S10 S11 S15 S14 1978. I bury the corner stone alongside.

New BT's - A 30" D. Fir bears N.79°30'E., 40.1 ft. scribed "T26S R1W S11 CS BT" on a double blaze.

A 26" D. Fir bears N.64°W., 41.0 ft. scribed "T26S R1W S10 CS BT" on a double blaze.

A 21" D. Fir bears S.70°W., 7.3 ft. scribed "T26S R1W S15 CS BT" on a double blaze.

A 16" D. Fir bears S.9°E., 24.2 ft. scribed "T26S R1W S14 CS BT" on a double blaze.

2/78

Dennis Gaylord, USFS  
Deputy, Douglas Co. Surveyors Office  
Randal Lopez & Jim Talburt, Witnesses  
Feb. 16 & 23, 1978  
C.S. 59/46