

Douglas County Surveyor's Record of  
Government Corners Renewed

T 26

T. S.

R 1

R.W.W.M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

89

Dennis Gaylord, USFS  
For: Douglas Co. Surveyors Office  
Witness: James Davis  
August 31, 1978  
C.S. 60/11

Section corner for Secs. 26, 25, 35 and 36.

Found - Orig. corner stone, 4" x 7" x 12" and marked with one notch on the east edge and one notch on the south edge, is firmly set in the ground.

A 26" D. Fir bears N.24°E., 25.8 ft. (Rec. N.22 1/2°E., 26.4 ft.) scribing visible on previously opened blaze.

A 36" D. Fir bears N.22 1/2°W., 19.3 ft. (Rec. N.25°W., 19.8 ft.) Has a healed blaze which has been previously partially opened.

A 24" Hemlock bears S.51 1/2°W., 20.2 ft. (Rec. S.54°W., 27.06 ft.) Has a healed scar. 10 lk. error in record measurement to this BT.

A 28" D. Fir bears S.68°E., 19.4 ft. (Rec. S.67 1/2°E., 19.14 ft.) Has a previously opened blaze with visible scribing. (This tree is not too healthy)

Set - Referencing the corner stone, I move it aside and set in it's place a 1 1/2" Iron pipe with a 2 1/2" brass cap marked "County Surveyor's Office T26S R1W S26 S25 S35 S36 1978". I bury the corner stone alongside the iron pipe.

New BT's- A 19" D. Fir bears S.60°E., 43.9 ft. scribed "T26S R1W S36 CS BT" on a double blaze.

Placed County BT signs on all 5 BTs.

8/31/78

90

Section Corner for Secs. 16, 15, 21 and 22.

Found - Original Corner stone marked "X" on top and with 3 notches on the South and 3 notches on the east edge, is set firmly in the ground. Stone measures 10" x 11" x 18".

A 44" D. Fir bears S.86°E., 5.94 ft. Has a healed blaze.

A 19" D. Fir bears N.12°E., 20.7 ft. (Rec. 21.12 ft.) Has a healed blaze.

A 30" D. Fir bears N.57°W., 11.22 ft. Has a healed scar.

A well decayed stump bears S.68°W., 10.56 ft. No marks or blazes visible.

Set - Referencing the corner stone, I set it aside and in its place I set a 1 1/2" Iron pipe with a 2 1/2" brass cap attached mkd. "County Surveyor's Office T26S R1W S16 S15 S21 S22 1978". I bury corner stone alongside iron pipe.

New BT's- A 25" Cedar, bears S.14°W., 41.7 ft. scribed "T26S R1W S21 CS BT" on a double blaze.

I placed County BT signs on all 4 trees.

8/31/78

91

Section Corner for Secs. 11, 12, 13 and 14.

Found - Orig. corner stone set firmly in place. Stone is marked "+" on top and has one groove on the east and 4 grooves on the south. Stone measures 12" x 13" x 17".

A 27" Fir snag bears S.24°W., 5.28 ft. scribing visible, "T26S R1W-14 BT".

No other BT's remaining.

Set - Moving the corner stone aside, I SET in its place a 1 1/2" I.P. with a 2 1/2" Brass cap attached stamped: County Surveyors Office T26S R1W S11 S12 S14 S13 1978.

New BT's-A 12" D. Fir bears S.62°30'E., 29.1 ft. scribed "T26S R1W S13 CS BT" on a double blaze.

A 6" D. Fir bears West, 42.4 ft. scribed "T26S R1W S14 CS BT" on a double blaze.

A 11" D. Fir bears N.34°W., 26.7 ft. scribed "T26S R1W S11 CS BT" on a double blaze.

A 12" D. Fir bears N.19°30'E., 22.6 ft. scribed "T26S R1W S12 CS BT" on a double blaze.

Placed County BT signs on all BT's. I bury corner stone alongside Iron Pipe.

Dennis Gaylord  
U.S.F.S.  
Deputy - Douglas  
Co. Surveyors  
Office  
Witness: James  
Davis  
Sept. 12, 1978  
C. S. 60/17