

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 S T. S. R 1 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

92

Section Corners for Secs. 14, 13 23 and 24.

Found - Orig. corner stone is set firmly in place. Stone is marked "X" on top and 3 grooves on the South. Stone measures 24" x 28" x 12" above ground.

Orig. 40" Fir is now a burned and decayed stump. Stump bears S.62°W. 6.0 ft. scribing visible, "6S T S 3 B0" No other BT's remaining.

Set - I am unable to move corner stone due to its size, S I SET a 1 1/2" Iron pipe with a 2 1/2" Brass cap, stamped: County Surveyor's Office T26S R1W S14 S13 S23 S24 W. C. 0.4' S 1978", alongside the corner stone, 0.4 ft. North of the "X" mark on the corner stone.

New BT's-A 19" D. Fir bears S.67°E., 37.5 ft. scribed "T26S R1W S24 CS BT" on a double blaze.

A 14" D. Fir bears N.56°E., 33.9 ft. scribed "T26S R1W S13 CS BT" on a double blaze.

A 19" D. Fir bears N.49°W., 17.0 ft. scribed "T26S R1W S14 CS BT" on a double blaze.

A 13" D. Fir bears S.6°W., 32.4 ft. scribed "T26S R1W S23 CS BT" on a double blaze.

All new accessories are referenced to the "X" mark on the corner stone. Placed County BT signs on all BT's.

9/14/78

93

Witness Corner for 1/4 Corner for Secs. 13 and 24.

Found - Orig. corner tree is now a 45" snag (D. Fir). Previously opened blaze on North side but face is decayed. Scribing and reverse is visible on South side of tree, "24".

No other accessories remaining.

Set - I set a 1 1/2" I.P. with a 2 1/2" Brass cap stamped: County Surveyor's Office T26S R1W 1/4 S13 S24 W.C. West 6.0' 1978" as a witness corner. Brass cap bears East, 6.0 ft. from center of corner tree snag.

New BT's-A 11" D. Fir bears N.45°E., 41.5 ft. scribed "1/4 S13 CS BT" on a double blaze.

A 10" D. Fir bears S.60°E., 27.9 ft. scribed "1/4 S24 CS BT" on a double blaze.

Trees are from the corner tree snag.

Placed County BT signs on all BT's.

9/14/78

94

Section Corner for Secs. 27, 26, 34 and 35.

Found - Orig. corner stone, marked "X" on top and with 2 grooves on the East face and one notch on the South edge, is firmly set in the ground. The stone measures 5" x 6" x 12".

A 75" D. Fir bears S.71°E., 15.84 ft. Has a healed blaze.

A 37" Hemlock bears S.3°E., 33.0 ft. Some scribing is visible on a nearly healed blaze.

A 32" Shasta Fir snag bears S.20°W., 45.54 ft. scribing visible on a partly healed blaze, T26S R1W S34 BT"

A 11" D. Fir bears N.25°W., 22.8 ft. Has a healed blaze. (This tree is crooked. Dist. is to base of tree.) Rec. dist. is 26.4 ft.

Set - Referencing the corner stone, I SET it aside and in its place I set a 1 1/2" I.P. with a 2 1/2" Brass cap attached, stamped: County Surveyor's Office T26S R1W S27 S26 S34 S35 1978". I bury the corner stone alongside the Iron pipe.

New BT - A 12" Shasta Fir bears S.43° 30'W., 58.9 ft. Scribed "T26S R1W S34 CS BT" on a double blaze.

Placed County BT signs on all 5 BT's.

9/13/78

95

Section Corner for Secs. 7, 8, 17 and 18. W. C.

Found - A 2 1/2" Brass cap buried 5" under the road surface, stamped T26S R1W S7 S8 S18 S17 1972 RPLS 544. Ren. #63

Possible orig. BT, a 42" D. Fir bears N.39°W., 44.4 ft. Has a single healed blaze. I open this tree but find no scribing. No sign of orig. corner stone. I discount this tree as being an orig. Mensch BT.

A 13" White Fir bears N.31°30'W., 36.7 ft. Some scribing visible on a nearly healed double blaze.

Dennis Gaylord, U.S.F.S.
Deputy - Douglas Co. Surveyors Office
Witness: James Davis
September, 1978
C.S. 60/17

1-79
Dennis Gaylord
U.S.F.S. Deputy
Doug. Co. Surveyors Office
Tony Flores, Witn.
March 15, 1979
C.S. 60/24