

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 T. S. R 1 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

99

1/4 Corner for Sec. 2 only of T.27-1
Found - 1" I.P. with alum. cap marked U.S.P.C. property corner T27S RLW
1963 1/4 S2 only RE 4287 Do Not Disturb".
20" Hemlock snag, S.69°W., 72.0 ft. vis. scribes Ren. #25
26" Hemlock S.26°W., 105.0 ft. visible scribes.
New BT - 24" Hemlock, S.61°W., 107.0 ft. "1/4 S2 BT".
Brass washer marked RLS #1654 set in BT face. Set post & sign 4.0 ft. South.

8/80

100

Closing corner
Section corner for Sec. 1 and Sec. 31 of T.25 1/2-1E.
Found - 1928 US GLO brass cap properly marked, on 3" iron post, firmly
set, 10" above ghe ground
A 48" Fir stump badly rotted with scribe marks "T2" visible
bears S.31°W., 48.2 ft.
A 30" D. Fir, with healed blaze bears S.36°E., 72.6 ft. (Rec.
S.38°E., 71.9 ft.)
A 16" Pine snag, with scribe marks visible on a partially healed
blaze, bears S.64°W., 23.6 ft. Ren. #11
New BT - A 20" D. Fir, bears S.16°W., 17.8 ft. marked "T 26S R1 W CC BT"
on a double blaze with a brass washer stamped "LS 536" nailed
into lower blaze.

9/80

101

W.C. to 1/4 Corner for Sec. 24 only of T.26-2
Found - 1" I.P. firmly set 4" above gro-nd with a 1916 US GLO brass cap
properly marked.
A 43" D. Fir snag, with no scribing visible on rotted blaze bears
N.63°W., 35.6 ft.
A protruding point of bluff with no orig. chisel marks visible
remarked "X B0" bears S.59°W., 3.7 ft. (Rec. S.51°W., 4.0 ft.)
A 4" x 4" X is at the exact bearing point.
New BT's- A 10" Hemlock bears N.13°W., 16.9 ft. scribed "X BT" on a
double blaze with brass washer stamped "LS 397" nailed into
lower blaze.

102

W.C. to 1/4 Corner for Sec. 19 only.
Found - Orig. 15" Cedar, opened to find scribe marks "1/4 S19" visible
bears S.24°E., 11.2 ft.
Set - 2" x 30" I.P. 18" in the ground on solid rock, in a 3 ft. diam.
times 2 ft. high mound of stone with a 3" brass cap mkd.
T26S R2W RLW 1981 LS 397
1/4 W.C.
S19
New BT's- A 7" Cedar bears S.22°E., 51.2 ft. scribed "X BT".
A 12" D. Fir bears N.41°E., 13.2 ft. scribed "X BT".

2/81

103

Center 1/4 corner for Section 8
Set - 2" x 30" iron pipe 24" in the ground with a 3" brass cap marked
"T26S RLW C 1/4 S8 1981 PLS 397".
BT's - 9" Hemlock bears S.73°E., 22.2 ft. scribed "C 1/4 S8 BT"
7" hemlock bears S.17°W., 20.5 ft. scribed "C 1/4 S8 BT".

104

1/4 Corner for Secs. 26 and 25
Found - A stone, 11 x 10" x 6" lying loose on ground surface, possibly
orig. 14" x 10" x 7" corner stone, decayed by weather scaling,
no markings visible.
An orig. 15" fir, now a 18" stump approx 4.5 ft. tall bears S.30°E
11.2 ft. Tree has good evidence of a healed blaze, no scribing
visible.
An orig. 10" hemlock, now 12" stump approx. 6.6 ft. tall bears
N.45°W., 6.6 ft. Tree has scribing 6 B visible on a partially
healed opened blaze.
Set - The position of the found stone is accepted as the corner position.
Location of stone is referenced out and the stone is removed to
be replaced by a DCSO 2 1/2" brass cap on a 1" x 30" I.P. marked:

Ronald Quimby
Romanso E. Ware
BHW, Eng.
For: U.S. Forest
Service
August 1980
M 79 - 55

Glenn Baughman LS 536
For: U.S. Forest Serv.
Sept. 1980
C.S. 58/229

George Grubb
For: U.S. Forest
Service
Feb. 1981
M 86 - 68

George Grubb
For: U.S. Forest
Service
April 1981
M 87 - 37

Stephen Flause,
Deputy, Doug. Co.
Surveyors Office
Terrie Plouff;
Karen Mosely
April 23, 1981
C.S. 61/19