

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 T. S. R 1 R.W.W.M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

704

C O N T - - - -

Stephen Flause
Deputy, Doug. Co.
Surveyors Office
Terrie Plouff
Karen Mosley
April 23, 1981
C.S. 61/19

(1/4 Cor. 26, 25)
"Douglas County Surveyor T26S R1W 1/4 S26 S25 1981"
Possible orig. stone is reset on the west side of the brass cap monument.
New BT's -An 11" DBH yew tree bears N.17°E., 38.4 ft. scribed "1/4 S25
CS BT" on dead barkless wood facing the corner.
An 8" DBH white fir bears S.21°W., 58.4 ft. scribed "1/4 S26 CS
BT" on a double blaze.
A 7" hemlock bears N.73°W., 50.8 ft. scribed "1/4 S26 CS BT" on a
double blaze.
No other suitable trees were available. All trees are tagged with DCSO
BT tags.

4/23/81

George E. Grubb
For: U. S. Forest
Service
May 1981
M 87 - 65 A & B

1/4 Corner for Sections 10 and 15.
Found - 11" x 9" x 5" basalt stone, firmly set, projecting 3" above the
ground marked "1/4" on the north face and "+" on top. (record
15" x 10" x 6")
Set - At the exact corner point set a 2" x 30" I.P. 24" in the ground
in a 3 ft. diam. mound of stone with a 3" brass cap marked:
T 26 S R1W 1/4 S10 S15 1981 LS 397.
New BTs- A 12" D. fir bears S.54°W., 14.6 ft. scribed 1/4 S15 BT.
A 13" hemlock bears N.63°W., 37.0 ft. scribed "1/4 S10 BT"
Set original corner stone alongside in mound of stone.

105

Center 1/4 Corner for Section 10
Set - 2" x 30" I.P., 30" in the ground in a 2 1/2 ft. diam. mound of
stone with a 2 1/2" brass cap marked: T26S R1W C 1/4 S10
1981 LS 397.
New BTs A 12" hemlock bears N.86°E., 46.4 ft. scribed "C 1/4 S10 BT"
A 10" hemlock bears N.25°W., 57.5 ft. scribed "C 1/4 S10 BT".

106

1/4 Corner for Secs. 10 and 11.
Set - 2" x 30" I.P. 22" in the ground in a 3 ft. diam. mound of stone with
a 3" brass cap marked: T26S R1W 1/4 S10 S11 1981 LS 397.
New BT's- A 18" D. fir bears S.40 1/2°W., 8.3 ft. scribed "1/4 S10 BT"
A 17" D. fir bears S.68°E., 10.2 ft. scribed "1/4 S11 BT".
5/81

107

Gregory Quibell
Deputy, Doug. Co.
Surveyors Office
Karen Reed
Aug. 30, 1982
C.S. 62/1

Section corner for Secs. 17, 18, 19 and 20
Found - Orig. 30" fir now 35" with good scar. I open and find scribed
"20".
Orig. stone not found.
I found no trace of other 3 BTs.
Set - Using record bearing and dist. from found orig. BT, N.82 1/2°W.,
66.0 ft., I SET a 1" x 30" I. pipe with brass cap attached 8"
into the ground along with an 18" high mound of stone 2 ft. wide
at the base. Cap is marked "Douglas Co Surveyor T26S S18 S17
S19 S20 R1W 1982".
New BTs - 26" fir scribed "BT CS T26S R1W S17" in double blaze reading from
bottom to top from uphill side of tree., bears N.5°E., 27.9 ft.
8" fir scribed "T26S R1W S19 CS BT" in double blaze bears
S.33°W., 58.1 ft.
10" maple scribed "T26S R1W S19 CS BT" in double blaze bears
S.70°W., 32.3 ft.

108

Maurice E. Farr
L.S. #1181
For: U.S. Forest
Service
Jan. 13, 1984
C.S. 62/15

1/4 Corner for Sec. 13 only of T.26-2
Found - 3" diam. brass cap firmly set, buried 4" in ground, properly mkd.
set by D. Garrett, 1972. Rep. #60
13" D. fir, S.2°W., 128.5 ft. with healed double blaze.
A steel fence post projecting 4 ft. above ground, N.3°W., 5.0 ft.
with U.S.F.S. signs #54.2 and #54.4 attached.
New Accessories: (No suitable trees in S.13)
A 6" D. fir, N.77°E., 116.5 ft. mkd. "X BT" on a single blaze.
N.E. corner of Butler's 2-story log house (appx. dimensions of
24 ft. x 40 ft.) bears S.18 1/2°W., 180.2 ft.
Note: Corner is 1 ft. east of 3'x6'x6' high boulder (recently moved to this
location) & is 18 ft. east of 30 ft. diam. pond. To locate, drive up USFS
Rd. #4710-021 to gate, thence north apprx. 300 ft. to corner.

8/30/82 109

RE-RENEWED, SEE CORNERS NO. #119

j/13/84