

Douglas County Surveyor's Record of  
Government Corners Renewed

T 26

T. S.

R 1

R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

110

Section corner for Secs. 13 and 24 only. OF T26-2W

Found - 1963 Douglas Co. brass disk on a 1" I.P. protruding 15" above ground in a 2 ft. dia. mound of stone, cap properly mkd.

Ren. #5

A 16" x 10" x 8" stone found with 3 notches possible on one edge. (per 1910 resurvey)

6" now a 23" D. fir with a double well healed blaze bears N.67°W., 9.2 ft. (orig.)

10" now a 21" D. fir with one chopped out and rotted blaze. no scribing visible and a double well healed blaze bears S.27°W 7.9 ft. (orig.)

9" now a 10" D. fir with a single well healed blaze bears S.63°W., 11.4 ft. (Ren. #5)

New BT - 8" hemlock double blazed and scribed "T26S R2W S13 CS BT" bears N.9 1/2°W., 16.5 ft.

Corner lies approx 100 ft. north of Hwy 138 on a south slope.

11/26/84

111

Section Corner for Sections 5, 6, 7 and 8.

Found - 1970 County brass cap protruding 12" above ground. Ren. #47

A 15" x 8" x 7" stone with 5 marks found on one edge. (Rec. 18" x 8" x 7" stone with 5 marks on south and east edges orig. and an "X" on top found per Ren. #47) lays along northeast edge of I.P.

Orig BT, a 6" now 10" dia. 3 1/2 ft. high rotted D. fir stump scribing found in previously opened blaze " / 5" bears N.33°E., 57.7 ft. (Rec. N.33°E., 57.4 ft. dist. to face of blaze.)

Orig. BT, a 40" now 67" dia. D. fir with a fully healed single blaze bears S.53°E., 83.2 ft. (agrees with record).

Orig. BT, a 18" now 46" dia. D. fir with a fully healed single blaze bears S.6°W., 71.3 ft. (Rec. S.4 1/2°W., 71.3 ft.)

No evidence of NW BT found.

18" now 17" dia. 40 ft. high D. fir snag with a partially healed single blaze scribing visible "T26S R1W S6 CS BT" bears N.49°W., 14.2 ft. Ren. #47

12" now 13" dia. D. fir with a fully healed single blaze bears N.17°E., 13.7 ft. Ren. #47

14" now 17" dia. D. fir with a fully healed single blaze bears S.67°E., 6.6 ft. Ren. #47

6" now 6" dia. dead D. fir with a fully healed single blaze bears S.20°W., 18.7 ft. Ren. #47

New BT - 10" dia. D. fir double blazed and scribed "T26S R1W S6 CS BT" bears N.9°W., 49.0 ft.

Corner lies on level ground.

1/15/86

112

1/4 Corner for Section 6 only of T.26-1E.

Found - Original GLO 1928 brass cap, properly marked, on 1" dia. iron pipe, is firmly set, projecting 10" above the ground.

A roothole bears N.25°E., 28.4 ft. with decayed log along side, size indeterminate, with no marks visible.

A decayed stump, size indeterminate, , bears S.18°E., 13.9 ft. with no marks visible.

New BTs - A 10" W. fir bears N.73°E., 25.5 ft. scribed "1/4 S6 BT" on a single blaze with a 3/4" brass washer, stamped "LS 1181" nailed flush to base of blaze.

A 5" W. fir bears S.18°E., 16.6 ft. scribed "XBT" on a single blaze with a 3/4" brass washer, stamped "LS 1181" nailed flush to base of blaze.

I set a 6 ft. long alum. post, driven 2 ft. in the ground, as a guard post, bears North, 2.0 ft. with Forest Service sign #54-4 attached.

Declination is 18° East. To reach corner drive 1.4 miles up forest road #4712-010, thence approx. 400 ft. West.

Randall W. Smith  
Stephen J. Flause  
Doug. County Surveyors  
Office, Deputies  
November 26, 1984  
C. S. 62/21

Douglas County  
Surveyors Office  
Deputies:  
Randall Smith  
Stephen Flause  
January 15, 1986  
C.S. 62/31

Maurice E. Farr  
LS #1181  
For. U.S. Forest  
Service  
Nov. 1986  
C.S. 62/33