

Douglas County Surveyor's Record of
Government Corners Renewed

T 26

T. S.

R 1

R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97301

Section corner for 1 and 12 only, T.26-2

113

Found - 1961 County brass cap on a 1" I.P. surrounded by a small mound of stones, protrudes 12" above ground. Cap mkd. with "1/4"-4" now 15" dia. D. fir with a fully healed single blaze bears N.33°W., 21.5 ft. (Agrees with M47-7, 1910 resurvey and Ren. #25 in T.26-2 distance is 20.5 ft.) Orig. BT.

36" now root hole with a tipped out 36" dia. D. fir that has a fully healed single blaze, root hole bears S.72°W., 29.0 ft. (Agrees with record) 1910 resurvey BT.

U.S.F.S. witness post and sign bears South, 5.3 ft. previously unrecorded, source unknown.

Set - We removed "1/4" from brass cap and build up a 2 ft. dia. 1 ft. high mound of stone.

New BTs- 14" dia. R. cedar double blazed and scribed "T26S R2W S1 CS BT" bears N.58°W., 26.2 ft.

4" dia. R. cedar double blazed and scribed "X BT" bears S.48 1/2°W., 31.2 ft.

Corner lies at southeast corner of a new clear cut.

114

Closing Corner for Sections 6 and 7 only. (From 1910 orig., Mensch)

From the 1910 Mensch retracement:

Found - An original 16x12x12 in. basalt stone (now measuring 7x12x2 in. high on portion protruding from ground. Because of severe frost cracking, we do not remove stone to examine further.

From Garrett survey M47-7:

Found - On the east edge of above stone is a 1/2" I.D. I.P. protruding 3" above ground.

(Bearings and distances measured from 1/2" I.D. iron pipe)

Found - From 1910 retracement, a madrone, 6" dia. now a 9" DBH madrone bears S.25°E., 18.9 ft. dist. as per record. No evidence found of scribing in previously opened blaze. No evidence found of northeast chinquapin BT.

New Accessories: We add new closing corner from Garrett survey M47-7., a 3" dia. brass cap on a 2" I.D. I.P. protruding 8" above ground bears East, 12.04 ft. dist. as per M 47-7. We also tie south-east bearing tree for the above mentioned cap:

Originally an 11" fir scribed T26S R1W S7 BT now a 13" DBH D. fir with a fully healed double blaze bears S.59°E., 42.5 ft.

A new bearing tree, a 15" DBH D. fir scribed CC, T26S R1W S6 CS BT on a double blaze bears N.55°E., 14.6 ft.

Monument is at east edge of old clear cut on a still definite north south cutting line and is south approx 350 ft. from a creek coursing N.75°E.

AND

Closing Corner for Sections 6 and 7 only, from Ren. #65

Found - A 3" dia. brass cap mkd. T26S R2W S12 S6 S7 1972 RPLS 544 on a 2" I.D. I.P. firmly set and protruding 8" above ground.

13" fir now a 15" DBH D. fir with a fully healed double blaze bears N.6°E., 10.1 ft. dist.

An 11" Fir now a 13" DBH D. fir with a fully healed double blaze bears S.48 1/2°E., 32.8 ft.

A USFS metal witness sign and post bears South, 4.5 ft. previously unrecorded.

New Accessories: We add original 1910 closing corner as set by Mensch!

This closing corner is monumented by the original 16x12x12 basalt stone, now a broken 12x7 in. stone protruding 2" above ground with no marks visible (We do not disturb) and by Garrett's 1/2" I.D. iron pipe on east edge of stone protruding approx. 3" above ground. This I.P. bears West, 12.04 ft. from brass cap monument. (agrees with record bearing and dist. from M47-7)

Monument is on east edge of old clear cut on a still definite north-south cutting line and is south approx. 350 ft. from a creek coursing N.75°E.

4/19/87

Douglas County Surveyors Office
Stephen John Flause Deputies
R. W. Smith
April 19, 1987
C.S. 62/40