

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 T. S. R 1 R. W. W. M.

FORE-CHAPMAN CO., EUGENE, ORE. 97401

CONT. - - - -

118

Douglas County Surveyors
Office - Randall Smith
Stephen Flause
April 5, 1991
C.S. 64/13

New BTs - 5" dia. D. fir, double blazed and scribed "1/4 S12 CS BT"
bears S.4°E., 13.3 ft.
28" dia. sugar pine, double blazed and scribed "1/4 S12 CS BT"
bears s.68°E., 18.5 ft.
5" dia. chinquapin, double blazed and scribed "1/4 S1 CS BT"
bears N.86½°E., 13.9 ft.
17" dia. D. fir double blazed and scribed "1/4 S1 CS BT"
bears N.44½°W., 18.4 ft.

4/5/91

119

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
Feb. 3, 1992
C.S. File 64/23

East 1/4 Corner Section 13 only of T.26-2
Found - 3" dia. brass cap 4" below ground. Ren. #60
8" now 16" dia. D. Fir down and out of position (to be cut up) with
a fully healed double blaze, root hole bears S.2°W., 128.5 ft.
(agrees with record. Ren. No. 60)
Steel fence post with U.S. Forest Service sign, bears N.0½°E.,
5.0 ft. (Rec. N.3°W., 5.0 ft.) Ren. No. 60
6" now 9" dia. D. Fir with a fully healed single blaze, bears
N.81°E., 116.5 ft. (Rec. N.77°E., 116.5 ft.) Ren. No. 109
NE corner of two story log cabin bears S.22½°W., 180.2 ft. (Rec.
S.18½°W., 180.2 ft.) Ren. No. 109

New Accessories:

3" dia. Holly tree, we did not blaze or scribe, in yard, bears
S.14½°W., 106.6 ft. No tags put on tree.
12" dia. Willow tree, we did not blaze or scribe, in yard, bears
N.5½°E., 33.2 ft. No tags put on tree.
SE corner of an old 20' x 20' log cabin bears N.25 3/4°W.,
183.3 ft. Cabin not set on permanent foundation.

Corner is 1 ft. East of a 3'x6'6" high boulder and 18 ft. East of a small
pond. Corner is at edge of yard. Owner did not want trees scribed. New
BTs are only ones of their kind near corner.

2/3/92

120

Mark Smalley
LS #2354
For: Roseburg Forest
Products.
Jan. 21, 1992
C.S. File 63/138

1/4 Corner Section 7 and 18
Found - Brass cap marked "T26S R1W ½ S7, S18, 1972, RPLS 544". Ren. #62
High Fir stump bears N.54 3/4°W., 11.9 ft. with alum. tag.
High Fir stump bears S.46½°E., 6.2 ft. with alum. tag.
New BT - 20" Fir stump with nail in the top bears S.88°W., 20.0 ft.
Corner in recent clearcut off the 4710-074 Road.

1/21/92

121

East ¼ Corner for Section 36 only, T.26-2
Found - 1" Iron Pipe, firmly set 10" above ground in a 2 ft. dia. mound
of stone with a 2½" Brass Cap properly marked.
50" D. Fir stump with healed blaze bears N.7°W., 15.3 ft.
41" D. Fir stump with healed blaze bears S.87°W., 32.3 ft.

New Accessories -

5" Fir with double blaze, upper scribed ¼ Sec 36, lower blaze
scribed BT with nail and washer stamped LS 839 and bears
S.41°W., 21.3 ft.

Set spike in center of 50" D. Fir stump which bears N.7°W., 15.3 ft.

Note - All bearing trees have a 6" red band painted around the trees and
the blaze face painted red. USFS sign 54-3, Bearing Tree, and
54-9, Land Surveying Monument, are nailed to all bearing trees.

122

Corner for Sections 24 & 25 only, T.26-2.
Found - 3" Iron Pipe firmly set 8" above ground with a 3½" Brass Cap
properly marked.
31" Cedar bears S.74°W., 19.1 ft with a partly healed lower blaze
and an open upper blaze with no scribing.
40" D. Fir stump bears N.7°W., 70.0 ft. with healed blaze.

New Accessories -

8" W. Fir with upper blaze scribed T26S R1W S30, lower blaze scribed
BT with brass washer stamped LS 839 bears S.21°E., 13.1 ft.

Note - All bearing trees have a 6" red band painted around the tree and
the blaze face painted red. USFS sign 54-3 'Bearing Tree' and
54-9 'Land Surveying Monument' are nailed to all bearing trees.

Don Bentz
For: U.S. Forest Service
July 19, 1993
C.S. File 63/153