

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

123

Don Bentz
For: US Forest Service
July 19, 1993
C.S. 63/153

Corner for Sections 25 & 36 only, T.26-2.

Found - 3" Iron Pipe, 12" above ground in a 24" mound of stone with a 3" Brass Cap properly marked.

40" Cedar bears S.84°W., 23.4 ft. with a partly visible scribing.

28" D.Fir with healed blazes was blown over. See Ren. # 13

New Accessories -

30" D.Fir with double blaze, upper scribed T26S R2W S25, lower blaze scribed BT with nail and washer stamped LS839 bears N.78°W., 42.8 ft.

Note - All bearing trees have a 6" red band painted around the tree and the blaze face painted red. USFS sign 54-3 'Bearing Tree' and 54-9, 'Land Surveying Monument' are nailed to all bearing trees.

124

Closing corner Sec. 30 & 31

Mon. Fd.- 2½" dia. brass cap on a 1½" O.D. iron pipe protrudes 12" above ground. (1967)

Note: 1967 DCSO BC/IP set in error. 1967 DCSO used a 1916 resurvey BT and a brg. & dist. from 1910.

No corner stone found

Bt's Fd.- Brg's & Dist. taken from 1967 DCSO BC/IP

44" now 49" dia. D.Fir, with a fully healed single blaze, bears N.38°E., 29.4' (rec. N.40°E., 32') (1967)

14" now 13" dia. Hemlock, with a partially healed single blaze scribing visible "26S R1W S31 CS BT", bears S.34°E., 34.7' (rec. S.32°E., 34.7') 1967

unhealed 12" now 17" dia. Hemlock, with a previously opened blaze scribing visible "Bt" facing N.70°W., bears S.30½°E., 15.2' (rec. from 1967 S.27°E., 15.2')

Note this is a BT marked in 1916 Mensch resurvey)

NOT A BT

8" now 10" dia. Hemlock, with a previously opened chopped out blaze, bears S.49 1/4°E., 30.9'. 1910 Bt scribing axed out in 1916.

Mon. Set- Brass cap from 1967 renewal is sawed off. I.P. now protrudes 8" above ground.

At a point determined from 1916 resurvey BT a 17" dia. Hemlock (S.70°E., 17.2') a 2 3/8" dia. brass cap on a 1 3/8" O.D. by 32" long iron pipe above ground. BC/IP is surrounded by a mound of stone.

New Accessories -

1967 1½" O.D. iron pipe, bears N.49¼°E., 10.7'

1967 13" Hemlock, bears S.51½°E., 35.1'

1967 49" D.Fir, bears N.41°E., 39.9'

Corner is at the bottom of a steep gully that courses west. Corner is in a old growth forrest.

see previous ren.# 70

DOUGLAS COUNTY
SURVEYORS OFFICE
RANDALL SMITH &
STEPHEN FLAUSE
JULY, 22, 1997
C.S. 64/75-30