

Douglas County Surveyor's Record of  
Government Corners Renewed

\* the words  
"at corner point"  
not in orig report  
"16605" se

26

T. S.

2

R. W. W. M.

FORE CHAPMAN CO., EUGENE, ORE. 94502

Section corner to secs. 14, 15, 22 and 23.

Found - 6 inch x 8 inch x 6 inch stone above ground with 2 notches on E. & 3 notches on S. and all BTs as recorded by Mench in 1916 & 1918. All BTs alive. N. E. BT shows scribe marks - Same for S.W. Laurel BT. All check for size, bearing, & distance. I also find orig. 12 inch (now 20 inch) Fir, S.70°W., 35.6 feet BT. - I do not open - shows good face. Set an iron pipe with brass cap at corner point alongside stone, mkd.

Sec.  $\frac{15}{22}$ / $\frac{14}{23}$  T26S R2W, County Surveyors Office, 1957.

Blaze and scribe:

16 inch Cedar, S.1°E., 128.4 feet mkd. S 23 T26S R2W, CS BT.

Note: Corner renewal requested by Lockwood, who will remove the S.E. BT.

10

63  
James W. Byron, Dep. Co. Surveyor.  
June 12, 1957.  
C. S. File No. 47/189.

FD CAP 4/13/92  
BLM  
e.s. 63/140

Section Corner to Sections 2 & 3.

Found - Corner Stone

3.5 ft. x 4' x 3' Rock - S. 20°E. 54 lks.

42" Fir - S.82°30'W. - 256 lks. - rescribed

Set - 38" Fir - S.45°E. 37.5 ft.

$\frac{1}{4}$  Corner to Sections 2 & 3.

Set -  $1\frac{1}{2}$ " Pipe in Mound of Stone

22" Fir - S. 71°W. - 9.5 ft.

10" Fir - N.67°E. - 10.5 ft.

Original Corner Not Found

Section Corner to Sections 2, 1, 12 & 11.

Found - 50" Fir - N.50°E. - 80 lks.

46" Fir - S.60°E. - 40 lks.

Set - 4" x 4' Post &

14" Fir - S.12°E. - 6.0 ft.

26" Fir - N.51°E. - 9.0 ft.

8" Fir - S.60°W. - 10.1 ft.

6" Fir - N.25°W. - 16.7 ft.

$\frac{1}{4}$  Corner to Sections 2 & 11

Set - Chev. Steering Column.

14" I. Cedar - N.42°W. - 19.2 ft.

36" Fir - S.50°E. - 4.7 ft.

Original Corner Not Found.

$\frac{1}{4}$  Section Corner to Sections 1 & 2.

Set -  $1\frac{1}{2}$ " Pipe in Mound of Stone

36" Fir - N.86°W. - 9.2 ft.

6" Fir - S.70°E. - 13.2 ft.

Original Corner Not Found.

Section Corner to Sections 1 & 2.

Found - 4" x 4' Post

22" Fir - S.44°E. 101 lks.

Set - 12" Fir - N.38°E. 18.5 ft.

12" Fir - S.12°W. 33.5 ft.

10" Fir - N. 04°W. 10.5 ft.

North  $\frac{1}{4}$  Corner to Section 2.

Found - Corner Stone

32" Fir = S.60°E. - 34 lks.

32" Fir - S.44°E. - 42 lks. - Rescribed

Set - 5" Fir - S.40°E. - 5.7 ft.

11

12

13

14

15

16

17

G. Robert Lecklider  
Surveyed for Mrs. Carl A. Messing  
July 6, 1959  
Map File M 11 - 31

RE-RENEWED, SEE CORNER NO. 1160

RE-RENEWED, SEE CORNER NO. #108