

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 2 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21891

Milo Godfrey
& Crew
3/29/63
C.S. File
No. 52/77

Corner to Secs. 13 and 24 only. 30
Found - Pile of Rocks at Cor.-chisel Mark "—" on one of them.
20" Fir N.67°W., not N.60°W., 9.2 ft., cut open & fd. good scribing.
20" Fir S.27°W., not S.14°W., 7.9 ft. opened & fd. old face
badly rotted. No scribing visible. This tree was opened
approx. 50 yrs. ago & looked as if scribing was chopped
off at that time.
No trace of Original N.E. and S. E. Trees.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
Pile Rocks around Cor. Office, 1965
New BT's: 9" D.Fir S.63°W. 11.4 ft. Mkd: T26S R2W S24 CS BT.
Rescribed: 20" D.Fir N.67°W. 9.2 ft. Mkd: T26S R2W S13 CS BT.
Corner lies approx. 130 ft. North of N. Umpqua Highway.

1/4 Corner to Sec. 13, T26-3W. & Sec. 18, T26-2W. 31
Found - Orig. 96", now 96" Fir Stub S.20°W. 14.5 ft., shows old axe
blaze with partial "S" scribe in bark.
No rock found at Corner. Very old blazes on trees both
N. & S. of Corner. No trace of other BT.
Set - 1" I.Pipe & Brass Cap Mkd: County Surveyor's Office, 1965
T26S R3W 1/4 S13/S18 R2W
New BT's: 10" Hemlock S.32°W. 9.3 ft. Mkd: 1/4 S13 CS BT.
7" Hemlock N.27°E. 18.9 ft. Mkd: 1/4 S18 CS BT.

Sec. Cor. to Secs. 18 & 19, T26-2W & 32
Secs. 13 & 24, T26-3W.
Found - Stone 4" x 12" x 15", firmly set, shows 2 notches on N. and
3 notches on S. edges.
17" Fir N.15°W. 7.3 ft., now stub, 5.0 ft. high, rotted &
burned, shows "T26SR3W S13 BT" scribe. Orig. N.E. BT O.K.
24" Fir S.84°E. 26.6 ft., record S.80°E. 20.5 ft., shows old
marks in bark, no scribe found, now snag.
24", now 28" Fir N.53°E. 78.8 ft., record 71.3 ft. Alive.
Open & shows scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T26S R3W S 13 | S 18
S 24 | S 19 R2W
Set Stone alongside Brass Cap.
New BT's: 6" D.Fir S.87°W. 13.1 ft. Mkd: T26S R3W S24 CS BT.
6" D.Fir N.74°W. 25.4 ft. Mkd: T26S R3W S13 CS BT.
No tree large enough to S. E.

1/4 Corner to Sec. 31, T26-2 and Sec. 36, T26-3W. 33
Found - Very old 4"x4" Sq. post scribed "S31" on E. & "1/4 S36" on W. face.
6", now 10" Cedar Stub 4' high, S. 83° W. 5.3 ft., Open &
shows part of "1/4" & all "S36 BT".
24", now 34" Fir, down, N. 50° E. 15.8 ft., shows scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
T26S R3W 1/4 S 36/S 31 R2W
New BT's: 5" D.Fir S. 47° E. 24.5 ft. Mkd: 1/4 S31 CS BT.
12" R. Cedar N. 9° W. 29.6 ft. Mkd: 1/4 S36 CS BT.

Sec. Cor. Secs. 30 & 31, T26-2W. & Secs. 25 & 36, T26-3 W. 34
Found - 26" D. Fir S. 45° E. 21.8 ft., prev. opened & shows "S" scribe.
No trace of S. W. BT. (Orig. BT)
No E. BT. possible rotted log laying in approximate location.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
T26S R3W S 25 | S 30
S 36 | S 31 R2W
New BT's: 6" D.Fir N. 61° E. 4.5 ft. Mkd: T26S R2W S30 CS BT.
6" D.Fir N. 5° W. 16.4 ft. Mkd: T26S R3W S25 CS BT.
7" D.Fir S. 37° W. 7.5 ft. Mkd: T26S R3W S36 CS BT.

Vernon "Ray" Tracy
M. Darby - J. Connel - G. McChesney
(Weyerhaeuser Co.)
June 1965
C. S. File No. 54/7

Vernon "Ray" Tracy
Mike Stone & Jerry Layne
Jan. 28, 1966
C. S. File No. 54/7

RE-RENEWED, SEE CORNER NO. #132

RE-RENEWED, SEE CORNER NO. 103

RE-RENEWED, SEE CORNER NO. #139

FD. OK
2/81
G. GRUBB
M 84-68