

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Vernon "Ray" Tracy
Jack Heritage & E. West
March 9, 1967
C.S. File No. 54/40

40

Sec. Corner to Secs. 35 & 36, T26-2W. and Secs. 1 & 2, T27-2W.

Found - No trace of Corner Stone.

Orig. 12", now 21" Fir, Alive, S. 30° W. 15.8 ft., prev. opened, face burned, fragmentary scribe visible.

Orig. 10", now 19" Fir, Alive, N. 39½° E. 11.9 ft., prev. opened, Open all of upper blaze & fine "T26S R2WS36" scribe.

Orig. 24", now 30" Fir, Alive, N. 30° W. 34.3 ft., shows good scar.

Orig. BT. N. 11° W. 9.2 ft., obliterated by Mensch, 1916, Alive & opened to axe blaze.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967

T 26S	S 35	S 36
T 27S	S 2	S 1

New BT's: 16" D. Fir S. 79½° E. 88.7 ft. mkd. T27S R2W S1 CS BT.

14" D. Fir N. 4° E. 6.0 ft. mkd. T26S R2W S36 CS BT.

18" D. Fir S. 19° W. 19.7 ft. mkd. T27S R2W S2 CS BT.

No trace of any other Orig. BT's.

41

¼ Corner to Sections 27 and 34.

Found - 1916 GLO Brass Cap in good condition & properly mkd.

* 16", now 18" Hemlock S. 10° E. 4.6 ft. Alive, healed blaze, we do not open.

* 10", now 16" Hemlock, N. 17° W. 10.6 ft. Alive, chopped open several years ago, shows "¼ S27 BT" scribe, face beginning to rot.

New BT's: * 14" Hemlock N. 51° E. 15.4 ft. mkd. ¼ S27 CS BT.

Note - The N.W. corner of Shivigny Mt. Lookout Tower bears S. 25° E.

The N.W. BT. marked in 1916 is also a BT. mkd. in 1909 by Gibbs & still shows scribe marks. Gibbs other BT. is now broken stump.

* New Stumps
Per R. Geisler
6/63
M 91-80

42

¼ Corner to Sections 30 and 31.

Found - Orig. 6", now 8" Laurel, Alive, N. 27° W. 4.6 ft., prev. opened & shows "T" & frag. scribe on badly rotted blaze.

No trace of SW. BT., call on creek to E. fits good.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967

T 26 S	R 2 W
¼ S 30	
¼ S 31	

New BT's: 12" D. Fir S. 40° W. 8.3 ft. mkd. ¼ S 31 CS BT.

16" Hemlock (Schoolmarm) N. 31° E. 16.2 ft. mkd. ¼ S30 CS BT.

Note - This corner lies on moderate N.E. slope of small rounded spur sloping N.W.

43

Section Corner to Sections 27 - 28 - 33 --34. FD. OK 7/99 BY D. EDWARDS
C.S. 65/25-4

Found - No trace of Corner Stone.

Orig. 10", now 22" Hemlock (Record called for Fir, N. 29° E.) N. 25° E. 17.2 ft., alive, scribe visible on previously opened blaze.

Orig. 20", now 25" Cedar, S. 78° E. 13.2 ft., alive, shows scribe on previously opened blaze.

Orig. 5", now 7" cedar, down, (called for Fir), S. 78° W. 17.8 ft. Open & find scribe & reverse.

Orig. 18" Cedar, now down, N. 29° W. 15.2 ft., shows scribe on unhealed blaze.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967

T26S	R2W
S 28	S 27
S 33	S 34

New BT's: 10" Hemlock N. 67° W. 10.0 ft. mkd. T26S R2W S28 CS BT.

9" Hemlock S. 46° W. 7.7 ft. mkd. T26S R2W S33 CS BT.

Orig. 25" Cedar S. 78° E. 13.2 ft., rescribed T26S R2W S34 CS BT.

Orig. 22" Hemlock N. 25° E. 17.2 ft. rescribed T26S R2W S27 CS BT.

FD. OK
6/63
R. GEISLER
M 91-80

Koke

44

¼ Corner to Sections 20 and 29.

Found - Unrecorded ¾" I. Rod which bears S. 4½° E. 9.6 ft. from true corner.

Orig. 10", now 22" Cedar, down & burned, N. 21° E. 15.8 ft., no scribe found.

Orig. 8", now 16" Fir Snag, S. 38° E. 7.9 ft., Open & find "¼ S" scribe.

(continued over)