

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21801

(continued)

Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S R 2 W
Office $\frac{1}{4}$ $\frac{S}{S}$ $\frac{20}{29}$

New BT's: 9" D. Fir N. 56° W. 47.8 ft. mkd. $\frac{1}{4}$ S20 CS BT.
15" Cedar S. 33° W. 94.9 ft. mkd. $\frac{1}{4}$ S29 CS BT.

Note - This area logged off & grown up to dense greasewood brush.
Corner on gentle S.E. slope approx. 200 ft. E. of logging road.

$\frac{1}{4}$ Corner to Sections 19 and 20. 45

Found - Orig. 20", now 32" Fir, N. 86 $\frac{1}{4}$ ° W. 33.7 ft., alive, Open &
find "B" scribe.

No trace of Maple to S.E.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S R 2 W
Office, 1967 $\frac{1}{4}$ S 19/ S 20

New BT's: Rescribed Orig. 32" D. Fir N. 86 $\frac{1}{4}$ ° W. 33.7 ft. mkd. $\frac{1}{4}$ S19 CS BT in bark.
40" D. Fir N. 54° E. 31.7 ft. mkd. $\frac{1}{4}$ S20 CS BT in bark
12" Hemlock N. 77° E. 69.7 ft. mkd. $\frac{1}{4}$ S20 CS BT. (corner

Note - This corner lies on very steep northerly slope. (No trace of stone.)

Section Corner to Sections 19 - 20 - 29 - 30. 46

Found - Orig. 6"x11"x14" Corner Stone mkd. with 5 notches on E. &
2 notches on S. edges.

Orig. 4", now 17" Laurel, S. 63° E. 39.6 ft., Alive. We open,
center rotted, no scribe.

Orig. 4", now 15" Maple S. 18° W. 34.3 ft. Alive, showed scar,
we open, center rotted, no scribe, bearing S.B. S. 13° W.

Orig. 4", now 16" Laurel, N. 6° W. 28.4 ft. Alive, we open,
center rotted, no scribe.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S R 2 W
(in place of Office S 19 | S 20
Corner Stone) 1967 S 30 | S 29

New BT's: 9" Laurel S. 12° E. 28.0 ft. mkd. T26S R2W S29 CS BT.
8" Chinquapin S. 52° W. 13.9 ft. mkd. T26S R2W S30 CS BT.
9" Chinquapin N. 49° W. 34.3 ft. mkd. T26S R2W S19 CS BT.
16" Pine N. 76° E. 31.4 ft. mkd. T26S R2W S20 CS BT.

Note - This corner lies on moderate S. E. slope.

$\frac{1}{4}$ Corner to Sections 29 and 30. 47

Found - Orig. Corner Stone 7"x8"x10", firmly set & faint " $\frac{1}{4}$ " on W.

Orig. 12", now 20" Cedar, S. 58° E. 3.3 ft. (face) Alive, shows
good scar; do not open.

Orig. 10", now 21" Cedar, N. 82° W. 17.2 ft. (face) Alive,
prev. opened & shows " $\frac{1}{4}$ S30 BT" scribe & we find chips with
reverse scribe on ground.

Set - Brass Cap at Cor. Mkd: County Surveyor's T26S R2W
(Reset Cor. Stone alongsd) Office, 1967 $\frac{1}{4}$ S 30/S 29

New BT's: 10" Hemlock N. 70° W. 21.1 ft. mkd. $\frac{1}{4}$ S30 CS BT.
7" Hemlock N. 55° E. 21.2 ft. mkd. $\frac{1}{4}$ S29 CS BT.

Note - This corner lies on moderate S.E. slope approx. 400 ft. N. of
power line from river to top of Mt. along Bob Creek.

$\frac{1}{4}$ Corner to Section 19 and 30. 48

Found - Orig. Corner Stone 6"x9"x12" mkd. " $\frac{1}{4}$ " on N. face & firmly set.
A large stump hole bears S. 63° W. 10.0 ft. & a small stump
hole bears N. 40° E. 7.0 ft. These holes fit locations for
original BT's.

9" Laurel Snag, open & find "S19B" scribe & reverse, bears N. 89° E. 19.1 ft.
Orig. 10" Laurel S. 15° W. 20.9 ft., approx. ring count indicates
this tree mkd. 50-55 yrs ago, scribed " $\frac{1}{4}$ S30 BT"

Pacing from top of ridge to East this corner fits call good,
Old blazes found west.

Set - Brass Cap at Cor. Mkd: County Surveyor's T26S R 2 W
Office S 19
1967 $\frac{1}{4}$ S 30

(continued next page)

Vernon "Ray" Tracy
Jack Heritage & E. West
July, 1967
C.S. File No. 54/40

RENEWED CORNER NO. #104