

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell
Ed Monrean
C.S. File No. 54/40

Closing Corner to Sections 31 and 32, T25-2W. 98
Found - 21" Cedar N.67°E. 20.3 ft., some scribing visible. Ren. #54, T25-2.
25, now 28" Cedar, N.68°W. 27.8 ft., shows good scar.
4" Fir Post at Cor. Mkd: "C.C. S31 & S32"
Set - Brass Cap at C.C. Mkd: County Surveyor's Office 1972
T25S R2W
C.C.
S 31 | S 32
S 6
T 26 S

Bearing Trees O.K. and Tagged.

Section Corner to Sections 5 and 6 only. (North Bdry.) 97
Found - Corner Tree, Broken Stob.
24" D. Fir, now down, S.68°E. 49.5 ft., shows good scar.
14" D. Fir, now down, S.30°W. 23.8 FT.
Set - Brass Cap on Side of Corner Stump (14") Mkd: County Surveyor's Office, 1972
T25S R2W
S 32
S 6 | S 5
T 26 S

New BT's: 17" D. Fir N.14½°W. 8.6 ft. scribed T25S R2W S32 CS BT.
15" D. Fir S.75°W. 35.0 ft. scribed T26S R2W S 6 CSBT.

No trees too good to the S.W. because of Rock Bluff directly south of corner, approximately 15 ft. high.

7/3/72

¼ Corner, Sec. 18 only, T26-1. 98
Set - Brass cap marked T26S, R1W, ¼ S18, 1972, RPLS 544.
BT's - 14" Fir, bears N.32°E., 58.4' Scribed ¼ S18 BT.
13" Fir, bears S.21½°E., 60.2' Scribed ¼ S18 BT.

FOOK
DCSO
2/4/72
C.S. 64/23

¼ Corner, Section 13, only. 99
Set - Brass cap marked T26S, R2W, ¼ S13, 1972, RPLS 544. #130
BT's - 8" Fir, bears S.2°W., 128.5' Scribed ¼ S13 BT.
6 ft. Steel fencepost with U.S. Forest Service Signs Nos. 54-2 & 54-4, bears N.3°W., 5.0'.

Section Corner, Secs. 7 & 18 only, T26-1. 100
Set - Brass cap marked T26S, S7, S18, R1W, T26S R2W, S13, 1972, RPLS 544.
BT's - 8" Fir, bears N.52°E., 29.1' Scribed T26S R1W, S7, BT.
7" Fir, bears S.18½°E., 26.9' Scribed T26S, R1W, S18, BT.

Section Corner, Sections 6 & 7 only, T26-1. 101
Set - Brass cap marked, T26S, S6, S7, R1W, T26S, R2W, S12, 1972, RPLS 544. #138
BT's - 13" Fir, bears N.6°E., 10.1' Scribed T26S R1W S6 BT.
11" Fir, bears S.48½°E., 32.8' Scribed T26S R1W S7 BT.

Corner #2, Tract 37, Secs. 16 & 17. 102
Found - 1918 G.O. Brass cap buried in split
42" D. Fir, now stump, S.42°E., 59.4 ft. scribing cut off, part of face left.
New BT - 37" Maple, S.33°E., 43.3 ft. scribed 2 T37 CS BT.
Note - This initial point of Umpqua Village (not found by B. Barnes.)
NORTH
4/13/73

1/4 Corner for SEC. 18 and Sec. 13 of T26-3 103
Found - 1965 Douglas County Surveyor Brass Cap. Ren. #31
6" Cedar stub, N.27°E., 18.9 ft.
10" Hemlock snag, S.34°W., 9.4 ft.
Set - New R.P. trees:
8" Cedar, S.85°E., 23.5 ft
16" Cedar, S.65°W., 57.3 ft. (Dist. to form nail at base of tree)

United States of America
Don E. Garrett
M 47 - 7
October, 1972

John M. Powell
J. Heritage
4/13/73
C.S. File 56/25

Donald Peel
for Weyerhaeuser
Nov. 1974
M 54 - 76

RE-RENEWED, SEE CORNER NO. #130
RE-RENEWED, SEE CORNER NO. #138

RE-RENEWED, SEE CORNER NO. #135

Jan 1972

Jan 75