

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 T. S. R 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Corner for Secs. 19 and 30.

101

Found - 1967 County Surveyors Brass cap properly mkd. Ren. #48

An orig. corner stone 6"x9"x12" with 1/4 on North face along side.

A 9" Madrone snag N.89°E., 19.1 ft. is now down and apparently rotted.

A 10" Madrone now 11" S.15°W., 20.9 ft. with scribing 1/4 S30 CS BT visible.

A 10" Cedar, now 11", N.52°W., 10.9 ft. with scribing 1/4 S19 CS BT visible.

A 10" D.Fir, now 11", S.38°W., 16.6 ft. Is blown down, scribing visible.

New BT - A 12" D.Fir, S.30°E., 23.0 ft. scribed 1/4 S30 CS BT.

Corner lies on top of ridge south easterly of old clearcut head of stream.

2/25/75

Gary E. Commons
Peter L. Earle
County Surveyors Off
Feb. 25, 1975
C.S. 57/17

Section Corner for Secs. 17 and 18 only.

105

Found - A 1918 GLO brass cap properly stamped, in good condition.

A 36" now 38" Fir, bears N.k8°W., 46.2 ft. with healed blaze alive and well.

A 12" Fir snag, bears N.1°W., (Record N.4°W) 40.3 ft. with well healed blaze.

A 16" Fir, bears N.78°W., (rec. N.75°W) 35.6 ft. with well healed blaze. (See 1960 resurvey)

New BT - A 20" Red Cedar, bears S.24°W., 53.1 ft. marked "T26S R2W S19 CS BT" in a double blaze.

SEE ALSO WEYERHAEUSER NOTES C.S. 59/8

4/22/76

A. Victor Cangie
G. Langlitz
D. Stewart
April 22, 1976
C.S. 59/8

Vicinity of 1/4 Corner For Secs. 5 and 6.

Found - 12" Hemlock, scribing visible. N.42°E., 8.9 ft.

20" Swell butt Hemlock, scribing visible. S.46°E., 20.1 ft.

72" Fir, scribing visible. Put Weyerhaeuser plate at base of tree, tree to be felled. S.51°W., 7.3 ft.

30" Fir, N.46°W., 25.1 ft. Tree felled. Weyerhaeuser plate at base of stump.

Weyerhaeuser plates are marked with 1959 GLO distances & reciprocal bearings

NOTE: THE GLO 1/4 CORNER FOR SECS. 5 AND 6, A 1959 GLO BRASS CAP WITH 2 BT'S, IS SOUTH 4.00 CHAINS.

VISITED 4/19/76 - G. LANGLITZ - NOT VERIFIED AS ORIG. COR. C.S. 59/8 & C.S. 59/30

North 1/4 Corner for Sec. 6 only.

107

Found - 40" now 56" orig. Fir, bears S.32°E. (rec. S.31°E) 25.7 ft. to center of tree. Old healed face.

36" now 44" Fir bears S.54°W., 23.8 ft. to center of tree, lower face had been opened, now pitched over.

1967 Doug. Co. Brass cap. Ren. #67

7" now 8" Fir, down, bears S.32°W., 14.3 ft. to root hole, scribing and tag visible.

14" now 16" D. Fir bears S.54°E., 15.2 ft. to center of tree, scribing and tag visible.

New BT's - 56" Fir bears S.33°E., 22.7 ft. (orig. 1914 tree) with "W" nail and plate

44" Fir bears S.54°W., 21.8 ft. (orig. 1914 tree) with "W" nail and plate.

4/28/76

Frank O. Williams
by Glen McChesney
For: Weyerhaeuser
Co.
April 28, 1976
C.S. 58/8

Standard Corner Secs. 1 and 2.

108

Found - 22" down Fir, S.44°E., 67 ft.

12" Fir, N.38°E., 18.5 ft.

12" Fir, S.07°W., 33.5 ft. (Recorded S.12°W.)

10" Fir, N.04°W., 10.5 ft.

Set - 1" Aluminum pipe.

BT's - 20" Fir, S.75°E., 46.0 ft. to R.R. spike.

16" Fir, S.89°W., 21.1 ft. to R.R. spike.

10" Fir, N.04°W., 9.9 ft. to R.R. spike.

10/77

Lee Roberts
For: Weyerhaeuser Co.
Oct. 1977
M 67 - 61